

# BID SET FOR PROPOSED PERIMETER CENTER EAST PARK

50 PERIMETER CENTER EAST  
CITY OF DUNWOODY, GEORGIA 30346  
PARCEL ID: 18 347 01 027, 064, 018, & 024

**UTILITY/GOVERNMENTAL  
CONTACT LIST:**


**WATER COMPANY:**  
DEKALB COUNTY WATERSHED MANAGEMENT  
774 JORDON LANE, SUITE 200  
DECATUR, GA 30034  
PHONE: (404) 731-3562  
CONTACT: BARON SAUSSY

**POWER COMPANY:**  
GEORGIA POWER  
PHONE: (404) 506-6539

**SANITARY SEWER COMPANY:**  
DEKALB COUNTY WATERSHED MANAGEMENT  
774 JORDON LANE, SUITE 200  
DECATUR, GA 30034  
PHONE: (404) 731-3562  
CONTACT: BARON SAUSSY

**LOCAL ZONING OFFICE**  
CITY OF DUNWOODY  
PLANNING & ZONING DIVISION  
4800 ASHFORD DUNWOODY RD  
DUNWOODY, GA 30338  
PHONE: (678) 382-6700  
CONTACT:

**FIRE DEPARTMENT**  
DEKALB COUNTY FIRE AND RESCUE  
1950 WEST EXCHANGE PLACE  
TUKER, GA 30084  
PHONE: (678) 406-7750



**SITE LOCATION MAP**

NOT TO SCALE

**SHEET INDEX**

SHEET NO.	SHEET NAME	ISSUED	LATEST REVISION	COMMENT
C-0	COVER SHEET	1/7/2022		
	BOUNDARY AND TOPOGRAPHIC SURVEY	8/21/2020		
DE-1	DEMOLITION PLAN	1/7/2022		
ES-1	PHASE I EROSION SEDIMENTATION AND POLLUTION CONTROL PLAN	1/7/2022		
ES-2	PHASE II EROSION SEDIMENTATION AND POLLUTION CONTROL PLAN	1/7/2022		
ES-3	PHASE III EROSION SEDIMENTATION AND POLLUTION CONTROL PLAN	1/7/2022		
ES-4	EROSION SEDIMENTATION AND POLLUTION CONTROL NOTES	1/7/2022		
ES-5	EROSION SEDIMENTATION AND POLLUTION CONTROL NOTES	1/7/2022		
C-1	SITE PLAN	1/7/2022		
C-2	GRADING PLAN	1/7/2022		
C-3	UTILITY PLAN	1/7/2022		
PR-1	PROFILES AND TABLES	1/7/2022		
D-1A	SITE PLAN DETAILS	1/7/2022		
D-2A - D-2B	GRADING AND DRAINAGE DETAILS	1/7/2022		
D-3A	UTILITY PLAN DETAILS	1/7/2022		
D-4A-D-4C	EROSION SEDIMENTATION AND POLLUTION CONTROL DETAILS	1/7/2022		
L-1	OVERALL LANDSCAPE PLAN	11/1/2021		
L-2	ENLARGED LANDSCAPE PLAN	11/1/2021		
L-3	ENLARGED LAYOUT PLAN	11/1/2021		
L-4	LANDSCAPE DETAILS	11/1/2021		
L-5	ENLARGED PLAYGROUND PLAN	11/1/2021		
L-6	ENLARGED FITNESS STATION PLAN	11/1/2021		
L-7	TRAIL DESIGN PLAN	11/1/2021		
L-8	CITY STANDARD ENTRY SIGN	11/1/2021		
L-9	CITY STANDARD ENTRY SIGN	11/1/2021		
L-10	CITY STANDARD KIOSK	11/1/2021		
L-11	CITY STANDARD KIOSK & ENTRY SIGN	11/1/2021		
SP-1	OVERALL SPLASHPAD PLAN	11/1/2021		
SP-2	SPLASH PAD LAYOUT PLAN	11/1/2021		
SP-3	SPLASH PAD DIMENSION PLAN	11/1/2021		
SP-4	SPLASH PAD CROSS SECTION	11/1/2021		
SP-5	SPLASH PAD PUMP ROOM EQUIPMENT LAYOUT PLAN	11/1/2021		
SP-6	SPLASH PAD FEATURE DETAILS	11/1/2021		
SP-7	SPLASH PAD FEATURE DETAILS	11/1/2021		
SP-8	SPLASH PAD FEATURE DETAILS	11/1/2021		
SP-9	SPLASH PAD DETAILS	11/1/2021		
SP-10	SPLASH PAD DETAILS	11/1/2021		
SP-11	SPLASH PAD DETAILS	11/1/2021		
SP-12	SPLASH PAD DETAILS	11/1/2021		
SP-13	SPLASH PAD PIPING PLAN	11/1/2021		
SP-14	SPLASHPAD SCHEMATIC	11/1/2021		
A-1	SMALL PAVILION PLAN & DETAILS	11/1/2021		
A-2	LARGE PAVILION PLAN & DETAILS	11/1/2021		
A-3	PRECAST RESTROOM PLANS	11/1/2021		
A-4	PRECAST RESTROOM ELEVATIONS	11/1/2021		
A-5	PRECAST RESTROOM SECTIONS	11/1/2021		
A-6	PUMP HOUSE PLANS & DETAILS	11/1/2021		
A-7	PUMP HOUSE ELEVATIONS & SECTIONS	11/1/2021		
E-1	ELECTRICAL NOTES	11/1/2021		
E-2	OVERALL ELECTRICAL SITE PLAN	11/1/2021		
E-3	ELECTRICAL ENLARGED SITE PLANS	11/1/2021		
E-4	PUMP HOUSE POWER & LIGHTING PLANS	11/1/2021		
E-5	ELECTRICAL SCHEDULES & ONE-LINE	11/1/2021		
E-6	ELECTRICAL DETAILS	11/1/2021		

**DEVELOPER-**  
CITY OF DUNWOODY PARKS AND REC  
4800 ASHFORD DUNWOODY RD  
DUNWOODY, GA 30338  
678 382-6857 PHONE

**NOTES:**

1. THE SITEMARK FOR THIS PROJECT SHALL MEET OR EXCEED THE "STANDARD SITEMARK SPECIFICATIONS".
2. ALL NECESSARY INSPECTIONS AND/OR CERTIFICATIONS REQUIRED BY CODES AND/OR UTILITY SERVICE COMPANIES SHALL BE PERFORMED PRIOR TO ANNOUNCED BUILDING POSSESSION AND THE FINAL CONNECTION OF SERVICES.


**ENGINEER-**



6745 Sugarloaf Parkway, Suite 100  
Duluth, GA 30097  
770.447.8999 . www.chacompanies.com



Know what's below.  
Call before you dig.



GSWCC# 10882  
EXP: 05/24/2024

Project Title  
PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOODY RD  
DUNWOODY, GA 30338

Project Developer  
CITY OF DUNWOODY  
4800 ASHFORD DUNWOODY RD  
DUNWOODY, GA 30338

SHEET NUMBER


**C-0**

**NOTES**


1. THE UNDERGROUND UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND EXISTING DRAWINGS. THIS SURVEYOR MAKES NO GUARANTEE THAT THE UNDERGROUND UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UNDERGROUND UTILITIES SHOWN ARE IN THE EXACT LOCATION INDICATED. ALTHOUGH HE DOES CERTIFY THAT THEY ARE LOCATED AS ACCURATELY AS POSSIBLE FROM INFORMATION SUPPLIED AND TO THE SURVEYOR'S BEST KNOWLEDGE ARE APPROXIMATELY AS SHOWN. THE SURVEYOR HAS NOT PHYSICALLY LOCATED THE UNDERGROUND UTILITIES.
2. I HAVE EXAMINED THE FEDERAL EMERGENCY MANAGEMENT AGENCY FLOOD INSURANCE RATE MAP FOR DEKALB COUNTY, GEORGIA AND INCORPORATED AREAS, COMMUNITY PANEL NUMBER 13089C00121, PANEL 12 OF 201, EFFECTIVE DATE MAY 16, 2013 AND FOUND A PORTION OF THE PROPERTY SHOWN HEREON TO FALL WITHIN A DESIGNATED FLOOD ZONE "A" (AREAS OF 100 YEAR FLOOD).
3. THE ORTHOMETRIC HEIGHTS (ELEVATIONS AND CONTOURS) SHOWN HEREON WERE DETERMINED BY GPS OBSERVATIONS AND WERE ADJUSTED BY PLANNERS AND ENGINEERS COLLABORATIVE IN SEPTEMBER 2017. NORTH AMERICAN DATUM OF 1983 (NAD83), NORTH AMERICAN VERTICAL DATUM OF 1988 (NAVD88), GEORGIA WEST ZONE STATE PLANE COORDINATES.
4. THE TERM "CERTIFICATION" RELATING TO PROFESSIONAL ENGINEERING AND LAND SURVEYING SERVICES SHALL MEAN A SIGNED STATEMENT BASED UPON FACTS AND KNOWLEDGE KNOWN TO THE REGISTRANT AND IS NOT A GUARANTEE OR WARRANTY, EITHER EXPRESSED OR IMPLIED.
5. THIS SURVEY HAS BEEN PREPARED WITHOUT THE BENEFIT OF A CURRENT TITLE INSPECTION REPORT. EASEMENTS OR OTHER ENCUMBRANCES MAY EXIST ON PUBLIC RECORD BUT NOT BE SHOWN HEREON.
6. THE UNDERGROUND UTILITIES SHOWN HEREON WERE DETERMINED BY LOCATING PAINT MARKINGS CREATED BY OTHERS.
7. NO ZONING INFORMATION PROVIDED FOR BUILDING SETBACKS.

**REFERENCES**

1. ALTA/ACSM LAND TITLE SURVEY FOR METLIFE REAL ESTATE INVESTMENTS, DATED 06/15/00, LAST UPDATED 05/13/04, PREPARED BY WATTS & BROWNING ENGINEERS, INC, SIGNED AND SEALED BY A. HAMMOND, PROFESSIONAL LAND SURVEYOR IN THE STATE OF GEORGIA, LICENSE NUMBER 2554.
2. FINAL PLAT FOR TOWNSEND AT PERIMETER, PREPARED BY PLANNERS & ENGINEERS COLLABORATIVE, DATED DECEMBER 29, 2016, RECORDED IN PLAT BOOK 2537 PAGE 97 AT SUPERIOR COURT OF DEKALB COUNTY, GEORGIA, SIGNED AND SEALED BY REGISTERED LAND SURVEYOR IN THE STATE OF GEORGIA, JONATHAN N. HOWARD, PROFESSIONAL LICENSE NUMBER 3008.



DETAIL 1 - N.T.S.



DETAIL 2 - N.T.S.

**LEGAL DESCRIPTION - TRACT 1**

ALL THAT TRACT OR PARCEL OF LAND lying and being in Land Lot 347 of the 18th District of DeKalb County, City of Dunwoody, Georgia, and being more particularly described as follows:

To find the TRUE POINT OF BEGINNING, COMMENCE at the intersection of the easterly land lot line of Land Lot 347 and with the northwesterly right of way of U.S. Interstate Highway 285 and proceed northerly 1266 feet more or less along said land lot line of Land Lot 347 to a 1 inch crimp top pipe found, said point being the TRUE POINT OF BEGINNING;

With the TRUE POINT OF BEGINNING thus established, thence leaving said easterly land lot line of Land Lot 347 and proceed North 85 degrees 28 minutes 55 seconds West, a distance of 421.14 feet to an iron pin set on the easterly right of way of Perimeter Center East (variable right of way); thence along said easterly right of way of Perimeter Center East 73.48 feet along an arc of a curve to the left, said curve having a radius of 659.62 feet and a chord bearing and distance of North 04 degrees 13 minutes 17 seconds East 73.44 feet to an iron pin set; thence leaving said easterly right of way of Perimeter Center East and proceed along the common property line between City of Dunwoody and S & F Activities, LLC the following courses and distances: South 85 degrees 37 minutes 45 seconds East, a distance of 266.62 feet to a 1/2 inch rebar found; North 08 degrees 17 minutes 41 seconds East, a distance of 115.72 feet a 1/2 inch rebar found; North 25 degrees 40 minutes 27 seconds West, a distance of 57.22 feet an iron pin set; thence leaving said common property line between City of Dunwoody and S & F Activities, LLC and proceed common property line between City of Dunwoody, South 85 degrees 53 minutes 17 seconds East, a distance of 193.26 feet to an iron pin with cap found; thence along common property line between City of Dunwoody and Dickie L. Slack, etal South 08 degrees 36 minutes 39 seconds West, a distance of 241.03 feet to a 1 inch crimp top pipe found, said pipe being the TRUE POINT OF BEGINNING.

Containing 1.348 acres.

**LEGAL DESCRIPTION - TRACT 2**

ALL THAT TRACT OR PARCEL OF LAND lying and being in Land Lot 347 of the 18th District of DeKalb County, City of Dunwoody, Georgia, and being more particularly described as follows:

To find the TRUE POINT OF BEGINNING, COMMENCE at the intersection of the easterly land lot line of Land Lot 347 and with the northwesterly right of way of U.S. Interstate Highway 285 and proceed northerly 1266 feet more or less along said land lot line of Land Lot 347 to a 1 inch crimp top pipe found; thence North 08 degrees 36 minutes 39 seconds East, a distance of 241.03 feet to an iron pin with cap found, said point being the TRUE POINT OF BEGINNING;

With the TRUE POINT OF BEGINNING thus established, thence leaving said easterly land lot line of Land Lot 347 and proceed North 85 degrees 53 minutes 17 seconds West, a distance of 193.26 feet to an iron pin set; thence along the common property line between City of Dunwoody and S & F Activities, LLC North 25 degrees 40 minutes 27 seconds West, a distance of 240.68 feet to a 1/2 inch rebar found on the southerly right of way of Perimeter Center East Extension (variable right of way); thence along said southerly right of way of Perimeter Center East Extension the following courses and distances: North 66 degrees 18 minutes 42 seconds East, a distance of 316.12 feet to an iron pin with cap found; North 71 degrees 52 minutes 56 seconds East, a distance of 50.25 feet to an iron pin with cap found; North 66 degrees 10 minutes 20 seconds East, a distance of 80.96 feet to a 1/2 inch rebar found; thence leaving said southerly right of way of Perimeter Center East Extension and proceed along the common property line between City of Dunwoody and BBK Coke Data Center, LLC the following courses and distances: South 07 degrees 36 minutes 35 seconds East, a distance of 104.53 feet to a small metal fence post found; South 27 degrees 19 minutes 10 seconds East, a distance of 55.94 feet to a point; South 06 degrees 13 minutes 45 seconds West, a distance of 40.76 feet to a point; South 20 degrees 16 minutes 14 seconds East, a distance of 173.37 feet to a point; thence along common property line between City of Dunwoody and Dickie L. Slack, etal the following courses and distances: South 01 degrees 14 minutes 16 seconds West, a distance of 21.30 feet to a point; thence North 89 degrees 27 minutes 23 seconds West, a distance of 204.39 feet to an iron pin set; thence South 08 degrees 36 minutes 39 seconds West, a distance of 30.64 feet to an iron pin with cap found, said pin being the TRUE POINT OF BEGINNING.

Containing 2.989 acres, more or less.


**LEGAL DESCRIPTION - TRACT 3**

ALL THAT TRACT OR PARCEL OF LAND lying and being in Land Lot 346 of the 18th District of DeKalb County, City of Dunwoody, Georgia, and being more particularly described as follows:

To find the TRUE POINT OF BEGINNING, COMMENCE at the intersection of the easterly land lot line of Land Lot 347 and with the northwesterly right of way of U.S. Interstate Highway 285 and proceed northerly 1266 feet more or less along said land lot line of Land Lot 347 to a 1 inch crimp top pipe found; thence North 08 degrees 36 minutes 39 seconds East, a distance of 241.03 feet to an iron pin with cap found; thence leaving said easterly land lot line of Land Lot 347 and proceed along tie-in line North 46 degrees 48 minutes 33 seconds East, a distance of 99.77 feet to a point, said point being the TRUE POINT OF BEGINNING;

With the TRUE POINT OF BEGINNING thus established, thence along common property line between City of Dunwoody and Dickie L. Slack, etal South 89 degrees -6 minutes 50 seconds East, a distance of 169.60 feet to a point on the westerly right of way of Old Georgetown Center (60 foot right of way); thence along said westerly right of way of Old Georgetown Center the following courses and distances: South 09 degrees 18 minutes 12 seconds West, a distance of 102.89 feet to a point; South 08 degrees 44 minutes 41 seconds West, a distance of 100.00 feet to a point; South 09 degrees 07 minutes 34 seconds West, a distance of 100.00 feet to a point; thence South 09 degrees 10 minutes 12 seconds West, a distance of 100.00 feet to the point; 93.14 feet along an arc of a curve to the left, said curve having a radius of 487.88 feet and a chord bearing and distance of South 05 degrees 41 minutes 45 seconds West 93.00 feet to a point; 92.13 feet along an arc of a curve to the left, said curve having a radius of 495.40 feet and a chord bearing and distance of South 02 degrees 40 minutes 58 seconds East 92.00 feet to a point; South 06 degrees 49 minutes 16 seconds East, a distance of 113.59 feet to a 1/2 inch rebar found; thence leaving said westerly right of way line of Old Georgetown Center and proceed along the northerly right of way of Lincoln Parkway East (60 foot right of way) South 86 degrees 21 minutes 28 seconds West, a distance of 98.31 feet to a point; thence leaving said northerly right of way of Lincoln Parkway North 05 degrees 29 minutes 45 seconds West, a distance of 35.60 feet to a point; 6.04 feet along an arc of curve to the right, having a radius of 25.00 feet and chord bearing of North 01 degrees 25 minutes 39 seconds East a distance of 6.03 feet to a point; thence North 08 degrees 21 minutes 03 seconds East, a distance of 34.08 feet to a point; thence North 22 degrees 44 minutes 20 seconds West, a distance of 20.24 feet to a point; thence North 33 degrees 48 minutes 28 seconds West, a distance of 7.84 feet to a point; 15.52 feet along an arc of curve to the right, having a radius of 25.00 feet and chord bearing of North 16 degrees 01 minutes 08 seconds West a distance of 15.28 feet to a point; thence North 01 degrees 46 minutes 13 seconds East, a distance of 4.52 feet to a point; thence North 20 degrees 49 minutes 49 seconds West, a distance of 36.32 feet to a point; thence North 17 degrees 52 minutes 28 seconds West, a distance of 50.19 feet to a point; 5.89 feet along an arc of curve to the right, having a radius of 25.00 feet and chord bearing of North 11 degrees 07 minutes 21 seconds West a distance of 5.88 feet to a point; thence North 04 degrees 22 minutes 14 seconds West, a distance of 52.39 feet to a point; thence North 18 degrees 40 minutes 24 seconds West, a distance of 34.60 feet to a point; thence North 05 degrees 15 minutes 26 seconds West, a distance of 30.90 feet to a point; thence North 31 degrees 30 minutes 37 seconds West, a distance of 5.07 feet to a point; 12.51 feet along an arc of curve to the right, having a radius of 25.00 feet and chord bearing of North 17 degrees 10 minutes 33 seconds West a distance of 12.38 feet to a point; thence North 02 degrees 50 minutes 29 seconds West, a distance of 12.44 feet to a point; thence North 09 degrees 09 minutes 37 seconds West, a distance of 11.47 feet to a point; 8.40 feet along an arc of curve to the right, having a radius of 25.00 feet and chord bearing of North 00 degrees 27 minutes 42 seconds East a distance of 8.36 feet to a point; thence North 10 degrees 05 minutes 01 seconds East, a distance of 93.74 feet to a point; thence North 11 degrees 41 minutes 15 seconds East, a distance of 76.35 feet to a point; 8.25 feet along an arc of curve to the right, having a radius of 25.00 feet and chord bearing of North 21 degrees 08 minutes 20 seconds East a distance of 8.21 feet to a point; thence North 30 degrees 35 minutes 24 seconds East, a distance of 17.47 feet to a point; thence North 07 degrees 26 minutes 16 seconds East, a distance of 36.92 feet to a point; thence North 04 degrees 46 minutes 55 seconds West, a distance of 53.58 feet to a point; 7.30 feet along an arc of curve to the right, having a radius of 25.00 feet and chord bearing of North 03 degrees 35 minutes 08 seconds East a distance of 7.28 feet to a point; thence North 11 degrees 57 minutes 11 seconds East, a distance of 46.85 feet to a point, said point being the TRUE POINT OF BEGINNING.

Containing 2.296 acres, more or less.



The field data upon which this map or plat is based has a closure precision of one foot in 73,087 feet and an angular error of 00° 00' 01" per angle point and was adjusted using the compass adjustment rule.

This map or plat has been calculated for closure and is found to be accurate to within one foot in 242,709 feet.

**EQUIPMENT USED:**

**ANGULAR:** TOPCON TOTAL STATION

**LINEAR:** TOPCON TOTAL STATION

As required by subsection (d) of O.C.G.A. Section 15-6-67, this plat has been prepared by a land surveyor and approved by all applicable local jurisdictions for recording as evidenced by approval certificates, signatures, stamps, or statements hereon. Such approvals or affirmations should be confirmed with the appropriate governmental bodies by any purchaser or user of this plat as to intended use of any parcel. Furthermore, the undersigned land surveyor certifies that this plat complies with the minimum technical standards for property surveys in Georgia as set forth in the rules and regulations of the Georgia Board of Registration of Professional Engineers and Land Surveyors and as set forth in O.C.G.A. Section 15-6-67.

Date of Map or Plat:

Date


**PLANNERS AND ENGINEERS COLLABORATIVE**  
 "WE PROVIDE SOLUTIONS"  
 ■ SITE PLANNING ■ LANDSCAPE ARCHITECTURE  
 ■ CIVIL ENGINEERING ■ LAND SURVEYING  
 350 RESEARCH COURT PEACHTREE CORNERS, GEORGIA 30092  
 (770)451-2741 ■ WWW.PECCAL.COM

5	-	-	-
4	-	-	-
3	-	-	-
2	-	-	-
1	08/21/20	REVISED DRAWING	MS
REV	DATE	DESCRIPTION	BY


BOUNDARY AND TOPOGRAPHIC SURVEY  
 FOR  
 THE CITY OF DUNWOODY  
 CITY OF DUNWOODY  
 DEKALB COUNTY  
 GEORGIA

LAND LOT(S) 347  
 DISTRICT 18th



DRAWN BY: PEC  
 CHECKED BY: MCS  
 FILE NO.: 17203.00  
 DATE: 09/25/2017  
 SCALE: 1" = 40'



CURVE DATA				
Curve #	ARC	RADIUS	CHORD	CHORD BEARING
C1	6.04'	25.00'	6.03'	S01°25'39"W
C2	15.52'	25.00'	15.28'	S16°01'08"E
C3	5.89'	25.00'	5.88'	S11°07'21"E
C4	12.51'	25.00'	12.38'	S17°10'33"E
C5	8.40'	25.00'	8.36'	S00°27'42"W
C6	8.25'	25.00'	8.21'	S21°08'20"W
C7	7.30'	25.00'	7.28'	S03°35'08"W



Property Line Table		
Line #	Length	Direction
L1	35.60'	N5° 29' 45"W
L2	34.08'	N8° 21' 03"E
L3	20.24'	N22° 44' 20"W
L4	7.84'	N33° 48' 28"W
L5	4.52'	N1° 46' 13"E
L6	36.32'	N20° 49' 49"W
L7	50.19'	N17° 52' 28"W
L8	52.39'	N4° 22' 14"W
L9	34.60'	N18° 40' 24"W
L10	30.90'	N5° 15' 26"W
L11	5.07'	N31° 30' 37"W
L12	12.44'	N2° 50' 29"W
L13	11.47'	N9° 09' 37"W
L14	93.74'	N10° 05' 01"E
L15	76.35'	N11° 41' 15"E
L16	17.47'	N30° 35' 24"E
L17	36.92'	N7° 26' 16"E
L18	53.58'	N4° 46' 55"W
L19	46.85'	N11° 57' 11"E



SHEET 2 OF 4

**PLANNERS AND ENGINEERS COLLABORATIVE**  
 "WE PROVIDE SOLUTIONS"

■ SITE PLANNING ■ LANDSCAPE ARCHITECTURE  
 ■ CIVIL ENGINEERING ■ LAND SURVEYING


350 RESEARCH COURT PEACHTREE CORNERS, GEORGIA 30092  
 (770)451-2741 ■ WWW.PECCAL.COM

REV	DATE	DESCRIPTION	BY
1	08/21/20	REVISED DRAWING	MS

LAND LOT(S) 347  
 DISTRICT 18th

BOUNDARY AND TOPOGRAPHIC SURVEY  
 FOR  
 THE CITY OF DUNWOODY  
 CITY OF DUNWOODY

DRAWN BY: PEC  
 CHECKED BY: MCS  
 FILE NO.: 17203.00  
 DATE: 09/25/2017  
 SCALE: 1" = 40'





**LEGEND**

- IF IRON PIN FOUND (#4 Re-Rod unless noted otherwise)
- IS IRON PIN SET (#4 Re-Rod unless noted otherwise)
- IC IRON PIN WITH CAP FOUND
- POINT
- OP OPEN TOP PIPE FOUND
- CP CRIMP TOP PIPE FOUND
- AI ANGLE IRON
- MF FK WALL FOUND
- MS FK WALL SET
- CM CONCRETE MONUMENT FOUND
- RM RIGHT OF WAY MONUMENT FOUND
- UP UTILITY POLE (CARRIES MULTIPLE UTILITIES)
- WP POWER POLE (WOOD)
- SW SERVICE POLE W/ LIGHT
- GW POWER POLE W/ GUY WIRE
- OW OVERHEAD WIRES
- EM ELECTRIC METER
- WH WATER VALVE
- FH FIRE HYDRANT
- WM WATER METER
- GM GAS METER
- SL STORM SEWER LINE
- SBCB SINGLE WING CATCH BASIN
- DBCB DOUBLE WING CATCH BASIN
- CI CURB INLET
- DI DROP INLET
- JB JUNCTION BOX
- SLS SANITARY SEWER LINE
- SSC SANITARY SEWER CLEANOUT
- SSM SANITARY SEWER MANHOLE
- TB TELEPHONE BOX
- TM TELEPHONE MANHOLE
- MW MONITORING WELL
- FM FIBER OPTIC MARKER
- UW UNDERGROUND WATER LINE
- UG UNDERGROUND GAS LINE
- UE UNDERGROUND ELECTRIC LINE
- UT UNDERGROUND TELEPHONE LINE
- UC UNDERGROUND CABLE LINE
- UO UNDERGROUND FIBER OPTIC LINE

**ABBREVIATIONS**

- APPROX. APPROXIMATE
- BM BENCH MARK
- C&G CURB & GUTTER
- CMP CORRUGATED METAL PIPE
- CL CENTERLINE
- DB DEED BOOK
- DIP DUCTILE IRON PIPE
- DIR. DIRECTION
- INV. INVERT
- P.O.B. POINT OF BEGINNING
- SWCB SINGLE WING CATCH BASIN
- DWCB DOUBLE WING CATCH BASIN
- PB PLAT BOOK
- N/A NOW OR FORMALLY
- RCP REINFORCED CONCRETE PIPE
- LP LIGHT POLE
- LPP LAMP POST



SHEET 3 OF 4

**PLANNERS AND ENGINEERS COLLABORATIVE**  
 "WE PROVIDE SOLUTIONS"  
 ■ SITE PLANNING ■ LANDSCAPE ARCHITECTURE  
 ■ CIVIL ENGINEERING ■ LAND SURVEYING  
 350 RESEARCH COURT PEACHTREE CORNERS, GEORGIA 30092  
 (770)451-2741 ■ WWW.PECCATL.COM

REV	DATE	DESCRIPTION	BY
5	-	-	-
4	-	-	-
3	-	-	-
2	-	-	-
1	08/21/20	REVISED DRAWING	MS

**BOUNDARY AND TOPOGRAPHIC SURVEY**  
 FOR  
**THE CITY OF DUNWOODY**  
 CITY OF DUNWOODY

LAND LOT(S) 347  
 DISTRICT 18th

DRAWN BY: PEC  
 CHECKED BY: MCS  
 FILE NO.: 17203.00  
 DATE: 09/25/2017  
 SCALE: 1" = 40'



A graphic scale bar with markings at 0, 20, 40, and 80 feet.

**LEGEND**

- PF IRON PIN FOUND (#4 Re-Rod unless noted otherwise)
- PS IRON PIN SET (#4 Re-Rod unless noted otherwise)
- PC IRON PIN WITH CAP FOUND
- POINT
- OP OPEN TOP PIPE FOUND
- CP CRIMP TOP PIPE FOUND
- AI ANGLE IRON
- FW FK WALL FOUND
- FS FK WALL SET
- CM CONCRETE MONUMENT FOUND
- RM RIGHT OF WAY MONUMENT FOUND
- UP UTILITY POLE (CARRIES MULTIPLE UTILITIES)
- WP POWER POLE (WOOD)
- SW SERVICE POLE W/ LIGHT
- GW POWER POLE W/ GUY WIRE
- OW OVERHEAD WIRES
- EM ELECTRIC METER
- WM WATER VALVE
- FH FIRE HYDRANT
- WM WATER METER
- GM GAS METER
- SL STORM SEWER LINE
- SMCB SINGLE WING CATCH BASIN
- DMCB DOUBLE WING CATCH BASIN
- CI CURB INLET
- DI DROP INLET
- JB JUNCTION BOX
- SSSL SANITARY SEWER LINE
- SSCS SANITARY SEWER CLEANOUT
- SSMH SANITARY SEWER MANHOLE
- TB TELEPHONE BOX
- TM TELEPHONE MANHOLE
- MW MONITORING WELL
- FM FIBER OPTIC MARKER
- UW UNDERGROUND WATER LINE
- UG UNDERGROUND GAS LINE
- UE UNDERGROUND ELECTRIC LINE
- UT UNDERGROUND TELEPHONE LINE
- UC UNDERGROUND CABLE LINE
- FO UNDERGROUND FIBER OPTIC LINE

**ABBREVIATIONS**

- APPROX. APPROXIMATE
- BM BENCH MARK
- C&G CURB & GUTTER
- CMP CORRUGATED METAL PIPE
- CL CENTERLINE
- DB DEED BOOK
- DIP DUCTILE IRON PIPE
- DIR. DIRECTION
- INV. INVERT
- P.O.B. POINT OF BEGINNING
- SWCB SINGLE WING CATCH BASIN
- DWCB DOUBLE WING CATCH BASIN
- PB PLAT BOOK
- N/F NOW OR FORMALLY
- RCP REINFORCED CONCRETE PIPE
- LP LIGHT POLE
- LPP LAMP POST



MATCH LINE - SEE THIS SHEET

SHEET 4 OF 4

**PLANNERS AND ENGINEERS COLLABORATIVE**

"WE PROVIDE SOLUTIONS"  
 ■ SITE PLANNING ■ LANDSCAPE ARCHITECTURE  
 ■ CIVIL ENGINEERING ■ LAND SURVEYING  
 350 RESEARCH COURT PEACHTREE CORNERS, GEORGIA 30092  
 (770)451-2741 ■ WWW.PECCATL.COM

REV	DATE	DESCRIPTION	BY
5	-	-	-
4	-	-	-
3	-	-	-
2	-	-	-
1	08/21/20	REVISED DRAWING	MS




**BOUNDARY AND TOPOGRAPHIC SURVEY**  
 FOR  
**THE CITY OF DUNWOODY**  
 CITY OF DUNWOODY

LAND LOT(S) 347  
 DISTRICT 18th

DRAWN BY: PEC  
 CHECKED BY: MCS  
 FILE NO.: 17203.00  
 DATE: 09/25/2017  
 SCALE: 1" = 40'

DEKALB COUNTY  
 GEORGIA

USER: 6674 - Jan 07, 2022 - 4:27pm  
 Z:\All Project Data\Projects\2020\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 MAIN.dwg - LAYOUT: DE-1 VERSION: -----



**DEMOLITION PLAN NOTES**

1. THE CONTRACTOR IS RESPONSIBLE FOR THE DEMOLITION, REMOVAL, AND DISPOSING IN A LOCATION APPROVED BY ALL GOVERNING AUTHORITIES, OF ALL STRUCTURES, PADS, WALLS, FLUMES, FOUNDATIONS, PARKING, DRIVES, DRAINAGE, STRUCTURES, UTILITIES, ETC., SUCH THAT THE IMPROVEMENTS SHOWN ON THE REMAINING PLANS CAN BE CONSTRUCTED. ALL FACILITIES TO BE REMOVED SHALL BE UNDERCUT TO SUITABLE MATERIAL AND BROUGHT TO GRADE WITH SUITABLE COMPACTED FILL MATERIAL PER THE SPECIFICATIONS.
2. THE CONTRACTOR IS RESPONSIBLE FOR REMOVING ALL DEBRIS FROM THE SITE AND DISPOSING OF THE DEBRIS IN A LAWFUL MANNER. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS REQUIRED FOR DEMOLITION AND DISPOSAL.
3. THE CONTRACTOR SHALL COORDINATE WITH RESPECTIVE UTILITY COMPANIES PRIOR TO THE REMOVAL AND/OR RELOCATION OF UTILITIES. THE CONTRACTOR SHALL COORDINATE WITH THE UTILITY COMPANY CONCERNING PORTIONS OF WORK WHICH MAY BE PERFORMED BY THE UTILITY COMPANY'S FORCES AND ANY FEES WHICH ARE TO BE PAID TO THE UTILITY COMPANY FOR THEIR SERVICES. THE CONTRACTOR IS RESPONSIBLE FOR PAYING ALL FEES AND CHARGES.
4. THE LOCATIONS OF ALL EXISTING UTILITIES SHOWN ON THIS PLAN HAVE BEEN DETERMINED FROM THE BEST INFORMATION AVAILABLE AND ARE GIVEN FOR THE CONVENIENCE OF THE CONTRACTOR. THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THEIR ACCURACY. PRIOR TO THE START OF ANY DEMOLITION ACTIVITY, THE CONTRACTOR SHALL NOTIFY THE UTILITY COMPANIES FOR ONSITE LOCATIONS OF EXISTING UTILITIES.
5. ALL EXISTING SEWERS, PIPING AND UTILITIES SHOWN ARE NOT TO BE INTERPRETED AS THE EXACT LOCATION, OR AS THE ONLY OBSTACLES THAT MAY OCCUR ON THE SITE. VERIFY EXISTING CONDITIONS AND PROCEED WITH CAUTION AROUND ANY ANTICIPATED FEATURES. GIVE NOTICE TO ALL UTILITY COMPANIES REGARDING DESTRUCTION AND REMOVAL OF ALL SERVICE LINES AND CAP ALL LINES BEFORE PROCEEDING WITH THE WORK. UTILITIES DETERMINED TO BE ABANDONED AND LEFT IN PLACE SHALL BE GROUTED UNDER BUILDING.
6. ELECTRICAL, TELEPHONE, CABLE, WATER, FIBER OPTIC CABLE AND/OR GAS LINES NEEDING TO BE REMOVED OR RELOCATED SHALL BE COORDINATED WITH THE AFFECTED UTILITY COMPANY. ADEQUATE TIME SHALL BE PROVIDED FOR RELOCATION, AND CLOSE COORDINATION WITH THE UTILITY COMPANY IS NECESSARY TO PROVIDE A SMOOTH TRANSITION IN UTILITY SERVICE. CONTRACTOR SHALL PAY CLOSE ATTENTION TO EXISTING UTILITIES WITHIN THE ANY ROAD RIGHT OF WAY DURING CONSTRUCTION.
7. CONTRACTOR MUST PROTECT THE PUBLIC AT ALL TIMES WITH FENCING, BARRICADES, ENCLOSURES, ETC., TO THE BEST PRACTICES AND AS APPROVED BY THE OWNER'S CONSTRUCTION MANAGER.
8. PRIOR TO DEMOLITION OCCURRING, ALL EROSION CONTROL DEVICES ARE TO BE INSTALLED.
9. CONTRACTOR MAY LIMIT SAW-OUT & PAVEMENT REMOVAL TO ONLY THOSE AREAS WHERE IT IS REQUIRED AS SHOWN ON THESE CONSTRUCTION PLANS; BUT IF ANY DAMAGE IS INCURRED ON ANY OF THE SURROUNDING PAVEMENT, ETC. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ITS REMOVAL AND REPAIR.
10. THE CONTRACTOR SHALL COORDINATE WATERMAIN WORK WITH THE FIRE DEPT. AND THE COUNTY UTILITY DEPARTMENT TO PLAN PROPOSED IMPROVEMENTS AND TO ENSURE ADEQUATE FIRE PROTECTION IS CONSTANTLY AVAILABLE TO THE SITE THROUGHOUT THIS SPECIFIC WORK AND THROUGH ALL PHASES OF CONSTRUCTION. CONTRACTOR WILL BE RESPONSIBLE FOR ARRANGING/PROVIDING ANY REQUIRED WATERMAIN SHUT OFFS WITH THE COUNTY DURING CONSTRUCTION. ANY COSTS ASSOCIATED WITH WATERMAIN SHUT OFFS WILL BE THE RESPONSIBILITY OF THE CONTRACTOR AND AS PART OF THE BASE BID.
11. DAMAGE TO ANY EXISTING CONDITIONS TO REMAIN WILL BE REPLACED/REPAIRED AT CONTRACTOR'S EXPENSE.
12. CONTRACTOR TO REPLACE/REPAIR ASPHALT AS NEEDED AFTER DEMOLITION, ABANDONMENT, OR RELOCATION OF PAVING, UTILITIES, STRUCTURES, ETC. AS PART OF THE BASE BID.
13. NO EQUIPMENT SHALL BE STORED WITH IN ANY RIGHT-OF-WAY WITH OUT PERMISSION OF RIGHT-OF-WAY OWNER.

**NOTE:**  
 PRIOR TO TREE REMOVAL, THE CONTRACTOR MUST FLAG ALL TREES TO BE REMOVED ON THIS PLAN AND STAKE THE CENTERLINE OF ALL SIDEWALKS AND STRUCTURES. CONTRACTOR MUST THEN WALK THE SITE WITH THE CITY ARBORIST TO VERIFY TREES TO BE REMOVED AND/OR MODIFY STRUCTURE LOCATIONS TO SAVE TREES IF POSSIBLE.




GSWCC# 10882  
 EXP: 05/24/2024

Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**

REVISIONS	BY

DRAWN BY: DMN  
 CHECKED BY: CLM  
 DATE: 01/07/2022  
 SCALE: 1" = 40'  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

**DE-1**



**CONSERVATION COMMISSION NOTES**

- EROSION CONTROL MEASURES WILL BE MAINTAINED AT ALL TIMES. IF FULL IMPLEMENTATION OF THE APPROVED PLAN DOES NOT PROVIDE FOR EFFECTIVE EROSION CONTROL, ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IMPLEMENTED TO CONTROL OR TREAT THE SEDIMENT SOURCE.
- THE ESCAPE OF SEDIMENT FROM THE SITE SHALL BE PREVENTED BY THE INSTALLATION OF EROSION AND SEDIMENT CONTROL MEASURES AND PRACTICES PRIOR TO LAND-DISTURBING ACTIVITIES.
- ALL EROSION & SEDIMENT CONTROL MEASURES WILL BE CHECKED DAILY AND ANY DEFICIENCIES NOTED WILL BE CORRECTED BY THE END OF EACH DAY. ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES WILL BE INSTALLED IF DEEMED NECESSARY AFTER ON-SITE INSPECTION BY THE ISSUING AUTHORITY.
- ANY DISTURBED AREA LEFT EXPOSED FOR A PERIOD GREATER THAN 14 DAYS SHALL BE STABILIZED WITH MULCH OR TEMPORARY SEEDING.

ACREAGE SUMMARY (IN ACRES)	
SITE AREA	6.633 AC±
ON-SITE DISTURBED AREA	3.54 AC±
OFF-SITE DISTURBED AREA	0.36 AC±
TOTAL DISTURBED AREA (MUST MATCH NO)	3.90 AC±
IMPERVIOUS AREA AT COMPLETION	0.99 AC±
PERVIOUS AREA AT COMPLETION	2.91 AC±

TEMPORARY SEDIMENT TRAP #1 CALCULATIONS	
DRAINAGE AREA = 0.29 AC	
DISTURBED AREA = 0.29 AC	
SEDIMENT STORAGE REQUIRED = 20 CY (67 CY/AC.)	
SEDIMENT STORAGE PROVIDED = 48 CY	
CLEANOUT VOLUME REQUIRED = 7 CY (22 CY/AC.)	
CLEANOUT VOLUME PROVIDED = 15 CY	
CLEANOUT VOLUME ELEVATION = 939.00	

TEMPORARY SILT FENCE CALCULATIONS	
DRAINAGE AREA = 1.39 AC	
DISTURBED AREA = 1.39 AC	
SILT FENCE REQUIRED = 556 LF (100 LF/0.25 AC)	
SILT FENCE PROVIDED = 594 LF	

NOTE: SILT FENCE IS BEING USED TO CONTAIN SEDIMENT FOR THE 1.39 ACRES THAT ARE DOWNSTREAM OF THE SEDIMENT TRAPS. THIS AREA IS EITHER DOWN GRADIENT OF THE PRIMARY SEDIMENT CONTROL MEASURE OR DRAINS AWAY FROM SAID FEATURES; THUS, IT CAN'T BE ROUTED THROUGH SAID FEATURES.

STORM DRAIN OUTLET PROTECTION									
NUMBER	AVG. STONE SIZE (600) (inches)	APRON LENGTH (L <sub>a</sub> ) (feet)	APRON WIDTH AT HEAD (W <sub>h</sub> ) (feet)	DOWNSTREAM OF PIPE (D) (feet)	MIN. APRON THICKNESS (t) (inches)	PIPE DIAMETER (inches)	FLOW RATE (cfs)	VELOCITY (fps)	TAILWATER CONDITION (feet)
St#1	24	16	7.5	19	36	30	20.18	13.38	0
St#2	12	6	3	7	18	12	0.24	3.71	0
St#3	12	6	1.5	6.5	18	0.5	0.55	3.43	0
St#4	12	6	1.5	6.5	18	0.5	0.55	3.43	0
St#5	12	6	1.5	6.5	18	0.5	0.55	3.43	0
St#6	12	6	1.5	6.5	18	0.5	0.55	3.43	0
St#7	12	6	1.5	6.5	18	0.5	0.55	3.43	0

**DEVELOPER/OWNER:**  
CITY OF DUNWOODY PARKS AND REC  
4800 ASHFORD DUNWOODY ROAD  
DUNWOODY, GA 30338  
(678) 382-6857

**SITE OPERATOR/GENERAL CONTRACTOR:**

**SUPERINTENDENT:**


**24 HR LOCAL EMERGENCY CONTACT**

BRENT WALKER (678)382-6857  
CITY OF DUNWOODY PARKS AND REC

(CONTRACTOR'S NAME) (PHONE NUMBER)

NOTE: CONTRACTOR TO PROVIDE UPDATED INFORMATION ONCE CONTRACT IS AWARDED.

NOTE: SEE SURVEY FOR EXISTING LEGEND SYMBOLS



LOCATION MAP NOT TO SCALE

**EROSION CONTROL LEGEND**

- PROPERTY LINE
- LIMITS OF DISTURBANCE
- GRADE BREAK
- CONTOUR ELEVATIONS
- STORM DRAIN
- DIRECTION OF OVERLAND FLOW
- LIMITS OF DRAINAGE SUB-BASIN
- SOIL SERIES BOUNDARY
- SILT FENCE
- TREE PROTECTION FENCE
- SWPPP INFORMATION SIGN

**SOIL SERIES LEGEND**

- Ca CARTECA SILT LOAM HSG: A/D
- Tf TOCCOA SANDY LOAM 0 TO 2 PERCENT SLOPES, HSG: A
- Ud URBAN LAND

**STRUCTURAL PRACTICES**

CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Cd	CHECK DAM			A small temporary barrier or dam constructed across a grade, drainage ditch or area of concentrated flow.
Co	CONSTRUCTION EXIT			A crushed stone pad located at the construction site exit to provide a place for removing mud from tires thereby protecting public streets.
Di	DITCH			A north channel or dike located above, below or across a slope to divert runoff. This may be a temporary or permanent structure.
Re	RETAINING WALL			A wall installed to stabilize cut and fill slopes where maximum permitted slopes are not obtainable. Each situation will require special design.
Sd1	SEDIMENT BARRIER			A barrier to prevent sediment from leaving the construction site. It may be sandbags, bags of straw or hay, brush, logs and poles, gravel, or a silt fence.
Sd2	BUILT SEDIMENT TRAP			An impounding area created by excavating across a storm drain inlet. The excavated area will be filled and stabilized on completion of construction activities.
Sd4	TEMPORARY SEDIMENT TRAP			A small temporary pond that drains a disturbed area but does not stabilize on completion of construction activities.
Sg	SILT CONTROL DATES			A rough soil surface with horizontal depressions on a contour or slopes left in a roughened condition after grading.
St	STORM DRAIN OUTLET PROTECTION			A paved or short section of riprap channel at the outlet of a storm drain system preventing erosion from the concentrated runoff.
Tp	TOPSOILING			The practice of stripping off the more fertile topsoil, storing it, then spreading it over the disturbed area after completion of construction activities.
Tr	TREE PROTECTION			To protect desirable trees from injury during construction activity.

**VEGETATIVE PRACTICES**

CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Bf	BUFFER ZONE			Strip of undisturbed original vegetation, enhanced or restored existing vegetation or the reestablishment of vegetation surrounding an area of disturbance or bordering streams.
Ds1	DISTURBED AREA STABILIZATION (WITH MULCHING ONLY)			Establishing temporary protection for disturbed areas where seedlings may not have a suitable growing season to produce an erosion retarding cover.
Ds2	DISTURBED AREA STABILIZATION (WITH TEMP SEEDING)			Establishing a temporary vegetative cover with fast growing seedlings on disturbed areas.
Ds3	DISTURBED AREA STABILIZATION (WITH PERM SEEDING)			Establishing a permanent vegetative cover such as trees, shrubs, vines, grasses, or legumes on disturbed areas.
Du	DUST CONTROL ON DISTURBED AREAS			Controlling surface and air movement of dust on construction site, roadways and similar sites.
Se	SLOPE STABILIZATION			A protective covering used to prevent erosion and establish temporary or permanent vegetation on steep slopes, steep ditches, or channels.

REFER TO PLAN SHEET ES-4 FOR GENERAL NOTES, MAINTENANCE NOTES, SITE DATA & QUAD MAP

PROVIDE TEMPORARY IRRIGATION OR WATERING VIA WATER TRUCK, AS NEEDED TO ESTABLISH TEMPORARY AND PERMANENT VEGETATION UNTIL THE PERMANENT IRRIGATION SYSTEM IS FULLY FUNCTION OR UNTIL THE NOT IS SUBMITTED IF A PERMANENT IRRIGATION SYSTEM ISN'T PLANNED. AREAS NOT HAVING A PERMANENT IRRIGATION SYSTEM SHALL BE IRRIGATED OR WATERED UNTIL THE NOT HAS BEEN SUBMITTED AND ACCEPTED.

REPRESENTS NOTE/FEATURE WHICH CORRESPONDS WITH THE ES&PC PLAN CHECKLIST. SEE SHEET ES-4 FOR ES&PC CHECKLIST.

**MULCHING SCHEDULE**

MULCHING MATERIAL	RATE/ACRE
DRY STRAW OR HAY	2.5 TONS (6 TO 8" DEEP)
WOOD WASTE, CHIPS, SAWDUST, OR BARK	6 TO 9 TONS (2 TO 3" DEEP)

**TEMPORARY SEEDING SCHEDULE**




SPECIES (MIXTURE OF)	RATE/ACRE	PLANTING DATES
SUDAN (SWEET OR TIFT)	60 LBS	APRIL-SEPT 1
ANNUAL RYE GRASS	40 LBS	AUG 1-APRIL 15

NOTE: APPLY LIME AT THE RATE OF 1 TON/ACRE REFER TO D-4A FOR FERTILIZER REQUIREMENTS

**PERMANENT SEEDING SCHEDULE**

SPECIES	RATE/ACRE	PLANTING DATES
COMMON BERMUDA (HULLED) (CYNODON DACTYLON)	10 LBS	MARCH 1-JULY 1
COMMON BERMUDA (UNHULLED) (CYNODON DACTYLON)	10 LBS	OCT 1-MAR 1
BAHIA PENSACOLA (PASPALUM NOTATUM)	60 LBS	JAN 1-DEC 31

NOTE: APPLY LIME AT THE RATE OF 1 TON/ACRE REFER TO D-4A FOR FERTILIZER REQUIREMENTS



GSWCC# 10882  
EXP: 05/24/2024

Project Title  
PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOODY RD  
DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY DMN  
CHECKED BY CLM  
DATE: 01/07/2022  
SCALE: 1" = 50'  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER

**ES-1**

USER: 6674 - Jan 07, 2022 - 4:27pm  
 Z:\All Project Data\Projects\2020\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Drawings\20-LD-025 MAIN.DWG - LAYOUT: ES-1 VERSION:

**CONSERVATION COMMISSION NOTES**

EROSION CONTROL MEASURES WILL BE MAINTAINED AT ALL TIMES. IF FULL IMPLEMENTATION OF THE APPROVED PLAN DOES NOT PROVIDE FOR EFFECTIVE EROSION CONTROL, ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IMPLEMENTED TO CONTROL OR TREAT THE SEDIMENT SOURCE.

THE ESCAPE OF SEDIMENT FROM THE SITE SHALL BE PREVENTED BY THE INSTALLATION OF EROSION AND SEDIMENT CONTROL MEASURES AND PRACTICES PRIOR TO LAND-DISTURBING ACTIVITIES.

ALL EROSION & SEDIMENT CONTROL MEASURES WILL BE CHECKED DAILY AND ANY DEFICIENCIES NOTED WILL BE CORRECTED BY THE END OF EACH DAY. ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES WILL BE INSTALLED IF DEMAND NECESSARY AFTER ONSITE INSPECTION BY THE ISSUING AUTHORITY.

ANY DISTURBED AREA LEFT EXPOSED FOR A PERIOD GREATER THAN 14 DAYS SHALL BE STABILIZED WITH MULCH OR TEMPORARY SEEDING.

ACREAGE SUMMARY table with columns: SITE AREA, ON-SITE DISTURBED AREA, OFF-SITE DISTURBED AREA, TOTAL DISTURBED AREA, IMPERVIOUS AREA AT COMPLETION, PERVIOUS AREA AT COMPLETION.

TEMPORARY SILT FENCE CALCULATIONS table with columns: NUMBER, AVG. STONE SIZE, APRON LENGTH, APRON WIDTH, DOWNSTREAM WIDTH, MIN. APRON THICKNESS, PIPE DIAMETER, FLOW RATE, VELOCITY, TAILWATER CONDITION.

**MULCHING SCHEDULE**


Mulching schedule table with columns: MULCHING MATERIAL, RATE/ACRE.

**TEMPORARY SEEDING SCHEDULE**

Temporary seeding schedule table with columns: SPECIES, RATE/ACRE, PLANTING DATES.

**PERMANENT SEEDING SCHEDULE**

Permanent seeding schedule table with columns: SPECIES, RATE/ACRE, PLANTING DATES.




DEVELOPER/OWNER: CITY OF DUNWOODY PARKS AND REC 4800 ASHFORD DUNWOODY ROAD DUNWOODY, GA 30338 (678) 382-6857

**24 HR LOCAL EMERGENCY CONTACT**

BRENT WALKER (678)382-6857 CITY OF DUNWOODY PARKS AND REC

EROSION CONTROL LEGEND table with symbols for PROPERTY LINE, LIMITS OF DISTURBANCE, GRADE BREAK, CONTOUR ELEVATIONS, STORM DRAIN, etc.

SOIL SERIES LEGEND table with symbols for Ca (CARTECAJ SILT LOAM), Tf (TOCCOA SANDY LOAM), Ud (URBAN LAND).



**STRUCTURAL PRACTICES**

Table of structural practices with columns: CODE, PRACTICE, DETAIL, MAP SYMBOL, DESCRIPTION.


**VEGETATIVE PRACTICES**

Table of vegetative practices with columns: CODE, PRACTICE, DETAIL, MAP SYMBOL, DESCRIPTION.

REFER TO PLAN SHEET ES-4 FOR GENERAL NOTES, MAINTENANCE NOTES, SITE DATA & QUAD MAP

PROVIDE TEMPORARY IRRIGATION OR WATERING VIA WATER TRUCK, AS NEEDED TO ESTABLISH TEMPORARY AND PERMANENT VEGETATION UNTIL THE PERMANENT IRRIGATION SYSTEM IS FULLY FUNCTION OR UNTIL THE NOT IS SUBMITTED IF A PERMANENT IRRIGATION SYSTEM ISN'T PLANNED.

**PHASE II EROSION SEDIMENTATION & POLLUTION CONTROL PLAN**



GSWCC# 10882 EXP: 05/24/2024

Project Title: PERIMETER CENTER EAST PARK CITY OF DUNWOODY, GEORGIA 4800 ASHFORD DUNWOODY RD DUNWOODY, GA 30338

REVISIONS table with columns: NO., REVISIONS, BY.

DRAWN BY: DMN CHECKED BY: CLM DATE: 01/07/2022 SCALE: 1"= 40' JOB No: 20-LD-025 / 061694.00 SHEET NUMBER

**ES-2**

USER: 6674 - Jan 07, 2022 - 4:27pm Z:\All Project Data\Projects\2020\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 MAIN.dwg - LAYOUT: ES-2, VERSION: -----





**CONSERVATION COMMISSION NOTES**

EROSION CONTROL MEASURES WILL BE MAINTAINED AT ALL TIMES. IF FULL IMPLEMENTATION OF THE APPROVED PLAN DOES NOT PROVIDE FOR EFFECTIVE EROSION CONTROL, ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IMPLEMENTED TO CONTROL OR TREAT THE SEDIMENT SOURCE.

THE ESCAPE OF SEDIMENT FROM THE SITE SHALL BE PREVENTED BY THE INSTALLATION OF EROSION AND SEDIMENT CONTROL MEASURES AND PRACTICES PRIOR TO LAND-DISTURBING ACTIVITIES.

ALL EROSION & SEDIMENT CONTROL MEASURES WILL BE CHECKED DAILY AND ANY DEFICIENCIES NOTED WILL BE CORRECTED BY THE END OF EACH DAY. ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES WILL BE INSTALLED IF DEMAND NECESSARY AFTER ONSITE INSPECTION BY THE ISSUING AUTHORITY.

ANY DISTURBED AREA LEFT EXPOSED FOR A PERIOD GREATER THAN 14 DAYS SHALL BE STABILIZED WITH MULCH OR TEMPORARY SEEDING.

**MULCHING SCHEDULE**

Table with columns: MULCHING MATERIAL, RATE/ACRE. Rows: DRY STRAW OR HAY (2.5 TONS), WOOD WASTE, CHIPS, SAWDUST, OR BARK (6 TO 9 TONS).

**TEMPORARY SEEDING SCHEDULE**

Table with columns: SPECIES (MIXTURE OF), RATE/ACRE, PLANTING DATES. Rows: SUDAN (SWEET OR TIFT), ANNUAL RYE GRASS.

NOTE: APPLY LIME AT THE RATE OF 1 TON/ACRE REFER TO D-4A FOR FERTILIZER REQUIREMENTS

**PERMANENT SEEDING SCHEDULE**

Table with columns: SPECIES, RATE/ACRE, PLANTING DATES. Rows: COMMON BERMUDA (HULLED), COMMON BERMUDA (UNHULLED), BAHIA PENSACOLA.

NOTE: APPLY LIME AT THE RATE OF 1 TON/ACRE REFER TO D-4A FOR FERTILIZER REQUIREMENTS

REFER TO PLAN SHEET D-4C FOR Sd2-Ex & Sg CALCULATIONS.

**ACREAGE SUMMARY**

Table with columns: SITE AREA, ON-SITE DISTURBED AREA, OFF-SITE DISTURBED AREA, TOTAL DISTURBED AREA, IMPERVIOUS AREA AT COMPLETION, PERVIOUS AREA AT COMPLETION.

**TEMPORARY SILT FENCE CALCULATIONS**

DRAINAGE AREA = 1.44 AC. DISTURBED AREA = 1.44 AC. SILT FENCE REQUIRED = 576 LF (100 LF/0.25 AC) SILT FENCE PROVIDED = 2,154 LF

STORM DRAIN OUTLET PROTECTION table with columns: NUMBER, AVG. STONE SIZE, APRON LENGTH, APRON WIDTH AT HEADWALL, DOWNSTREAM OF PIPE, MIN. APRON THICKNESS, PIPE DIAMETER, FLOW RATE, VELOCITY, TAILWATER CONDITION.

DEVELOPER/OWNER: CITY OF DUNWOODY PARKS AND REC 4800 ASHFORD DUNWOODY ROAD DUNWOODY, GA 30338 (678) 382-6857

**24 HR LOCAL EMERGENCY CONTACT**

BRENT WALKER (678)382-6857 CITY OF DUNWOODY PARKS AND REC


NOTE: CONTRACTOR TO PROVIDE UPDATED INFORMATION ONCE CONTRACT IS AWARDED.

**EROSION CONTROL LEGEND**

- PROPERTY LINE
LIMITS OF DISTURBANCE
GRADE BREAK
CONTOUR ELEVATIONS
STORM DRAIN
DIRECTION OF OVERLAND FLOW
LIMITS OF DRAINAGE SUB-BASIN
SOIL SERIES BOUNDARY
SILT FENCE
TREE PROTECTION FENCE
SWPPP INFORMATION SIGN

**SOIL SERIES LEGEND**

- Ca CARTECAE SILT LOAM HSG: A/D
Tf TOCCOA SANDY LOAM 0 TO 2 PERCENT SLOPES, HSG: A
Ud URBAN LAND



**STRUCTURAL PRACTICES**

Table with columns: CODE PRACTICE, DETAIL, MAP SYMBOL, DESCRIPTION.

Main table for Structural Practices listing various erosion control measures like Sediment Basins, Silt Fences, etc.

**VEGETATIVE PRACTICES**

Table with columns: CODE PRACTICE, DETAIL, MAP SYMBOL, DESCRIPTION.


Main table for Vegetative Practices listing measures like Buffer Zones, Seeding, etc.

REFER TO PLAN SHEET ES-4 FOR GENERAL NOTES, MAINTENANCE NOTES, SITE DATA & QUAD MAP

PROVIDE TEMPORARY IRRIGATION OR WATERING VIA WATER TRUCK, AS NEEDED TO ESTABLISH TEMPORARY AND PERMANENT VEGETATION UNTIL THE PERMANENT IRRIGATION SYSTEM IS FULLY FUNCTION OR UNTIL THE NOT IS SUBMITTED IF A PERMANENT IRRIGATION SYSTEM ISN'T PLANNED. AREAS NOT HAVING A PERMANENT IRRIGATION SYSTEM SHALL BE IRRIGATED OR WATERED UNTIL THE NOT HAS BEEN SUBMITTED AND ACCEPTED.

REPRESENTS NOTE/FEATURE WHICH CORRESPONDS WITH THE ES&PC PLAN CHECKLIST. SEE SHEET ES-4 FOR ES&PC CHECKLIST.

PHASE III EROSION SEDIMENTATION & POLLUTION CONTROL PLAN



PERIMETER CENTER EAST PARK CITY OF DUNWOODY, GEORGIA 4800 ASHFORD DUNWOODY RD DUNWOODY, GA 30338

REVISIONS table with columns: NO., REVISIONS, BY.

DRAWN BY: DMN CHECKED BY: CLM DATE: 01/07/2022 SCALE: 1" = 40'

JOB No. 20-LD-025 / 061694.00 SHEET NUMBER

ES-3



**EROSION CONTROL NOTES**

- SILT FENCE MUST MEET THE REQUIREMENTS OF THE MANUAL FOR EROSION AND SEDIMENT CONTROL OF GEORGIA.
- ADDITIONAL EROSION CONTROL MEASURES WILL BE EMPLOYED BY CONTRACTOR WHERE DETERMINED NECESSARY BY ACTUAL SITE CONDITIONS TO ENSURE COMPLIANCE WITH REGULATIONS. ANY MEASURES IMPLEMENTED REQUIRING HYDRAULIC CALCULATIONS ARE TO BE COORDINATED WITH AND CERTIFIED BY THE DESIGN PROFESSIONAL PRIOR TO COMMENCEMENT.
- PROVISIONS TO PREVENT EROSION OF SOIL FROM THE SITE SHALL BE, AT A MINIMUM, IN CONFORMANCE WITH THE REQUIREMENTS OF THE CITY OF DUNWOODY EROSION AND SEDIMENTATION ORDINANCE AND THE SEDIMENT CONTROL MANUAL FOR EROSION AND SEDIMENT CONTROL.
- PRIOR TO ANY OTHER CONSTRUCTION, A STABILIZED CONSTRUCTION ENTRANCE SHALL BE CONSTRUCTED AT EACH ENTRY TO OR EXIT FROM THE SITE. ALL OTHER DRIVEWAYS WITHOUT A CONSTRUCTION EXIT SHALL BE BARRICADED TO PROHIBIT INGRESS AND EGRESS TRAFFIC.
- THE CONSTRUCTION EXITS SHALL BE MAINTAINED IN A CONDITION WHICH SHALL PREVENT TRACKING OR FLOW OF MUD ONTO PUBLIC RIGHT-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH STONE, AS CONDITIONS DEMAND, AND REPAIR AND/OR CLEAN-OUT OF ANY STRUCTURES USED TO TRAP SEDIMENT. ALL MATERIALS SPILLED, DROPPED, WASHED, OR TRACKED FROM VEHICLE FROM THE SITE ONTO PUBLIC ROADWAY OR INTO STORM SEWER MUST BE REMOVED.
- DURING AND AFTER CONSTRUCTION IS COMPLETE, THE DETENTION POND AND POND OUTLET STRUCTURE SHALL BE CLEANED OF ALL DEBRIS AND EXCESS SEDIMENT. BOTTOM OF POND SHALL BE BROUGHT TO ELEVATION AND SHAPED AS SHOWN ON THE GRADING PLAN.
- THE CONTRACTOR SHALL FURNISH AND MAINTAIN ALL NECESSARY TRAFFIC CONTROL DEVICES, AS NEEDED.
- EROSION CONTROL DEVICES SHALL BE INSTALLED BEFORE GROUND DISTURBANCE OCCURS. THE LOCATION OF SOME OF THE EROSION CONTROL DEVICES MAY HAVE TO BE ALTERED FROM THAT SHOWN ON THE APPROVED PLANS IF DRAINAGE PATTERNS DURING CONSTRUCTION ARE DIFFERENT FROM THE FINAL PROPOSED DRAINAGE PATTERNS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ACCOMPLISH EROSION CONTROL FOR ALL DRAINAGE PATTERNS CREATED AT VARIOUS STAGES DURING CONSTRUCTION. ANY DIFFICULTY IN CONTROLLING EROSION DURING ANY PHASE OF CONSTRUCTION SHALL BE REPORTED TO THE DESIGN PROFESSIONAL IMMEDIATELY.
- THE CONTRACTOR SHALL REMOVE ACCUMULATED SILT WHEN THE SILT IS WITHIN 1/2 OF THE ORIGINAL HEIGHT OF THE SILT FENCE UTILIZED FOR EROSION CONTROL. IN THE SEDIMENTATION PONDS, SILT SHALL BE REMOVED WHEN THE CLEANOUT VOLUME (22 CY/AC) IS REACHED. SEDIMENT STORAGE INDICATORS MUST BE INSTALLED IN EACH POND.
- FAILURE TO INSTALL, OPERATE OR MAINTAIN ALL EROSION CONTROL MEASURES WILL RESULT IN ALL CONSTRUCTION BEING STOPPED ON THE JOB SITE UNTIL SUCH MEASURES ARE CORRECTED BACK TO LOCAL AND STATE STANDARDS.
- A COPY OF THE APPROVED LAND DISTURBANCE PLAN AND PERMIT SHALL BE PRESENT ON THE SITE WHENEVER LAND DISTURBANCE ACTIVITY IS IN PROGRESS.
- SILT BARRIERS ARE TO BE PLACED AT DOWNSTREAM TOE OF ALL FILL SLOPES.
- ALL SLOPES AND AREAS DISTURBED DURING CONSTRUCTION SHALL BE GRADED SMOOTH AND 4" OF AMENDED TOPSOIL APPLIED. THE AREA SHALL THEN BE SEEDED, FERTILIZED, MULCHED, WATERED AND MAINTAINED UNTIL A HEALTHY STAND OF PERMANENT VEGETATION HAS BEEN ESTABLISHED FOR ALL DISTURBED AREAS.
- ABSOLUTELY NO SEDIMENT SHALL BE PERMITTED TO LEAVE THE SITE DURING CONSTRUCTION. IF HEAVY RAINS AND UNUSUAL SITE CONDITIONS RESULT IN THE POLLUTION OF ROADSWAYS OR ADJACENT PARCELS THEN THE GRADING CONTRACTOR SHALL CLEAN THE DISTURBED AREAS IMMEDIATELY AND RESTORE THE AREAS TO THE ORIGINAL CONDITION.
- ADDITIONAL EROSION CONTROL MEASURES MAY BE REQUIRED BY THE GOVERNING OFFICIALS. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO BE INTIMATE WITH THE LOCAL EROSION CONTROL LAWS AND TO REFLECT THIS KNOWLEDGE IN HIS/HER ACTIONS AND QUOTATIONS.
- REVEALING THE CONSTRUCTION SEQUENCE FOR THE RELATIONSHIP BETWEEN THE INSTALLATION OF EROSION CONTROL FEATURES AND GENERAL CONSTRUCTION.
- MAINTENANCE OF ALL EROSION AND SEDIMENT CONTROL MEASURES, WHETHER TEMPORARY OR PERMANENT, SHALL BE AT ALL TIMES THE RESPONSIBILITY OF THE PROPERTY OWNER AND THE CONTRACTOR.
- ALL GRADED SLOPES STEEPER THAN 3:1 OR OVER 5' IN HEIGHT REGARDLESS OF SLOPE MUST BE HYDRA SEEDED AND COVERED WITH EXCELSON CURLEX BLANKETS OR APPROVED EQUAL FIBER MATTING. IF NOT HYDRA SEEDED, APPROVED MATTING THAT HAS BEEN IMPROVED WITH SEED AND FERTILIZER MUST BE USED. ALL SLOPES MUST BE PROPERLY PROTECTED UNTIL A PERMANENT VEGETATIVE STAND IS ESTABLISHED.
- ALL DISTURBED AREAS MUST BE SEEDED AND MULCHED AS SOON AS FINAL GRADE IS ACHIEVED. THESE DISTURBED AREAS MUST BE PROTECTED UNTIL PERMANENT VEGETATION IS ESTABLISHED.
- CONTRACTOR MUST HAUL OFF ALL SOLID WASTE TO AN APPROVED LAND FILL. SOLID WASTE BURNING ON SITE IS PROHIBITED.
- ALL CONSTRUCTION SHALL BE STABILIZED AT THE END OF EACH WORKING DAY. THIS INCLUDES BACKFILLING OF TRENCHES FOR UTILITY CONSTRUCTION AND PLACEMENT OF GRAVEL OR BITUMINOUS PAVING FOR ROAD CONSTRUCTION.
- WASTE MATERIALS SHALL NOT BE DISCHARGED INTO WATERS OF THE STATE, EXCEPT AS AUTHORIZED BY A SECTION 404 PERMIT.
- NON-EXEMPT ACTIVITIES SHALL NOT BE CONDUCTED WITHIN THE 25 OR 50-FOOT UNDISTURBED STREAM BUFFERS AS MEASURED FROM THE POINT OF CONTACT WITH THE VEGETATION OR WITHIN 25-FOOT MARSHLAND BUFFER AS MEASURED FROM THE JURISDICTIONAL DETERMINATION LINE WITHOUT FIRST OBTAINING THE NECESSARY PERMITS AND PERMITS.
- THERE ARE STATE WATERS LOCATED WITHIN 200 FT. OF THE SITE.
- THERE ARE NO WETLAND DISTURBANCES PROPOSED FOR THIS DEVELOPMENT.
- ALL CONCRETE WASHOUT AREAS ARE TO BE CONTAINED IN SUCH A MANNER THAT NONE OF THE WATER COMES INTO CONTACT WITH THE SURROUNDING SOILS OR STORMWATER.
- CONCRETE WASHOUT AREA IS FOR CONCRETE WASH DOWN OF TOOLS, CONCRETE MIXER CHUTES, HOPPERS AND THE REAR OF VEHICLES. WASHOUT OF THE DRUM AT THE CONSTRUCTION SITE IS PROHIBITED.
- MOVEMENTS PERMITS TO THE ESC&PC PLAN WHICH HAVE SIGNIFICANT EFFECT ON BMPs WITH A HYDRAULIC COMPONENT MUST BE CERTIFIED BY THE DESIGN PROFESSIONAL.
- THE APPLICABLE PORTIONS EROSION SEDIMENTATION AND POLLUTION CONTROL PLAN IS TO BE PROVIDED TO EACH SECONDARY PERMITTEE TO THE ESC&PC PLAN WHICH HAVE SIGNIFICANT EFFECT ON BMPs WITH A HYDRAULIC COMPONENT MUST BE CERTIFIED BY THE DESIGN PROFESSIONAL.

**PRIMARY PERMITTEE CERTIFICATION**

"I CERTIFY UNDER PENALTY OF LAW THAT THIS REPORT AND ALL ATTACHMENTS WERE PREPARED UNDER MY DIRECTION OR SUPERVISION IN ACCORDANCE WITH A SYSTEM DESIGNED TO ASSURE THAT CERTIFIED PERSONNEL PROPERLY GATHER AND EVALUATE THE INFORMATION SUBMITTED. BASED ON MY INQUIRY OF THE PERSON OR PERSONS WHO MANAGE THE SYSTEM, OR THOSE PERSONS DIRECTLY RESPONSIBLE FOR GATHERING THE INFORMATION, THE INFORMATION SUBMITTED IS, TO THE BEST OF MY KNOWLEDGE AND BELIEF, TRUE, ACCURATE, AND COMPLETE. I AM AWARE THAT THERE ARE SIGNIFICANT PENALTIES FOR SUBMITTING FALSE INFORMATION, INCLUDING THE POSSIBILITY OF FINE AND IMPRISONMENT FOR KNOWING VIOLATIONS."

**BRENT WALKER** *11/29/21*  
 PRINT NAME (AUTHORIZED REPRESENTATIVE) DATE  
*[Signature]*  
 ADDRESS: 4800 ASHFORD DUNWOODY RD, DUNWOODY GA 30338  
 PHONE: 678-392-6857 FAX: 678-533-0702  
 EMAIL: BRENT.WALKER@DUNWOODYGA.GOV

**DESIGN PROFESSIONAL 7-DAY CERTIFICATION**

DATE OF INSPECTION: \_\_\_\_\_  
 GSWCC LEVEL II DESIGN PROFESSIONAL GSWCC CERTIFICATION NO. \_\_\_\_\_  
 THE INSPECTION REVEALED THE FOLLOWING DISCREPANCIES FROM THE EROSION, SEDIMENTATION, AND POLLUTION CONTROL PLANS:

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

THE DISCREPANCIES MUST BE ADDRESSED IMMEDIATELY AND A REINSPECTION SCHEDULED. WORK SHALL NOT PROCEED ON THE SITE UNTIL THE DESIGN PROFESSIONALS CERTIFICATION IS OBTAINED.




**ANTICIPATED ACTIVITY SCHEDULE**

ACTIVITY	MONTH								
	1	2	3	4	5	6	7	8	9
1 INSTALL SEDIMENT CONTROLS	X								
2 CLEARING AND GRUBBING									
3 DEMOLITION									
4 MASS GRADING									
5 STORM DRAINAGE INSTALLATION									
6 INSTALL SEDIMENT TRAPS @ SITS									
7 SANITARY SEWER INSTALLATION									
8 UTILITY									
9 BLDG CONST & PAVING									
10 DESILING OF STORM BASIN									
11 GRASS									
12 FINAL LANDSCAPING									
13 MAINTAIN EROSION CONTROL									
14 CLEAN UP									

NOTE: THE INSTALLATION OF EROSION CONTROL MEASURES AND PRACTICES SHALL BE INSTALLED PRIOR TO OR CONCURRENT WITH LAND DISTURBING ACTIVITIES. \_\_\_\_\_ REPRESENTS A 30-DAY PERIOD

**BEST MANAGEMENT PRACTICES SEQUENCE**

- PHASE I**
- INSTALL STABILIZED CONSTRUCTION EXIT(S).
  - INSTALL SILT FENCE(S) AND TREE PROTECTION FENCE(S) ON THE SITE. (CLEAR ONLY THOSE AREAS NECESSARY TO INSTALL SILT FENCE).
  - PREPARE TEMPORARY PARKING AND STORAGE AREA.
  - QA 7 DAY BMP INSPECTION REQUIRED**  
THE GENERAL CONTRACTOR SHALL CONTACT CHA TO SCHEDULE AN INSPECTION OF THE INSTALLATION OF THE INITIAL SEDIMENT REQUIREMENTS AND PERIMETER CONTROL BMP'S WITHIN 7 DAYS AFTER INSTALLATION.
  - CONSTRUCT AND STABILIZE SEDIMENT TRAP(S) WITH APPROPRIATE OUTFALL STRUCTURES. (CLEAR ONLY THOSE AREAS NECESSARY TO INSTALL BASINS AND TRAPS).
  - BEGIN CLEARING AND GRUBBING THE SITE.
  - BEGIN GRADING THE SITE.
  - START CONSTRUCTION OF THE BUILDING PAD AND STRUCTURES.
- PHASE II**
- TEMPORARY SEED, THROUGHOUT CONSTRUCTION, DENUEED AREAS THAT WILL BE INACTIVE FOR 14 DAYS OR MORE.
  - INSTALL UTILITIES, UNDERDRAINS, STORM SEWERS, CURBS AND GUTTERS.
  - INSTALL RIP-RAP AROUND OUTLET STRUCTURES AS EACH OUTLET STRUCTURE IS INSTALLED.
  - INSTALL INLET PROTECTION AT ALL STORM SEWER STRUCTURES AS EACH INLET STRUCTURE IS INSTALLED.
  - PERMANENTLY STABILIZE AREAS TO BE VEGETATED AS THEY ARE BROUGHT TO FINAL GRADE.
  - PREPARE SITE FOR PAVING.
- PHASE III**
- COMPLETE OFF SITE ROADWAY WORK AND ASSOCIATED UNDERGROUND UTILITIES INSTALLING BMP'S AS SHOWN.
  - PAVE THE SITE.
  - INSTALL APPROPRIATE INLET PROTECTION DEVICES FOR PAVED AREAS AS WORK PROGRESSES.
  - COMPLETE GRADING AND INSTALLATION OF PERMANENT STABILIZATION OVER ALL AREAS.
  - FILE NOTE.



**NOTE:**  
 IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO CONDUCT ALL MONITORING OF STORM WATER RUNOFF AS DICTATED BY THE NEW GA LAW "CLEAN WATER ACT" GENERAL PERMIT NO. GSP00001 GOVERNING EROSION CONTROL. ALL COSTS ARE TO BE INCLUDED IN BASE BID. CONTRACTOR IS RESPONSIBLE FOR ALL MONITORING FROM THE TIME LAND DISTURBING ACTIVITIES BEGIN UNTIL THE TIME "NOTICE OF TERMINATION" IS FILED. CONTRACTOR TO REFER TO EROSION CONTROL PLANS, SHEETS ES-1 THRU ES-3, AND GENERAL PERMIT NO. GSP00001 FOR ADDITIONAL NOTES AND INFORMATION.

**DESIGN PROFESSIONAL CERTIFICATIONS**

- "I CERTIFY THAT THE PERMITTEE'S EROSION, SEDIMENTATION AND POLLUTION CONTROL PLAN PROVIDES FOR AN APPROPRIATE AND COMPREHENSIVE SYSTEM OF BEST MANAGEMENT PRACTICES REQUIRED BY THE GEORGIA WATER QUALITY CONTROL ACT AND THE DOCUMENT "MANUAL FOR EROSION AND SEDIMENT CONTROL IN GEORGIA" (MANUAL) PUBLISHED BY THE GEORGIA SOIL AND WATER CONSERVATION COMMISSION AS OF JANUARY 1 OF THE YEAR IN WHICH THE LAND-DISTURBING ACTIVITY WAS PERMITTED, PROVIDES FOR THE SAMPLING OF THE RECEIVING WATERS) OR THE SAMPLING OF THE STORM WATER OUTFALLS AND THAT THE DESIGNED SYSTEM OF BEST MANAGEMENT PRACTICES AND SAMPLING METHODS IS EXPECTED TO MEET THE REQUIREMENTS CONTAINED IN THE GENERAL NPDES PERMIT NO. GSP100001."
- "I CERTIFY UNDER PENALTY OF LAW THAT THIS PLAN WAS PREPARED AFTER A SITE VISIT TO THE LOCATIONS DESCRIBED HEREIN BY MYSELF OR MY AUTHORIZED AGENT, UNDER MY DIRECT SUPERVISION."

**CHRISTOPHER MANES, P.E.**  
 PE # 032720  
 GSWCC CERTIFICATION NO. 10882  
 DATE: 01/07/2022

REPRESENTS NOTE/FEATURE WHICH CORRESPONDS WITH THE ESC&PC PLAN CHECKLIST. SEE SHEET ES-4 FOR ESC&PC CHECKLIST.

**DEVELOPER/OWNER:**  
 CITY OF DUNWOODY PARKS AND REC  
 4800 ASHFORD DUNWOODY ROAD  
 DUNWOODY, GA 30338  
 (678) 382-6857

**SITE OPERATOR/GENERAL CONTRACTOR:**

**SUPERINTENDENT:**


**ALLOWABLE NTU VALUE CHART (APPENDIX B)**

Waters Supporting Warm Water Fisheries

Site Size, acres	Surface Water Drainage Area, square miles							
	0-4.99	5-9.99	10-24.99	25-49.99	50-99.99	100-249.99	250-499.99	500+
1.00-10	75	150	200	400	750	750	750	750
10.01-25	50	100	100	200	300	500	750	750
25.01-50	50	50	100	100	200	300	750	750
50.01-100	50	50	50	100	100	150	300	600
100.01 +	50	50	50	50	50	100	200	100



**EROSION SEDIMENTATION, AND POLLUTION CONTROL PLAN NOTES**



GSWCC# 10882  
 EXP: 05/24/2024

Project Title  
**PERIMETER CENTER EAST PARK**  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOODY RD  
 DUNWOODY, GA 30338

**REVISIONS**

NO.	REVISIONS	BY


DRAWN BY: DMN  
 CHECKED BY: CLM  
 DATE: 01/07/2022  
 SCALE: NO SCALE  
 JOB No.: 20-LD-025 / 061964.00  
 SHEET NUMBER

**ES-5**


USER: 6674 - Jan 07, 2022 - 4:28pm  
 Z:\All Project Data\Projects\2020\20-LD-025 Main\DWG - LAYOUT: C-1 - PERIMETER CENTER EAST PARK, DUNWOODY, GA\LD\Production\Production Drawings\20-LD-025 MAIN.DWG



Know what's below.  
 Call before you dig.



REFER TO SHEET D-1A  
 FOR SITE PLAN DETAILS



LOCATION MAP  
 NOT TO SCALE

**SITE AREA DEMISE**

TRACT 1	1.348 ± AC.
TRACT 2	2.989 ± AC.
TRACT 3	2.296 ± AC.
<b>SITE AREA</b>	<b>6.633 ± AC.</b>

NOTE:  
 THIS CHART IS FOR CONCEPTUAL PURPOSES ONLY. ACREAGE ARE APPROXIMATE AND MAY VARY DEPENDING ON ACTUAL BOUNDARY SURVEY.

**PARKING CALCULATIONS**

REQUIRED PARKING	SPACES
ON-SITE PARKING	21 SPACES
OFF-SITE PARKING	16 SPACES
<b>TOTAL PARKING</b>	<b>37 SPACES</b>

**SITE PLAN NOTES**

- ALL WORK AND MATERIALS SHALL COMPLY WITH ALL CITY REGULATIONS AND CODES AND O.S.H.A. STANDARDS.
- ALL DISTURBED AREAS ARE TO RECEIVE FOUR INCHES OF TOPSOIL, SEED, MULCH AND WATER UNTIL A HEALTHY STAND OF GRASS IS ESTABLISHED.
- ALL ISLANDS WITH CURB & GUTTER SHALL BE LANDSCAPED. THOSE ISLANDS ARE TO HAVE 18" CURB & GUTTER. ALL REMAINING ISLANDS ARE TO BE STRIPED AS SHOWN.
- ALL CURBED RADII ARE TO BE 3' UNLESS OTHERWISE NOTED. STRIPED RADII ARE TO BE 3'.
- ALL DIMENSIONS AND RADII ARE TO THE FACE OF CURB UNLESS OTHERWISE NOTED.
- EXISTING STRUCTURES WITHIN CONSTRUCTION LIMITS ARE TO BE ABANDONED, REMOVED OR RELOCATED AS NECESSARY. ALL COST SHALL BE INCLUDED IN BASE BID.
- CONTRACTOR SHALL BE RESPONSIBLE FOR ALL RELOCATIONS, INCLUDING BUT NOT LIMITED TO, ALL UTILITIES, STORM DRAINAGE, SIGNS, TRAFFIC SIGNALS & POLES, ETC. AS REQUIRED. ALL WORK SHALL BE IN ACCORDANCE WITH GOVERNING AUTHORITIES' SPECIFICATIONS AND SHALL BE APPROVED BY SUCH. ALL COST SHALL BE INCLUDED IN BASE BID.
- TOTAL LAND AREA IS 6.633± ACRES.
- THE SITE WORK FOR THIS PROJECT SHALL MEET OR EXCEED "THE SITE WORK SPECIFICATIONS".
- REFER TO ELECTRICAL PLANS FOR SITE LIGHTING ELECTRICAL PLAN.
- ALL BOUNDARY AND TOPOGRAPHICAL INFORMATION SHOWN WAS TAKEN FROM A SURVEY BY PLANNERS AND ENGINEERS COLLABORATIVE DATED 08/21/2020.
- A PORTION OF THE PROPERTY LIES IN A 100-YEAR FLOODPLAIN OR IN AN IDENTIFIED "FLOOD PRONE AREA", AS DEFINED PURSUANT TO THE FLOOD DISASTER PROTECTION ACT OF 1973, AS AMENDED AS REFLECTED BY FLOOD INSURANCE RATE MAP PANEL 1308920022K DATED 08/15/2019.
- THE CURRENT ZONING OF ALL PROPERTY SHOWN FOR DEVELOPMENT IS "O-I". ADJACENT PROPERTY ZONED AS SHOWN.
- ALL GENERAL CONTRACTOR WORK TO BE COMPLETED (EARTHWORK, FINAL UTILITIES, AND FINAL GRADING) BY THE MILESTONE DATE IN PROJECT DOCUMENTS. OUTLOT AREA TO BE KEPT FREE OF JOB TRAILERS AND STORAGE AFTER THE CONTRACT MILESTONE DATE FOR THE OUTLOT. THE GENERAL CONTRACTOR TO PROVIDE CLEAR ACCESS FOR OUTLOT CONTRACTOR TO THE SPECIFIC PARCEL AT ALL TIMES AFTER MILESTONE DATE. PURCHASER OF OUTLOT TO PROVIDE PERMIT DOCUMENTS AND SWPPP REQUIRED BY STATE/LOCAL REQUIREMENTS FOR SPECIFIC OUTLOT.

**TRAIL NOTE**


TRAIL ALIGNMENT SHOWN IS FOR BUILDING PURPOSES ONLY. BASIS OF TRAIL DESIGN HAS BEEN DEVELOPED BY USING SURVEYED TOPOGRAPHY, AND APPLYING DESIRED HIKING TRAIL DETAILS AND GRADIENTS. ALL LAYOUT AND FINAL TRAIL ALIGNMENTS TO BE FIELD VERIFIED PRIOR TO CONSTRUCTION. SEE SHEET L-7 FOR MORE DETAIL.

**LEGEND FOR PROPOSED IMPROVEMENTS**

- PROPOSED BUILDING
- PROPOSED CURB AND GUTTER
- PROPOSED PARKING SPACES
- STANDARD DUTY ASPHALTIC PAVEMENT
- PROPOSED TRAIL
- PROPOSED SIDEWALK



**SITE PLAN**



GSWCC# 10882  
 EXP: 05/24/2024

Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338




REVISIONS	BY

DRAWN BY: DMN  
 CHECKED BY: CLM  
 DATE: 01/07/2022  
 SCALE: 1" = 40'  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

**C-1**

**GRADING/DRAINAGE PLAN LEGEND**

- STORM SEWER PIPING
- JUNCTION BOX/STORM MANHOLE/UP-FLO FILTER
- ▭ DRAINAGE STRUCTURE INDICATOR
- SLOPE ARROW
- ▬ RIP-RAP APRON
- ▭ PRECAST HEADWALL STRUCTURE GDOT STD 1125 ENERGY DISSIPATER
- ▭ CURB INLET (W/ NON-MOUNTABLE HOOD & GRATE) GDOT STD 1019A TYPE "E"
- ▭ FLARED END SECTION GDOT STD 1120
- TC = TOP OF CURB
- TP = TOP OF PAVEMENT
- FG = FINISHED GRADE
- ▭ BIOSLOPE. SEE DETAIL SHEET.



**SITE GRADING NOTES**


1. CONTRACTOR IS RESPONSIBLE FOR DEMOLITION OF EXISTING STRUCTURES INCLUDING REMOVAL OF ANY EXISTING UTILITIES SERVING THE STRUCTURE. UTILITIES ARE TO BE REMOVED TO THE RIGHT-OF-WAY.
2. THE CONTRACTOR IS SPECIFICALLY CAUTIONED THAT THE LOCATION AND/OR ELEVATION OF ALL EXISTING UTILITIES (ABOVE OR BELOW GROUND) AS SHOWN ON THESE PLANS ARE APPROXIMATE AND WERE LOCATED BASED ON EITHER VISUAL OBSERVATIONS AT THE SITE, EXISTING SURVEYS AND/OR FROM UTILITY OWNERS. CHA DOES NOT GUARANTEE THAT EXISTING UTILITY LOCATIONS SHOWN ARE EXACT. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO DETERMINE THE EXACT LOCATIONS OF EXISTING UTILITIES (ABOVE OR BELOW GROUND) BEFORE BEGINNING ANY CONSTRUCTION. THE CONTRACTOR SHALL CALL THE APPROPRIATE UTILITY COMPANIES AND THE UTILITIES' PROTECTION CENTER AT LEAST 72 HOURS BEFORE ANY EXCAVATION TO REQUEST EXACT FIELD LOCATION OF UTILITIES. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO NOTIFY OWNER AND/OR ENGINEER OF ANY UTILITY CONFLICTS WITH THE PROPOSED IMPROVEMENTS SHOWN ON THE PLANS.
3. ALL CUT OR FILL SLOPES SHALL BE 2:1 OR FLATTER UNLESS OTHERWISE NOTED.
4. PRECAST STRUCTURES MAY BE USED AT CONTRACTORS OPTION.
5. STORM PIPE TYPE AND JOINTS SHALL BE AS FOLLOWS:
  - A. CONCRETE PIPE (RCP): ASTM C 76.
    - FOR FILLS LESS THAN 15 FEET OVER TOP OF PIPE: CLASS III OR GREATER SHALL BE USED.
    - FOR FILLS 15 FEET TO 20 FEET OVER PIPE: CLASS IV OR GREATER SHALL BE USED.
    - FOR FILLS GREATER THAN 20 FEET OVER PIPE: CLASS V OR GREATER SHALL BE USED.
  - B. JOINT MATERIAL:
    - a. RUBBER O-RING GASKET: AASHTO M 198, TYPE B OR ASTM C 443
    - b. BITUMEN OR BUTYL-RUBBER SEALANT: ASTM C990.
    - FLARED END SECTIONS: ASTM C 76 OR, FOR SECTIONS WITH TIE WALL, AASHTO M 170.
  - C. HIGH DENSITY POLYETHYLENE PIPE (HDPE): AASHTO M 252 TYPE S, M 294 TYPE S, OR ASTM F 2306 SMOOTH INTERIOR/ANNULAR EXTERIOR.
    - JOINT MATERIAL:
      - a. RUBBER GASKET.
        - 1) ADS N-12 WT BY ADVANCED DRAINAGE SYSTEMS, INC
        - 2) ADS N-12 ST BY ADVANCED DRAINAGE SYSTEMS, INC.
        - 3) BLUE SEAL BY HANCOR, INC.
        - 4) SURE-LOK BY HANCOR, INC.
      - b. CORRUGATED COUPLING BANDS.
        - 1) HI-Q BY HANCOR, INC.
        - 2) ADS N-12 BY ADVANCED DRAINAGE SYSTEMS, INC.
      - c. PE WRAP.
6. EXISTING DRAINAGE STRUCTURES TO BE INSPECTED AND REPAIRED AS NEEDED, AND EXISTING PIPES TO BE CLEANED OUT TO REMOVE ALL SILT AND DEBRIS.
7. EXISTING GRADE CONTOUR SHOWN AT 1 FOOT INTERVALS.
8. PROPOSED GRADE CONTOUR SHOWN AT 1 FOOT INTERVALS.
9. IF ANY EXISTING STRUCTURES TO REMAIN ARE DAMAGED DURING CONSTRUCTION IT SHALL BE THE CONTRACTORS RESPONSIBILITY TO REPAIR AND/OR REPLACE THE EXISTING STRUCTURE AS NECESSARY TO RETURN IT TO EXISTING CONDITIONS OR BETTER.
10. ALL STORM PIPE ENTERING STRUCTURES SHALL BE GROUTED TO ASSURE CONNECTION AT STRUCTURE IS WATERTIGHT.
11. ALL STORM SEWER MANHOLES IN PAVED AREAS SHALL BE FLUSH WITH PAVEMENT, AND SHALL HAVE TRAFFIC BEARING RING & COVERS. MANHOLES IN UNPAVED AREAS SHALL BE 12" ABOVE FINISH GRADE. LIDS SHALL BE LABELED "STORM SEWER".
12. THE CONTRACTOR SHALL ADHERE TO ALL TERMS & CONDITIONS AS OUTLINED IN THE GENERAL N.P.D.E.S. PERMIT FOR STORMWATER DISCHARGE ASSOCIATED WITH CONSTRUCTION ACTIVITIES.
13. CONTRACTOR SHALL ADJUST AND/OR CUT EXISTING PAVEMENT AS NECESSARY TO ASSURE A SMOOTH FIT AND CONTINUOUS GRADE.
14. CONTRACTOR SHALL ASSURE POSITIVE DRAINAGE AWAY FROM BUILDINGS FOR ALL NATURAL AND PAVED AREAS.
15. TOPOGRAPHIC INFORMATION TAKEN FROM A TOPOGRAPHIC SURVEY BY PLANNERS AND ENGINEERS COLLABORATIVE. IF CONTRACTOR DOES NOT ACCEPT EXISTING TOPOGRAPHY AS SHOWN ON THE PLANS, WITHOUT EXCEPTION, HE SHALL HAVE MADE, AT HIS EXPENSE, A TOPOGRAPHIC SURVEY BY A REGISTERED LAND SURVEYOR AND SUBMIT IT TO THE OWNER FOR REVIEW.
16. ALL UNSURFACED AREAS DISTURBED BY GRADING OPERATION SHALL RECEIVE 4 INCHES OF TOPSOIL. CONTRACTOR SHALL APPLY STABILIZATION FABRIC TO ALL SLOPES AS INDICATED ON THE EROSION CONTROL PLANS. CONTRACTOR SHALL GRASS DISTURBED AREAS IN ACCORDANCE WITH CITY SPECIFICATIONS UNTIL A HEALTHY STAND OF GRASS IS OBTAINED.
17. CONSTRUCTION SHALL COMPLY WITH ALL APPLICABLE GOVERNING CODES AND BE CONSTRUCTED TO SAME.
18. ALL STORM STRUCTURES SHALL HAVE A SMOOTH UNIFORM POURED MORTAR INVERT FROM INVERT-IN TO INVERT-OUT.
19. CONTRACTOR TO CONTACT THE FIRE DEPARTMENT FOR BLASTING REQUIREMENTS.
20. WHERE ASPHALT OVERLAY IS SPECIFIED ON THE PLANS, THE CONTRACTOR SHALL PROVIDE LEVELING, WHERE NECESSARY, TO ACHIEVE THE PROPOSED GRADES SPECIFIED ON THE GRADING PLAN. THE CONTRACTOR SHALL INCLUDE ALL COSTS IN BASE BID.
21. CONTRACTOR SHALL VERIFY BENCHMARKS PRIOR TO SETTING FINISHED GRADES.

**\* STRUCTURE TYPE**

CURB INLET - GDOT STANDARD 1019A TYPE E. (SEE DETAIL SHEETS)  
 JUNCTION BOX - SEE DETAIL SHEETS.  
 HEADWALL - SEE DETAIL SHEETS.  
 FLARED END SECTION - SEE DETAIL SHEETS.  
 UP-FLO FILTER - SEE DETAIL SHEETS.

**\*\* PIPE TYPE**

UNLESS A PIPE TYPE MATERIAL IS SPECIFIED IN THE DRAINAGE SCHEDULE, THE CONTRACTOR MAY USE AT HIS DISCRETION ANY OF THE PIPE MATERIALS LISTED AS APPROVED STORM PIPE MATERIALS IN THE SITE GRADING NOTES.



**REFER TO SHEETS D-2A & D-2B FOR GRADING AND DRAINAGE DETAILS**



GSWCC# 10882  
 EXP: 05/24/2024


Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**


REVISIONS	BY

DRAWN BY DMN  
 CHECKED BY CLM  
 DATE: 01/07/2022  
 SCALE: 1" = 40'  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER


**C-2**

USER: 6674 - Jan 07, 2022 - 4:28pm  
 Z:\All Project Data\Projects\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 MAIN.DWG - LAYOUT: C-2, VERSION: -----






- ### DEKALB COUNTY NOTES
- ALL DESIGN AND CONSTRUCTION FOR WATER, SEWER, FIRE LINES, LIFT STATIONS AND BACKFLOW PREVENTION SHALL COMPLY WITH DEKALB COUNTY DEPARTMENT OF WATERSHED MANAGEMENT DESIGN STANDARD LATEST EDITION. ACTUAL FIELD CONDITIONS MAY DICTATE MORE STRINGENT REQUIREMENTS IF DETERMINED NECESSARY BY THE CONSTRUCTION INSPECTOR.
  - DEVELOPER SHALL PROVIDE RECORD DRAWINGS "AS-BUILT PLANS" AND "FINAL PLANS" IN HARD COPY AND ELECTRONIC FORMAT, AS WELL AS, RECORD ALL EASEMENTS THAT WILL BE DEDICATED TO DEKALB COUNTY IN THE COURT HOUSE, PRIOR TO APPROVAL OF THE "AS-BUILT PLANS".
  - FIELD CHANGES DURING CONSTRUCTION MUST BE SUBMITTED FOR REVIEW AND APPROVED BY THE DEKALB COUNTY DEPARTMENT OF WATERSHED MANAGEMENT BEFORE CHANGES ARE IMPLEMENTED.
  - PROJECTS LOCATED WITHIN THE CITIES, THE DEVELOPER SHALL PROVIDE A MAINTENANCE BOND TO DEKALB COUNTY WATERSHED MANAGEMENT PRIOR TO APPROVAL OF AS-BUILT PLANS.
  - CONTRACTOR MUST JET CLEAN AND T.V. SANITARY SEWER AFTER ALL CONNECTIONS IS MADE TO THE EXISTING SEWER LINE LOCATIONS. TRACER WIRE IS TO BE INSTALLED FOR ALL PVC PIPES.
  - WATER AND SEWER FEES NEED TO BE PAID UNDER THE FOLLOWING CIRCUMSTANCES:
    - NEW CONSTRUCTION, RE-DEVELOPMENT, ADDITIONS, CHANGE OF USE, ETC.
    - THESE FEES ARE TO BE PAID AT 330 WEST PONCE DE LEON AVE, 2ND FLOOR.
    - FAILURE IN PAYMENT OF THESE FEES WILL RESULT IN POSTPONEMENT OF THE PLAN REVIEW PROCESS.
    - CALL (404) 371-4918 FOR FEE CALCULATIONS OR ANY QUESTIONS.
  - CONTRACTOR TO NOTIFY THE DWM CONSTRUCTION INSPECTOR AT LEAST 72 HOURS PRIOR TO COMMENCING CONSTRUCTION ACTIVITIES.
  - FIRE LINES, F.O.G., BACKFLOW PREVENTION AND LIFT STATIONS REQUIRE A SEPARATE REVIEW.
  - PROJECTS ENTERING A STATE OF GEORGIA CONTROLLED RIGHT-OF-WAY WILL REQUIRE DOT PERMIT. ALL REQUIRED MATERIALS TO BE SUBMITTED TO DWM. REFER TO GDOT CHECKLIST FOR REQUIREMENTS.



REFER TO SHEETS D-3A FOR UTILITY PLAN DETAILS



LOCATION MAP  
NOT TO SCALE

### SITE UTILITY NOTES




- ALL FILL MATERIAL IS TO BE IN PLACE, AND COMPACTED BEFORE INSTALLATION OF PROPOSED UTILITIES.
- CONTRACTOR SHALL NOTIFY THE UTILITY AUTHORITIES INSPECTORS 72 HOURS BEFORE CONNECTING TO ANY EXISTING LINE.
- SANITARY SEWER PIPE SHALL BE AS FOLLOWS:
  - 8" PVC SDR35 PER ASTM D 3034, FOR PIPES LESS THAN 12' DEEP
  - 6" PVC SDR26 PER ASTM D 3034, FOR PIPES MORE THAN 12' DEEP
  - 6" PVC SCHEDULE 40
  - DUCTILE IRON PIPE PER ANWA C150
- WATER LINES SHALL BE AS FOLLOWS:
  - PIPE SIZES LESS THAN 3-INCHES THAT ARE INSTALLED BELOW GRADE AND OUTSIDE BUILDING SHALL COMPLY WITH ONE OF A COMBINATION OF THE FOLLOWING:
    - 4.1.1.1. SEAMLESS COPPER TUBING - TYPE "M" SOFT COPPER, ASTM B 88.
    - 4.1.1.1. FITTINGS: WROUGHT COPPER (95-5 TIN ANTIMONY SOLDER JOINT), ASME B 16.22.
    - 4.1.2. POLYVINYL CHLORIDE (PVC) WATER PIPE - PIPE, ASTM D 2241, WITH SDR 21 RATING, CONTINUALLY MARKED WITH MANUFACTURER'S NAME, PIPE SIZE, CELL CLASSIFICATION, SDR RATING, AND ASTM D 1784 MATERIAL CLASSIFICATION.
    - 4.1.1.1. PIPE JOINTS: INTEGRALLY MOLDED BELL ENDS, ASTM D 2672.
    - 4.1.1.2. CEMENT PRIMER: ASTM F 296.
    - 4.1.1.3. SOLVENT CEMENT: ASTM - D 2564.
  - MINIMUM TRENCH WIDTH SHALL BE 2 FEET.
  - ALL WATER JOINTS ARE TO BE MECHANICAL JOINTS WITH THRUST BLOCKING AS CALLED OUT IN SPECIFICATIONS.
  - ALL UTILITIES SHOULD BE KEPT TEN (10') APART (PARALLEL) OR WHEN CROSSING 18" APART (OUTSIDE EDGE OF PIPE TO OUTSIDE EDGE OF PIPE).
  - CONTRACTOR SHALL MAINTAIN A MINIMUM OF 4 FEET COVER ON ALL WATERLINES IN UNPAVED AREAS. DCDWM MAY REQUIRE COVER GREATER THAN 4 FEET FOR WATERLINES UNDER ROADS WITH HEAVY VEHICULAR LOADS AND TRAFFIC.
  - SANITARY SEWER PIPE COVER PER DCDWM REQUIREMENTS:
    - PVC IN UNPAVED AREAS: DEPTH OF COVER SHALL BE A MINIMUM OF 4 FEET.
    - PVC IN PAVED AREAS/R.O.W.: DEPTH OF COVER SHALL BE BETWEEN 7 FEET (MIN.) AND 15 FEET (MAX).
    - PIPES WITH DEPTH OF COVER LESS THAN 7 FEET IN PAVED AREAS SHALL BE DIP.
    - PIPES WITH DEPTH OF COVER LESS THAN 4 FEET IN UNPAVED AREAS SHALL BE DIP IN A STEEL CASING.
  - IN THE EVENT OF A VERTICAL CONFLICT BETWEEN WATERLINES, SANITARY LINES, STORM LINES AND GAS LINES (EXISTING AND PROPOSED), THE SANITARY LINE SHALL BE DUCTILE IRON PIPE WITH MECHANICAL JOINTS AT LEAST 10 FEET ON BOTH SIDES OF CROSSING. THE WATERLINE SHALL HAVE MECHANICAL JOINTS WITH APPROPRIATE THRUST BLOCKING AS REQUIRED TO PROVIDE A MINIMUM OF 18" CLEARANCE MEETING REQUIREMENTS OF ANSI A21.10 OR ANSI 21.11 (AWWA C-151) (CLASS 50).
  - LINES UNDERGROUND SHALL BE INSTALLED, INSPECTED AND APPROVED BEFORE BACKFILLING.
  - TOPS OF EXISTING MANHOLES SHALL BE RAISED AS NECESSARY TO BE FLUSH WITH PROPOSED ELEVATIONS, AND TO BE ONE FOOT ABOVE FINISHED GROUND ELEVATIONS WITH WATER TIGHT LIDS.
  - ALL CONCRETE FOR ENCASEMENTS SHALL HAVE A MINIMUM 28 DAY COMPRESSION STRENGTH AT 3000 P.S.I.
  - DRAWINGS DO NOT PURPORT TO SHOW ALL EXISTING UTILITIES.
  - EXISTING UTILITIES SHALL BE VERIFIED IN FIELD PRIOR TO INSTALLATION OF ANY NEW LINES.
  - REFER TO INTERIOR PLUMBING DRAWINGS FOR THE IN OF ALL UTILITIES.
  - CONTRACTOR IS RESPONSIBLE FOR COMPLYING TO THE SPECIFICATIONS OF THE LOCAL AUTHORITIES WITH REGARDS TO MATERIALS AND INSTALLATION OF THE WATER AND SEWER LINES.
  - ALL NECESSARY INSPECTIONS AND/OR CERTIFICATIONS REQUIRED BY CODE AND/OR UTILITY SERVICE COMPANIES SHALL BE PERFORMED PRIOR TO ANNOUNCED BUILDING POSSESSION AND THE FINAL CONNECTION OF SERVICE.
  - CONTRACTOR SHALL COORDINATE WITH ALL UTILITY COMPANIES FOR INSTALLATION REQUIREMENTS AND SPECIFICATIONS.
  - CONTRACTOR TO PROVIDE TRENCHING, CONDUIT, FULL WIRE AND BACKFILL FOR TELEPHONE AND ELECTRIC LINES.
  - THE CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING THE EXACT LOCATION, SIZE, AND MATERIAL OF ANY EXISTING WATER OR SEWER FACILITY PROPOSED FOR CONNECTION OR USE BY THIS PROJECT. THE RELOCATION OF ANY WATER/SEWER FACILITY REQUIRED TO AVOID ANY PART OF THIS DEVELOPMENT IS THE RESPONSIBILITY OF THE DEVELOPER.
  - ALL CONSTRUCTION TO CONFORM TO APPLICABLE COUNTY SPECIFICATIONS AND IN ACCORDANCE WITH COUNTY ORDINANCES.
  - TRENCHES OF 20 FEET OR GREATER REQUIRE SHORING. SHORING DESIGN TO BE CERTIFIED BY A PROFESSIONAL ENGINEER. TRENCH SAFETY REQUIREMENTS WILL BE STRICTLY ENFORCED. CONTRACTOR TO MEET OR EXCEED ALL OSHA STANDARDS.
  - REFER TO ARCHITECTURAL PLANS FOR SITE LIGHTING AND ELECTRICAL PLANS.

### NOTICE TO GENERAL CONTRACTOR REGARDING UTILITY INSTALLATION:

THE INFORMATION SHOWN ON THESE PLANS RELATED TO THE EXISTING SUBSURFACE UTILITY LINES IS BASED ON FIELD RUN SURVEY, AS-BUILT RECORDS AND/OR UTILITY COMPANY RECORDS AND IS CORRECT TO THE BEST KNOWLEDGE OF THE ENGINEER. HOWEVER, SINCE THE EXISTING SUBSURFACE FACILITIES HAVE NOT BEEN EXPOSED AND VERIFIED, THE INFORMATION PROVIDED IS NOT TO BE CONSIDERED PRECISE. THE GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING THE EXACT LOCATION, SIZE, MATERIAL AND INVERT ELEVATION AT THE PROPOSED (IE-IN POINT(S)) OF THE EXISTING SUBSURFACE UTILITIES PRIOR TO ORDERING MATERIALS TO INSTALL THE PROPOSED UTILITIES. THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER IF CONDITIONS IDENTIFIED IN THE FIELD ARE SUBSTANTIALLY DIFFERENT THAN THOSE SHOWN ON THE PLANS. IT IS STRONGLY RECOMMENDED THAT FIELD VERIFYING OCCUR DURING THE INITIAL STAGES OF CONSTRUCTION AND PRIOR TO ORDERING OF MATERIALS. THE OWNER WILL NOT ACCEPT ANY CHANGE ORDERS ASSOCIATED WITH UNEXPECTED FIELD CONDITIONS THAT ARE NOT IDENTIFIED PRIOR TO ORDERING MATERIALS FOR THE PROPOSED RELOCATIONS. CONTRACTOR SHALL COORDINATE THE TIMING OF THE RELOCATIONS WITH THE RESPECTIVE UTILITY SERVICE PROVIDERS. LINES TO BE RELOCATED SHALL REMAIN OPERATIONAL AT ALL TIMES UP UNTIL THE NEW SERVICE LINE BECOMES ACTIVE. CONNECTIONS BETWEEN EXISTING AND RELOCATED LINES THAT REQUIRE TEMPORARY INTERRUPTION OF SERVICE SHALL BE PERFORMED ONLY AT LOW DEMAND TIMES WHICH MAY REQUIRE WORK TO BE PERFORMED AT NIGHT AND/OR ON WEEKENDS. CONTRACTOR SHALL INCLUDE ALL COSTS FOR SUCH WORK IN THE BASE BID.



### UTILITY PLAN



GSWCC# 10882  
EXP: 05/24/2024

Project Title  
PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338


REVISIONS	BY

DRAWN BY DMN  
CHECKED BY CLM  
DATE: 01/07/2022  
SCALE: 1" = 40'  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER


**C-3**

USER: 6674 - Jan 07, 2022 - 5:55pm  
 Z:\All Project Data\Projects\2020\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 MAIN.dwg - LAYOUT: C-3 VERSION:


# STORM SEWER



**ST1 THRU ST3**  
scale: 1"=40' horizontal  
1"=4' vertical



**ST2 TO ST4 THRU ST6**  
scale: 1"=40' horizontal  
1"=4' vertical




**ST7 THRU ST8**  
scale: 1"=40' horizontal  
1"=4' vertical


STRUCTURE TABLE				
STRUCTURE #	STRUCTURE TYPE	TOP OF CASTING	INVERT OUT	INVERT IN
ST1	HEADWALL			925.00 (ST2)
ST2	JUNCTION BOX	937.25	926.20	926.40 (ST3) 931.00 (ST4)
ST3	FLARED END SECTION		933.00	
ST4	FIRST DEFENSE	940.25	934.00	934.00 (ST5)
ST5	CURB INLET	940.00	935.20	935.30 (ST6)
ST6	CURB INLET	940.00	936.00	
ST7	OPEN PIPE	938.75		937.00 (ST8)
ST8	TRENCH DRAIN		939.00	

PIPE TABLE			
PIPE NAME	LENGTH	SIZE	SLOPE
ST1-ST2	11	30	11.31%
ST2-ST3	62	30	10.56%
ST2-ST4	44	24	6.85%
ST4-ST5	20	24	5.91%
ST5-ST6	39	18	1.80%
ST7-ST8	30	12	6.70%


# SANITARY SEWER




**SS0X THRU SS6**  
scale: 1"=40' horizontal  
1"=4' vertical



**SS1 THRU SS7**  
scale: 1"=40' horizontal  
1"=4' vertical



**SS3 THRU SS10**  
scale: 1"=40' horizontal  
1"=4' vertical



**SS8 THRU SS11**  
scale: 1"=40' horizontal  
1"=4' vertical

STRUCTURE TABLE				
STRUCTURE #	STRUCTURE TYPE	TOP OF CASTING	INVERT OUT	INVERT IN
SS0X	EXISTING MANHOLE	947.11		936.00 (SS1)
SS1	CLEANOUT		938.00	937.90 (SS2) 938.90 (SS7)
SS2	CLEANOUT		938.40	938.40 (SS3)
SS3	CLEANOUT		938.85	938.85 (SS4) 939.35 (SS8)
SS4	CLEANOUT		939.15	939.15 (SS5)
SS5	CLEANOUT		939.45	939.45 (SS6)
SS6	AT BUILDING		939.50	
SS7	AT BUILDING		939.80	
SS8	CLEANOUT		939.75	940.00 (SS11) 939.75 (SS9)
SS9	CLEANOUT		940.00	940.00 (SS10)
SS10	AT BUILDING		940.50	
SS11	AT BUILDING		940.50	

PIPE TABLE			
PIPE NAME	LENGTH	SIZE	SLOPE
SS0X-SS1	21	6	9.58%
SS1-SS2	25	6	2.03%
SS1-SS7	8	3	11.19%
SS2-SS3	22	6	2.08%
SS3-SS4	14	4	2.11%
SS3-SS8	17	6	2.29%
SS4-SS5	13	4	2.24%
SS5-SS6	2	4	2.00%
SS8-SS9	9	2.5	2.81%
SS9-SS10	4	2.5	12.50%

**NOTE**  
CONTRACTOR IS RESPONSIBLE FOR COMPARING THE STORM AND SANITARY SEWER SCHEDULES WITH THE PROFILES FOR THE STORM AND SEWER LINES AND INFORMING THE ENGINEER OF ANY CONFLICTS OR DISCREPANCIES PRIOR TO COMMENCEMENT OF CONSTRUCTION.

## PROFILES AND TABLES



GSWCC# 10882  
EXP: 05/24/2024

Project Title  
PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY: DMN  
CHECKED BY: CLM  
DATE: 01/07/2022  
SCALE: 1"= 60'  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER















# PR-1

USER: 6674 - Jan 07, 2022 - 4:52pm  
Z:\All Projects\2020\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 MAIN.dwg - LAYOUT: PR-1, VERSION: -----



Know what's below.  
Call before you dig.

USER: 6674 - Jan 07, 2022 - 4:30pm  
 Z:\All Project Data\Projects\2020\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 Details.dwg



GSWC# 10882  
 EXP: 05/24/2024

Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338



REVISIONS	BY

DRAWN BY: DMN  
 CHECKED BY: CLM  
 DATE: 01/07/2022  
 SCALE: NO SCALE  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

SITE PLAN DETAILS  
 D-1A



USER: 6674 - Jan 07, 2022 - 4:30pm  
Z:\All Project Data\Projects\2020\20-LD-025 Perimeter Center East Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 Details.dwg



**Notes**

1. MANHOLE WALL AND SLAB THICKNESSES ARE NOT TO SCALE.
2. CONTACT HYDRO INTERNATIONAL FOR A BOTTOM OF STRUCTURE ELEVATION PRIOR TO SETTING FIRST DEFENSE MANHOLE.
3. CONTRACTOR TO CONFIRM RIM, PIPE INVERTS, PIPE DIA. AND PIPE ORIENTATION PRIOR TO RELEASE OF UNIT TO FABRICATION.

Stormwater Solutions  
94 Hutchins Drive  
Portland, Maine 04102  
Tel: (207) 756-6200  
Fax: (207) 756-6212  
stormwater@hydro-int.com

**GEOTECHNICAL NOTES:**

**SOIL MATERIALS**

A. Satisfactory soil materials are defined as those complying with ASTM D2487 soil classification groups CL, ML, GC, SC, GW, GP, GM, SM, SW, and SP.

B. Unsatisfactory soil materials are defined as those complying with ASTM D2487 soil classification groups CH, OL, OH, MH, ML and PT.

C. Backfill and Fill Materials: Satisfactory soil materials free of clay, rock or gravel larger than 4 inches in any dimension (2 inches for material used in trench backfill), debris, waste, frozen materials, organics, vegetation and other deleterious matter. Fill material should be moisture conditioned to maintain a moisture content within 3 percentage points above and below the soil's optimum moisture content as determined by the standard Proctor test. Fill and backfill to be used onsite shall be evaluated and approved by a Geotechnical Engineer.

D. Imported material for structural fill shall comply with ASTM D2487 soil classification groups CL, ML, SC, SM or GW. Offsite borrow materials may be used as structural fill provided that they have a liquid limit (LL) and a plastic index (PI) not exceeding 40 and 20 percent, respectively and moisture conditioned to maintain a moisture content within three percentage points above and below the optimum moisture contents.

**2.2 BACKFILL AND FILL**

A. Backfill excavations as promptly as work permits, but not until completion of the following:

1. Acceptance by Local authority having jurisdiction of construction below finished grade, including perimeter insulation.
2. Review, approval, and recording of the locations of underground utilities.
3. Removal of concrete formwork.
4. Removal of shoring and bracing (including backfilling of voids with satisfactory materials).
5. Removal of trash and debris from excavation.
6. Permanent or temporary horizontal bracing is in place on horizontally supported walls.

B. Place backfill on subgrades free of mud, frost, snow or ice.

C. Ground Surface Preparation: Remove vegetation, debris, obstructions, and deleterious materials from ground surface prior to placement of fills.

D. Bench sloped surfaces steeper than 1 vertical to 4 horizontal so fill material will bond with existing material. Plow, scarify, bench or break up sloped surfaces flatter than 1 vertical to 4 horizontal so fill material will bond with existing material.

E. Place soil material in layers to require subgrade elevations, for each area classification listed below, using materials listed above.

1. Under grassed areas, use satisfactory excavated or borrow material.
2. Under walks, curbs, and pavements, use satisfactory excavated or borrow material.
3. Under building slabs, use satisfactory excavated or borrow materials and drainage/porous fill material as indicated.

**2.3 UTILITY TRENCH BACKFILL**

A. Place backfill on subgrades free of mud, frost, snow, or ice.

B. Place and compact bedding course in trench bottoms and where indicated. Shape bedding course to provide continuous support for bells, joints, and barrels of pipes and for joints, fittings, and bodies of conduits.

C. Backfill trenches with concrete where trench excavations pass within 18 inches of column or wall footings and that are carried below bottom of such footings or that pass under wall footings. Place concrete to level of bottom of adjacent footing.

D. Provide 4-inch (100-mm) thick, concrete-base slab support for piping or conduit less than 30 inches (750 mm) below surface of roadways. After installing and testing, completely encase piping or conduit in a minimum of 4 inches (100 mm) of concrete before backfilling or placing roadway subbase.

E. Place and compact initial backfill of satisfactory soil, free of particles larger than 1 inch (25 mm) in any dimension, to a height of 12 inches (300 mm) over the utility pipe or conduit.

F. Carefully compact initial backfill under pipe haunches and compact evenly up on both sides and along the full length of utility piping or conduit to avoid damage or displacement of piping or conduit. Coordinate backfilling with utilities testing.

G. Controlled Low-Strength Material: Place initial backfill of controlled low-strength material to a height of 12 inches (300 mm) over the utility pipe or conduit.

H. Backfill voids with satisfactory soil while installing and removing shoring and bracing.

I. Place and compact final backfill of satisfactory soil to final subgrade elevation.

J. Controlled Low-Strength Material: Place final backfill of controlled low-strength material to final subgrade elevation.

K. Install warning tape directly above utilities, 12 inches (300 mm) below finished grade, except 6 inches (150 mm) below subgrade under pavements and slabs.

L. Do not backfill trenches until any required testing and inspections have been completed and Owner's Geotechnical Engineer and authority having jurisdiction authorizes backfilling. Backfill carefully to avoid damage or displacement of pipe systems.

M. Under piping and conduit and equipment, use crushed stone where required over rock bearing surface and for correction of unauthorized excavation. Shape excavation bottom to fit bottom 90 degrees of cylinder.

N. Place backfill and fill materials evenly adjacent to structures, piping, or conduit to required elevations. Prevent wedging action of backfill against structures or displacement of piping or conduit by carrying material uniformly around structure, piping, or conduit to approximately same elevation in each lift.

**2.4 SOIL MOISTURE CONTROL**


A. Uniformly moisten or aerate subgrade and each subsequent fill or backfill soil layer before compaction to within 3 percentage points of optimum moisture content as determined by the standard proctor test (ASTM D-698).

1. Do not place backfill or fill soil material on surfaces that are muddy, frozen, or contain frost or ice.
2. Remove and replace, or scarify and air dry otherwise satisfactory soil material that exceeds optimum moisture content by 3 percentage points and is too wet to compact to specified dry unit weight.


B. Moisture Control: Where subgrade or layer of soil material must be moisture conditioned before compaction, uniformly apply water to surface of subgrade or layer of soil material. Apply water in minimum quantity as necessary to prevent free water from appearing on surface during or subsequent to compaction operations. Maintain the moisture content of the structural fill materials to within 3 percentage points of the optimum moisture content until permanently covered.

C. Remove and replace, or scarify and air dry, soil material that is too wet to permit compaction to required density.

1. Stockpile or spread soil material that has been removed because it is too wet to permit compaction. Assist drying by discing, harrowing, or pulverizing until moisture content is reduced to a satisfactory value.
2. Work wet materials as directed by the Owner's Geotechnical Engineer. Base bids on working material daily for a maximum of five days of acceptable weather.
3. No additional payment will be made for these operations.
4. Time extensions will not be granted for working wet material on site.



**CONCRETE ANCHOR FOR STORM OR SEWER PIPE**  
N.T.S.



**BIOSLOPE CROSS SECTION**  
N.T.S.

**2.5 COMPACTION OF SOIL BACKFILL AND FILLS**

A. Place backfill and fill materials in layers not more than 8 inches in loose depth for material compacted by heavy compaction equipment, and not more than 4 inches in loose depth for material compacted by hand-operated tampers.

B. Before compaction, moisten or aerate each layer as necessary to provide optimum moisture content. Compact each layer to required percentage of maximum dry density or relative dry density for each area classification. Do not place backfill or fill material on surfaces that are muddy, frozen, or contain frost or ice.

C. Control soil and fill compaction, providing minimum percentage of density indicated for each area classification indicated below. Correct improperly compacted areas or lifts as directed by Engineer if soil density tests indicate inadequate compaction.

D. Percentage of Maximum Density Requirements: Compact soil to not less than the following percentages of maximum density at a moisture content within 3 percentage points of optimum in accordance with ASTM D698:

1. **Building Areas** - Compact the fill to 98 percent of the soil's maximum standard Proctor density value (ASTM D-698). In cut areas, the subgrade should be proofrolled and if found unstable, it should be scarified and re-compacted to 98 percent of the soil's maximum standard Proctor density value. Field density testing frequency should be performed as one test per lift for every 2,500 square feet.
2. **Pavement Areas** - Compact the upper 12 inches of subgrade in fill areas and the upper 12 inches in cut areas to 98 percent of the soil's maximum standard Proctor density value (ASTM D-698) and 95 percent of the soil's maximum standard Proctor density value below this level. Field density testing should be performed as one test per lift for every 2,500 square feet.
3. Under grass or unpaved areas, compact each layer of backfill or fill material at 95 percent maximum density.
4. Seal all fill areas at the end of each working day, utilizing a smooth drum roller.

**2.6 PAVEMENT SUBBASE COURSE:**

A. General: Place subbase material, in layers of indicated thickness, over subgrade surface to support a pavement base course.

B. Grade Control: During construction, maintain lines and grades including crown and cross-slope of subbase course.

C. Shoulders: Place shoulders along edges of subbase course to prevent lateral movement. Construct shoulders of acceptable soil materials, placed in such quantity to compact to thickness of each subbase course layer. Compact and roll at least at 12\"/>

5. Compact subbase and base course at optimum moisture content to required grades, lines, cross sections, and thickness to not less than 95 percent of maximum dry unit weight according to ASTM D 698.

H. Pavement Shoulders: Place shoulders along edges of subbase and base course to prevent lateral movement. Construct shoulders, at least 12 inches (300 mm) wide, of satisfactory soil materials and compact simultaneously with each subbase and base layer to not less than 95 percent of maximum dry unit weight according to ASTM D 698.

**2.7 BUILDING SLAB DRAINAGE COURSE**

A. General: Place drainage/porous fill material, over subgrade surface to support concrete building slabs and sidewalks areas indicated.

B. Place drainage course on subgrades free of mud, frost, snow, or ice.

C. Placing: Place drainage/porous fill material on prepared subgrade in layers of uniform thickness, conforming to indicated cross-section and thickness. Maintain optimum moisture content for compacting material during placement operations.

D. When a compacted drainage course is indicated to be 6 inches thick or less, place material in a single layer. When indicated to be more than 6 inches thick, place material in equal layers, except no single layer more than 6 inches or less than 3 inches in thickness when compacted.

**2.8 FIELD QUALITY CONTROL**

A. Quality Control Testing During Construction: Allow testing service to inspect and approve each subgrade and fill layer before further backfill or construction work is performed.

1. If in the opinion of the Owner's Geotechnical Engineer based on testing service reports and inspection, subgrade or fills have been placed that are below required density, perform additional compaction and testing until required density is obtained.

B. The Owner will engage, and pay for, the services of a Geotechnical Engineer whose function shall be to afford complete engineering control by testing of the conditions of all footing subgrades, the placement of all structural fills under structures, building pad and pavement areas, and all compaction where required, and to observe the proof rolling of the building pad and pavement areas.

C. The Owner's Geotechnical Engineer will be present as deemed necessary during all phases of the Work requiring filling, compaction operations or testing. The Geotechnical Engineer will provide the Engineer with written certification that fill and compaction was completed with accepted materials in accordance with the Documents, and give a professional opinion regarding shrinkage or settlement of fill and safe load bearing capacity of fill.

D. Site Preparation and Proofrolling: The Owner's Geotechnical Engineer will determine if any additional excavation or in-place densification is necessary to prepare a subgrade for fill placement for slab or pavement support.

E. Fill Placement and Compaction: The Owner's Geotechnical Engineer will witness all fill operations and take sufficient in-place density tests to verify that the indicated degree of fill compaction is achieved. The Owner's Geotechnical Engineer will observe and approve borrow materials used and shall determine if their existing moisture contents are suitable/acceptable.

F. Footing Excavation Review: The Owner's Geotechnical Engineer will review the footing excavations for the building foundations. He will verify that the design bearing pressures are available and that no loose or soft areas exist beneath the bearing surfaces of the footing excavations.

G. The Owner's Geotechnical Engineer will submit two (2) copies each of his reports, recommendations and/or opinions to the Architect/Engineer and the Owner. Pertinent information will be provided to the Contractor as required.



GSWCC# 10882  
EXP: 05/24/2024

Project Title  
**PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338**









REVISIONS	BY

DRAWN BY: DMN  
CHECKED BY: CLM  
DATE: 01/07/2022  
SCALE: NO SCALE  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER

**GRADING AND  
DRAINAGE DETAILS**  
D-2A



USER: 6674 - Jan 07, 2022 - 4:30pm  
 Z:\All Project Data\Projects\2020\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 Details.dwg



GSWCC# 10882  
 EXP: 05/24/2024

Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338


REVISIONS	BY

DRAWN BY: DMN  
 CHECKED BY: CLM  
 DATE: 01/07/2022  
 SCALE: NO SCALE  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

UTILITY PLAN DETAILS  
 D-3A




USER 6674 - Jan 07, 2022 - 4:30pm  
 Z:\All Project Data\Projects\2020\20-LD-025 Perimeter Center Park, Dunwoody, GA\LD\Production\Production Drawings\20-LD-025 Details.dwg




Slope surface shall be smooth before placement for proper soil contact.  
 If there is a berm at the top of slope, anchor upslope of the berm.  
 Min. 2" overlap.  
 Anchor in 6"x6" min. Trench and staple at 12" intervals.  
 Min. 6" overlap.  
 Staple overlaps max. 5" spacing.  
 Bring material down to a level area, turn the end under 4" and staple at 12" intervals.  
 Do not stretch blankets/matting tight-allow the rolls to conform to any irregularities.  
 For slopes less than 3H:1V, rolls may be placed in horizontal strips.  
 Lime, fertilize, and seed before installation. Planting of shrubs, trees, etc. should occur after installation.


### TYPICAL INSTALLATION GUIDELINES FOR ROLLED EROSION CONTROL PRODUCTS (RECP)




### CURB INLET FILTER "PIGS IN BLANKET"




### FABRIC AND SUPPORTING FRAME FOR INLET PROTECTION




### CRUSHED STONE CONSTRUCTION EXIT



### CONCRETE WASHOUT DETAIL




### CONCRETE WASHOUT DETAIL (continued)



- PREPARE SOIL BEFORE INSTALLING BLANKETS, INCLUDING ANY NECESSARY APPLICATION OF LIME, FERTILIZER, AND SEED.
  - BEGIN AT THE TOP OF THE SLOPE BY ANCHORING THE BLANKET IN A 6" DEEP X 6" WIDE TRENCH WITH APPROXIMATELY 12" OF BLANKET EXTENDED BEYOND THE UP-SLOPE PORTION OF THE TRENCH AS SHOWN IN DETAIL 2. ANCHOR THE BLANKET WITH A ROW OF STAPLES/STAKES APPROXIMATELY 12" APART IN THE BOTTOM OF THE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING. APPLY SEED TO COMPACTED SOIL AND FOLD REMAINING 12" PORTION OF BLANKET BACK OVER SEED AND COMPACTED SOIL. SECURE BLANKET OVER COMPACTED SOIL WITH A ROW OF STAPLES/STAKES SPACED APPROXIMATELY 12" APART ACROSS THE WIDTH OF THE BLANKET.
  - ROLL THE BLANKETS (A) DOWN OR (B) HORIZONTALLY ACROSS THE SLOPE. BLANKETS WILL UNROLL WITH APPROPRIATE SIDE AGAINST THE SOIL SURFACE. ALL BLANKETS MUST BE SECURELY FASTENED TO SOIL SURFACE BY PLACING STAPLES/STAKES IN APPROPRIATE LOCATIONS AS PER MANUFACTURER'S RECOMMENDATION.
  - THE EDGES OF PARALLEL BLANKETS MUST BE STAPLED WITH MINIMUM 6" OVERLAP. TO ENSURE PROPER SEAM ALIGNMENT, PLACE THE EDGE OF THE OVERLAPPING BLANKET (BLANKET BEING INSTALLED ON TOP) EVEN WITH THE SEAM STITCH ON THE PREVIOUSLY INSTALLED BLANKET.
  - CONSECUTIVE BLANKETS SPICED DOWN THE SLOPE MUST BE PLACED END OVER END (SHINGLE STYLE) WITH AN APPROXIMATE 3" OVERLAP. STAPLE THROUGH OVERLAPPED AREA, APPROXIMATELY 12" APART ACROSS ENTIRE BLANKET WIDTH.
  - PLACE STAPLES/STAKES PER MANUFACTURER'S RECOMMENDATION FOR THE APPROPRIATE SLOPE BEING APPLIED.
- IN LOOSE SOIL CONDITIONS, THE USE OF STAPLE OR STAKE LENGTHS GREATER THAN 6" MAY BE NECESSARY TO PROPERLY SECURE THE BLANKETS.
  - FOLLOW EROSION CONTROL TECHNOLOGY COUNCIL SPECIFICATION FOR PRODUCT SELECTION.

EROSION CONTROL BLANKET (CHANNEL INSTALLATION)  
 N.T.S.

### BLOCK AND GRAVEL DROP INLET PROTECTION



## EROSION SEDIMENTATION, AND POLLUTION CONTROL DETAILS



GSWCC# 10882  
 EXP: 05/24/2024

Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY DMN  
 CHECKED BY CLM  
 DATE: 01/07/2022  
 SCALE: NO SCALE  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER


D-4B



USER: 3532 - Nov 01, 2021 - 11:07am  
 V:\Projects\ANY\K5\061694\000\_09\_Design-DWG\Drawings\01\_Sheets\L-1.dwg - LAYOUT: L-1 VERSION: LAND DEVELOPMENT-41352



**LANDSCAPE LEGEND**




EXISTING TREE TO REMAIN

**PLANT KEY**



LARGE DECIDUOUS TREE



DECIDUOUS ORNAMENTAL TREE



LARGE EVERGREEN SHRUB

**LANDSCAPE PLAN NOTES**

1. SEE SITE DEMOLITION PLAN FOR EXISTING TREES TO BE REMOVED AND EXISTING TREES TO BE PROTECTED.
2. ALL DISTURBED AREAS OF THE SITE WHICH ARE SCHEDULED TO BE SEEDED SHALL RECEIVE TOPSOIL. TOPSOIL TO BE INSTALLED TO A MINIMUM 6" DEPTH. COORDINATE WITH SITE EROSION CONTROL PLAN FOR ALL APPROVED TEMPORARY AND PERMANENT STABILIZATION METHODS THROUGHOUT CONSTRUCTION ACTIVITY.
3. COORDINATE WITH EROSION CONTROL PLANS FOR LIMITS OF SEEDING AND ESTABLISHMENT OF TEMPORARY AND PERMANENT GRASS COVER.
4. COORDINATE WITH ENLARGED LANDSCAPE PLANS FOR INSTALLATION OF PERENNIAL AND SMALL SHRUB PLANTING MATERIALS.




Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**

REVISIONS BY


DRAWN BY: TM  
 CHECKED BY: PG  
 DATE: 11/01/2021  
 SCALE: 1" = 40'  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

**L-1**

**OVERALL  
 LANDSCAPE PLAN**



100% CONSTRUCTION DOCUMENTS





**LANDSCAPE LEGEND**

- LANDSCAPE MULCH, SPEC PER CITY STANDARDS
- TREE PROTECTION FENCE
- EXISTING TREE TO REMAIN
- PLANT KEY**
- LARGE DECIDUOUS TREE
- DECIDUOUS ORNAMENTAL TREE
- LARGE EVERGREEN SHRUB
- 3' RADIUS MULCH RING AROUND TREE



**LANDSCAPE PLAN NOTES**

1. SEE SITE DEMOLITION PLAN FOR EXISTING TREES TO BE REMOVED AND EXISTING TREES TO BE PROTECTED.
2. ALL DISTURBED AREAS OF THE SITE WHICH ARE SCHEDULED TO BE SEEDED SHALL RECEIVE TOPSOIL. TOPSOIL TO BE INSTALLED TO A MINIMUM 6" DEPTH. COORDINATE WITH SITE EROSION CONTROL PLAN FOR ALL APPROVED TEMPORARY AND PERMANENT STABILIZATION METHODS THROUGHOUT CONSTRUCTION ACTIVITY.
3. COORDINATE WITH EROSION CONTROL PLANS FOR LIMITS OF SEEDING AND ESTABLISHMENT OF TEMPORARY AND PERMANENT GRASS COVER.
4. COORDINATE WITH ENLARGED LANDSCAPE PLANS FOR INSTALLATION OF PERENNIAL AND SMALL SHRUB PLANTING MATERIALS.

**ENLARGED LANDSCAPE PLAN**



**SHRUB BED DETAIL PLAN**



Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**

REVISIONS	BY

DRAWN BY: TM  
 CHECKED BY: PG  
 DATE: 11/01/2021  
 SCALE: 1" = 20'  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER


**L-2**

USER: 3532 - Nov 01, 2021 - 11:08am  
 V:\Projects\ANY\K5\061694\000\_09\_Design-DWG\Drawings\01\_Sheets\L-1.dwg - LAYOUT: L-2 VERSION: LAND DEVELOPMENT-41352



100% CONSTRUCTION DOCUMENTS







**LANDSCAPE LEGEND**

- LANDSCAPE MULCH, SPEC PER CITY STANDARDS
- TREE PROTECTION FENCE
- EXISTING TREE TO REMAIN
- PLANT KEY**
- LARGE DECIDUOUS TREE
- DECIDUOUS ORNAMENTAL TREE
- LARGE EVERGREEN SHRUB
- 3' RADIUS MULCH RING AROUND TREE



**LANDSCAPE PLAN NOTES**

1. SEE SITE DEMOLITION PLAN FOR EXISTING TREES TO BE REMOVED AND EXISTING TREES TO BE PROTECTED.
2. ALL DISTURBED AREAS OF THE SITE WHICH ARE SCHEDULED TO BE SEEDED SHALL RECEIVE TOPSOIL. TOPSOIL TO BE INSTALLED TO A MINIMUM 6" DEPTH. COORDINATE WITH SITE EROSION CONTROL PLAN FOR ALL APPROVED TEMPORARY AND PERMANENT STABILIZATION METHODS THROUGHOUT CONSTRUCTION ACTIVITY.
3. COORDINATE WITH EROSION CONTROL PLANS FOR LIMITS OF SEEDING AND ESTABLISHMENT OF TEMPORARY AND PERMANENT GRASS COVER.
4. COORDINATE WITH ENLARGED LANDSCAPE PLANS FOR INSTALLATION OF PERENNIAL AND SMALL SHRUB PLANTING MATERIALS.

**ENLARGED LANDSCAPE PLAN**



**SHRUB BED DETAIL PLAN**



Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**


REVISIONS	BY

DRAWN BY: **TM**  
 CHECKED BY: **PG**  
 DATE: **11/01/2021**  
 SCALE: **1" = 20'**  
 JOB No. **20-LD-025 / 061694.00**  
 SHEET NUMBER

**L-3**


USER: 3532 - Nov 01, 2021 - 11:08am  
 V:\Projects\ANY\K5\061694\000\_000\_Design-DWG\Drawings\01\_Sheets\L-1.dwg - LAYOUT: L-3 VERSION: LAND DEVELOPMENT-41352

100% CONSTRUCTION DOCUMENTS



NOTES:

1. PLANTING SOIL MIX IN INDIVIDUAL PLANTING HOLES OR CONTINUOUS BEDS; SEE SCHEDULE OF SOIL AMENDMENTS IN SPECIFICATIONS.
2. AFTER PLACEMENT AND ROTATION OF SHRUB REMOVE ALL ROPES FROM ROOT BALL AND CUT AND REMOVE TOP OF BURLAP. COMPLETELY REMOVE BURLAP IF IT IS MADE OF SYNTHETIC MATERIAL.
3. DELETE SOIL SAUCER AROUND EACH SHRUB IF CONTINUOUS BED. PROVIDE NEAT TRIMMED SOIL EDGE AT CONTINUOUS BEDS AGAINST LAWN. WHERE PLANT BEDS ABUT CURBS OR WALKS MULCH SHOULD BE FLUSH WITH TOP OF CURBS AND EVEN WITH WALK SURFACES.
4. PRUNE BROKEN CANES AFTER PLANTING



6 NOT USED

SCALE: 1" = 1'-0"

3 SHRUB PLANTING


SECTION

SCALE: 1" = 1'-0"

2 PERENNIAL AND GROUND COVER PLANTING

SECTION

SCALE: 1" = 1'-0"




NOTES:

1. SET TREES STRAIGHT AND PLUMB
2. TREES 6" IN HEIGHT 2 1/2" IN CAL. OR LARGER SHALL BE GUYED AND STAKED WITH 3 EQUALLY SPACED 2 x 4 STAKES
3. PLANT SO THAT TOP OF ROOT BALL IS THE SAME GRADE AS AT THE NURSERY
4. AFTER PLACEMENT AND ROTATION OF TREE REMOVE ALL ROPES FROM ROOT BALL AND CUT AND REMOVE TOP 1/2 OF BURLAP. COMPLETELY REMOVE BURLAP IF IT IS MADE OF SYNTHETIC MATERIAL.

5 CONIFEROUS TREE PLANTING

SECTION

SCALE: 1" = 1'-0"



NOTES:

1. PRUNE ANY BROKEN BRANCHES AFTER FINAL PLACEMENT. PRUNE PERIMETER BRANCHES AS REQUIRED BUT RETAIN NATURAL SHAPE OF TREE. NEVER CUT A LEADER. PRUNING TO BE PERFORMED BY A QUALIFIED ARBORIST/BOTANIST ONLY.
2. TREE SHALL BE PLUMB AND STRAIGHT.

4 DECIDUOUS TREE PLANTING

SECTION

SCALE: 1" = 1'-0"

1 PLANTING SCHEDULE

SECTION

SCALE: N.T.S.

#	KEY	BOTANICAL NAME	COMMON NAME	SIZE	ROOT	SPACING
<b>TREES</b>						
15	CC	CERCIS CANADENSIS	EASTERN REDBUD	2" CAL.	B & B	AS SHOWN
16	CF	CORNUS FLORIDA	FLOWERING DOGWOOD	2" CAL.	B & B	AS SHOWN
3	CV	CHIONANTHUS VIRGINICUS	WHITE FRINGE TREE	2" CAL.	B & B	AS SHOWN
5	GB	GINKGO BILOBA 'AUTUMN GOLD'	GINKGO	3" CAL.	B & B	AS SHOWN
4	NS	NYSSA SYLVATICA	BLACK TUPELO	3" CAL.	B & B	AS SHOWN
7	PC	PISTACIA CHINENSIS	CHINESE PISTACHE	3" CAL.	B & B	AS SHOWN
3	PA	PLATANUS X ACERIFOLIA 'MORTON CIRCLE'	EXCLAMATION! PLANETREE	3" CAL.	B & B	AS SHOWN
6	QL	QUERCUS LYRATA 'HIGHBEAM'	HIGHBEAM OVERCUP OAK	3" CAL.	B & B	AS SHOWN
4	QS	QUERCUS SHUMARDII	SHUMARD OAK	3" CAL.	B & B	AS SHOWN
<b>SHRUBS</b>						
2	CP	CHAMAECYPARIS PISIFERA 'GOLDEN MOP'	JAPANESE FALSECYPRESS	#5	CONT.	AS SHOWN
9	KD	DIERVILLA X	KODIAK ORANGE DIERVILLA	#5	CONT.	AS SHOWN
12	HA	HYDRANGEA ARBORESCENS	INCREDIBALL SMOOTH HYDRANGEA	#5	CONT.	AS SHOWN
25	HQ	HYDRANGEA QUERCIFOLIA 'RUBY SLIPPERS'	RUBY SLIPPERS OAKLEAF HYDRANGEA	#5	CONT.	AS SHOWN
17	IV	ITEA VIRGINICA 'SPRICH'	LITTLE HENRY DWRF. VIRG. SWEETSPIRE	#5	CONT.	AS SHOWN
17	VR	VIBURNUM RHYTIDOPHYLLOIDES 'ALLEGHENY'	ALLEGHENY VIBURNUM	#5	CONT.	AS SHOWN
<b>ORNAMENTAL GRASSES</b>						
54	MC	MUHLENBERGIA CAPILLARIS 'LENCA'	REGAL MIST PINK MUHLY GRASS	#2	CONT.	AS SHOWN
<b>PERENNIALS &amp; GROUNDCOVERS</b>						
20	CE	CAREX ELATA 'AUREA'	BOWLES GOLDEN SEDGE	#1	CONT.	AS SHOWN
31	NR	NEPETA	CAT'S PAJAMAS CATMINT	#1	CONT.	AS SHOWN
21	SN	SALVIA N. 'CARADONNA'	CARADONNA	#1	CONT.	AS SHOWN



6745 Sugarloaf Parkway, Suite 100  
Duluth, GA 30097  
770.447.8995 www.chacompanies.com



Project Title  
PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338

REVISIONS BY



DRAWN BY TM  
CHECKED BY PG  
DATE: 11/01/2021  
SCALE: 1" = ##'  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER

L-4

100% CONSTRUCTION DOCUMENTS


AGE 5-12 PLAYGROUND:
168364 ADVENTUREScape DESIGN #1 DIRECT BURY ONLY
176078 LOLLIPOP CLIMBER
179594 VIBE ROOF
176079 SUNBEAM CLIMBER
152907 DECK LINK W/BARRIERS TWO STEPS
152907 DECK LINK W/BARRIERS THREE STEPS
173567 MARBLE PANEL
115254 STORE FRONT PANEL (BELOW DECK)
123333 40" ROLLER SLIDE
156070 POINTE/PINNACLE EXT. DECK
120901 GRAB BAR
185852 TRANSFER STEP
165533 BOW LADDER
156449 HELIX NET
182503 WELCOME SIGN (LSI PROVIDED) 5-12 YEARS
156450 SWIGGLE STIX
156462 RINGTANGLE
156457 ARCOVER
156448 O-ZONE
179188 EVOS 2 ARCH W/3-5 ATTACH POINTS
124863 SIDEWINDER2 DB ONLY
OUTRIGGER
THE POINTE

TOTAL ELEVATED PLAY COMPONENTS: 7
TOTAL ELEVATED COMPONENTS ACCESSIBLE BY RAMP: 0, REQUIRED: 0
TOTAL ELEVATED COMPONENTS ACCESSIBLE BY TRANSFER: 7, REQUIRED: 4
TOTAL ACCESSIBLE GROUND LEVEL COMPONENTS SHOWN 6, REQUIRED: 2
TOTAL DIFFERENT TYPES OF GROUND LEVEL COMPONENTS: 6, REQUIRED: 6



**LEGEND**  
 PLAYGROUND SURFACING, RE: SPECIFICATIONS

- PLAYGROUND NOTES**
- BASIS OF DESIGN FOR ALL PLAYGROUND EQUIPMENT IS BASED ON LANDSCAPE STRUCTURES PLAYGROUND EQUIPMENT, OR APPROVED EQUAL. SEE SPECIFICATIONS
  - PROVIDE PLAYGROUND SURFACE COLOR SAMPLES TO OWNER FOR APPROVAL.
  - INSTALL PLAYGROUND MATS UNDER LOCATIONS SHOWN UNDER SWINGS AND SLIDE LANDINGS.
    - 100% RECYCLED RUBBER WEAR MAT
    - MINIMUM THICKNESS OF 1.5"
    - 40" x 60" RECOMMENDED SIZE, OR SIMILAR
    - SUBMIT PRODUCT DATA FOR APPROVAL




Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS	BY


DRAWN BY: TM  
 CHECKED BY: PG  
 DATE: 11/01/2021  
 SCALE: 1" = 10'  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

**L-5**




USER: 3532 - Nov 01, 2021 - 11:08am  
 V:\Projects\ANY\K5\061694\00\_Design-DWG\Drawings\01\_Sheets\L-1.dwg - LAYOUT: L-5 VERSION: LAND DEVELOPMENT-41352


100% CONSTRUCTION DOCUMENTS




3 FREEZE RESISTANT BOTTLE FILLER AND DRINKING FOUNTAIN SCALE: N.T.S.



2 WOOD-GRAIN POLYETHYLENE BENCH SCALE: N.T.S.



1 BIKE RACK SCALE: 1" = 1'-0"





LEGEND



FITNESS STATION NOTES

1. BASIS OF DESIGN FOR ALL FITNESS STATION EQUIPMENT IS BASED ON LANDSCAPE STRUCTURES HEALTHBEAT EXERCISE EQUIPMENT, OR APPROVED EQUAL.

ENLARGED FITNESS STATION PLAN






Project Title  
PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY: TM  
CHECKED BY: PG  
DATE: 11/01/2021  
SCALE: 1" = 5'  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER

L-6




**SLOPE FINISH**  
REMOVE ROOTS THAT PROTRUDE FROM THE BACKSLOPE WITH DIAMETERS GREATER THAN SHOWN IN THE SLOPE AND TRAILBED FINISH TABLE.


**TRAILBED FINISH**  
REMOVE LOOSE ROCK ON THE TRAILBED WITH A DIMENSION GREATER THAN SHOWN IN THE SLOPE AND TRAILBED FINISH TABLE.  
REMOVE OR REDUCE EMBEDDED ROCK THAT PROTRUDES MORE THAN THE DIMENSIONS SHOWN IN THE SLOPE AND TRAILBED FINISH TABLE.

- NOTES:**
- SLASH CONSISTS OF LOGS, LIMBS, BRUSH, AND ROCKS PLACED RANDOMLY IN A WAY TO CATCH SEDIMENT MOVEMENT.
  - LIMB ALL TREES AND SHRUBS AND TAMP SLASH INTO GROUND SO THAT 80% OF SLASH IS IN CONTACT WITH THE GROUND.


**3 TYPICAL TRAIL CONDITIONS**  
SECTION SCALE: N.T.S.



**2 TYPICAL TRAIL SECTION**  
SECTION SCALE: N.T.S.



**1 SWITCHBACK CONDITION**  
PLAN/SECTION SCALE: N.T.S.



**LANDSCAPE LEGEND**



- CRUSHED ROCK TRAIL
- TRAIL CENTERLINE

**TRAIL PLAN NOTES**

- TRAIL ALIGNMENT SHOWN IS FOR BIDDING PURPOSES ONLY. BASIS OF TRAIL DESIGN HAS BEEN DEVELOPED BY USING SURVEYED TOPOGRAPHY, AND APPLYING DESIRED HIKING TRAIL DETAILS AND GRADIENTS (SEE NOTE 2). ALL LAYOUT AND FINAL TRAIL ALIGNMENTS TO BE FIELD VERIFIED PRIOR TO CONSTRUCTION (SEE NOTE 3).
- TRAIL DESIGN NOTES:
  - UTILIZE "LIGHT-ON-THE-LAND" APPROACH. ALL EFFORTS SHOULD BE MADE TO PRESERVE AS MUCH EXISTING LANDSCAPE AS POSSIBLE WHEN CONSTRUCTING THE CRUSHED STONE TRAIL. AVOID LARGE TREES. SURVEY SHOWN MAY NOT REPRESENT ALL SPECIMEN TREES FOUND NEAR PROPOSED TRAIL ROUTE.
  - TYPICAL WIDTH OF TRAIL IS 5' (60").
  - MAXIMUM SUSTAINED SLOPE IS 10%, SEE PLAN FOR ANTICIPATED GRADIENTS, PER SURVEY.
  - MAXIMUM SLOPE IS 15%, AND SHOULD NOT BE SUSTAINED FOR MORE THAN 100 LINEAR FEET OF TRAIL. SEE PLAN FOR ANTICIPATED GRADIENTS, PER SURVEY, AND WHERE THIS CONDITION MAY OCCUR ON PLAN.
  - MAXIMUM TRAIL CROSS SLOPE IS 2%. SEE PLAN FOR ANTICIPATED GRADIENT, PER SURVEY.
- CONSTRUCTION NOTES:
  - TRAIL SURFACE TO BE CRUSHED STONE USING 3/8" MINUS CRUSHER FINES, SEE SPECIFICATIONS.
  - SURVEYOR TO FIELD LOCATE/FLAG POINTS SHOWN ON THIS PLAN PRIOR TO SITE VISIT.
  - ENGINEER, OWNER AND CONTRACTOR TO WALK PROPOSED ROUTE TO DETERMINE SUITABILITY OF TRAIL ALIGNMENT. ALL TRAIL DESIGN NOTES (SEE NOTE 2) SHOULD BE CONSIDERED WHEN ANALYZING FINAL LAYOUT.
  - ONCE FINAL LAYOUT IS DETERMINED, CLEAR BRUSH AND SAPLING TREES TO APPROXIMATELY 2' EACH SIDE OF TRAIL. OVERHEAD LIMBS SHOULD BE PRUNED BACK TO A HEIGHT OF 8'-10' CLEAR OVER TRAIL SURFACE.
  - SEE DETAILS ON THIS SHEET FOR PROPOSED TRAIL DESIGN CONDITIONS.
  - USE AGGREGATE THAT IS UNIFORMLY MIXED AT OPTIMUM MOISTURE CONTENT AND SPREAD AND COMPACT IN LAYERS TO FINAL THICKNESS AND WIDTH SHOWN ON PLANS.
  - COMPACT ALL DISTURBED SOIL AND TRAIL MATERIALS. OBTAIN COMPACTION BY ONE OF THE FOLLOWING METHODS:
    - BY HAND, USING NON-MECHANIZED COMPACTION TOOLS OVER THE FULL AREA OF EACH LAYER UNTIL VISUAL DISPLACEMENT CEASES;
    - BY MECHANICAL VIBRATORY COMPACTORS OVER THE FULL AREA OF EACH LAYER UNTIL VISUAL DISPLACEMENT CEASES, BUT NOT FEWER THAN THREE COMPLETE PASSES;
    - BY USING A ROLLER OR MECHANICAL HAND TAMPER UNTIL THE DENSITY IS AT LEAST 90 PERCENT OF THE MAXIMUM DENSITY, AS DETERMINED BY AASHTO T 99, METHOD C OR D.
  - UPON COMPLETION, CONTRACTOR SHALL SEED, FERTILIZE AND MULCH ANY DISTURBED AREA.
- SUBMITTALS:
  - SUBMIT 3/8" MINUS CRUSHER RUN FOR REVIEW USING THE FOLLOWING GRADATION:

SIEVE SIZE/ PARTICLE SIZE	PERCENT PASSING
3/8"	100%
#4	90-100%
#8	55-80%
#16	40-70%
#30	25-50%
#200	6-15%

**TRAIL PLAN**



Project Title  
**PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338**

REVISIONS	BY

DRAWN BY: TM  
CHECKED BY: PG  
DATE: 11/01/2021  
SCALE: 1" = 20'  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER

**L-7**

USER: 3932 - Nov 01, 2021 - 11:08am  
V:\Projects\ANY\K5\061694\000\_09\_Design-DWG\Drawings\01\_Sheets\L-7.dwg - LAYOUT: L-7 VERSION: LAND DEVELOPMENT-41392

100% CONSTRUCTION DOCUMENTS

SIGN TYPE A: PARK ID

Materials & Specifications table, Job Name (City of Dunwoody GA), Location (Dunwoody GA), Customer Contact, Designer (Glen Miller), DWG Date (4-26-20), Rev Date (9-10-20), Scale (1/2" = 1'-0"), File Name (City of Dunwoody GA-20-49482-20-49482 Type A), Design Specifications Accepted By (ALUM LANSBURY).

SIGN TYPE A: PARK ID - A4

Materials & Specifications table, Job Name (City of Dunwoody GA), Location (Dunwoody GA), Customer Contact, Designer (Glen Miller), DWG Date (4-26-20), Rev Date (9-10-20), Scale (1/2" = 1'-0"), File Name (City of Dunwoody GA-20-49482-20-49482 Type A), Design Specifications Accepted By (ALUM LANSBURY).

PARK ENTRY SIGN AND KIOSK NOTES

- 1. DESIGN INTENT, PLANS AND SPECIFICATIONS ATTACHED TO THIS SHEET HAS BEEN PROVIDED BY THE CITY OF DUNWOODY AS A STANDARD DESIGN AND BASIS OF BIDDING FOR THE PARK ENTRY SIGN AND TRAIL KIOSK.
2. SUBMIT SHOP DRAWINGS FOR REVIEW.
3. SEE PLANS FOR LOCATION OF EACH ITEM.
4. PROVIDE TWO (2) TYPE 'A' ENTRY SIGNS
5. PROVIDE ONE (1) KIOSK


SIGN TYPE A: PARK ID

Materials & Specifications table, Job Name (City of Dunwoody GA), Location (Dunwoody GA), Customer Contact, Designer (Glen Miller), DWG Date (4-26-20), Rev Date (9-10-20), Scale (1/2" = 1'-0"), File Name (City of Dunwoody GA-20-49482-20-49482 Type A), Design Specifications Accepted By (ALUM LANSBURY).

Technical drawings showing structural details for sign assembly, including framing, masonry base, and pole connections. Includes notes like 'NEED PICKUP EXTENSIONS' and 'GRAPHICS SHOWN EXTRACTED FROM BID DOCUMENTS'.

Technical drawings showing detailed views of support tubes and center poles for the sign, including dimensions and material specifications.

Technical drawings showing detailed views of faux beam framing, masonry base, and pole connections, including dimensions and material specifications.





Project Title: PERIMETER CENTER EAST PARK CITY OF DUNWOODY, GEORGIA 4800 ASHFORD DUNWOOD RD DUNWOODY, GA 30338

Table with columns for REVISIONS and BY, currently empty.

DRAWN BY: TM
CHECKED BY: PG
DATE: 11/01/2021
SCALE: 1" = #
JOB No: 20-LD-025 / 061694.00
SHEET NUMBER



L-8

USER: 3532 - Nov 01, 2021 - 11:08am  
 V:\Projects\NYX\K5\061694\09\_Design-DWG\Drawings\01\_Sheets\L-1.dwg - LAYOUT: L-9 VERSION: LAND DEVELOPMENT-41352



**PARK ENTRY SIGN AND KIOSK NOTES**

- DESIGN INTENT, PLANS AND SPECIFICATIONS ATTACHED TO THIS SHEET HAS BEEN PROVIDED BY THE CITY OF DUNWOODY AS A STANDARD DESIGN AND BASIS OF BIDDING FOR THE PARK ENTRY SIGN AND TRAIL KIOSK.
- SUBMIT SHOP DRAWINGS FOR REVIEW.
- SEE PLANS FOR LOCATION OF EACH ITEM.
- PROVIDE TWO (2) TYPE 'A' ENTRY SIGNS
- PROVIDE ONE (1) KIOSK



100% CONSTRUCTION DOCUMENTS


DRAWN BY	TM
CHECKED BY	PG
DATE:	11/01/2021
SCALE:	1" = ##'
JOB No.	20-LD-025 / 061694.00
SHEET NUMBER	

**L-9**

Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**

REVISIONS	BY

DRAWN BY: TM  
 CHECKED BY: PG  
 DATE: 11/01/2021  
 SCALE: 1" = ##'  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER



SIGNAGE PACKAGE NOTES AND FINISHES

PAINT SCHEDULE

Table with 2 columns: Item, Description. Includes Benjamin Moore 460 Herb Bouquet (P1), Benjamin Moore 447 Holiday Wreath (P2), Benjamin Moore Exterior Ready-Mixed (P3), Benjamin Moore HC-80 Bleaker Balga\* (P4), Matthews Paint MPO900 Greenhorn (P5), Matthews Paint MP11372 Urban Forest (P6).

VINYL SCHEDULE

Table with 2 columns: Item, Description. Includes Oracal 961-010 - White (V1), 3M Digital Print, Matte Finish, UV Laminate, Exterior Grade (V2).

MATERIAL SCHEDULE

Table with 2 columns: Item, Description. Includes Landmark Stone - Chestnut Limestone (M1), Aluminum (M2), Magnetic Digital Print (M3), Continental Cast Stone - Smooth Face (M4).

HARDWARE SCHEDULE

Table with 2 columns: Item, Description. Includes Outdoor Enclosed Bulletin Board (H1).

GENERAL NOTES

- FIELD SURVEY IS REQUIRED PRIOR TO PRODUCING FINAL SHOP DRAWINGS TO VERIFY ARCHITECTURAL INTEGRITY & LAYOUT. ALL DRAWINGS IN THIS PACKAGE ARE FOR INTENT ONLY. NO DIMENSIONS HAVE BEEN CONFIRMED. RESPONSIBILITY FOR ALL FIELD VERIFICATION LIES WITH SIGN FABRICATOR.

TYPICAL NOTES

- REFER TO DRAWING NOTES FOR MATERIAL THICKNESS AND/OR DIAMETER UNLESS SPECIFICALLY NOTED IN THE FINISH SCHEDULE. BID ALTERNATE PRICING SHOULD BE INCLUDED ON BID SUMMARY FORM IN THE CORRESPONDING BID ALTERNATE COLUMN.

ASSEMBLY SPECIFICATIONS

- ALL HARDWARE TO BE SECURED WITH LOCTITE OR EQUIVALENT TO DETER VANDALISM.

FABRICATION SPECIFICATIONS

- SEAMLESS CONSTRUCTION; ALL SEAMS/WELDS TO BE FILLED, GROUND, SANDED, AND FINISHED SMOOTH. NO VISIBLE FASTENERS UNLESS THEY ARE SPECIFICALLY PART OF DESIGN INTENT. NO ALTERNATES MAY BE INTRODUCED UNLESS CLEARLY OUTLINED BY CONTRACTOR AND APPROVED BY OWNER AND DESIGNER.

Project Specifications

City of Dunwoody Park Signage
Project #31538.00

The following design documents are for the sole purpose of conveying design intent and are not intended for construction purposes. The fabricator may make recommendations and/or changes to the details as shown in the drawings with written approval of the Owner's representative.

Sky Design and the Owner shall review all shop drawings for conformance with the design intent of these drawings only and will not be held responsible or liable for any results of construction from working drawings, materials selection, shop drawings, or any other agreements.

REVIEW

- Site: The fabricator is responsible for verifying all site conditions with regards to fabrication and installation before manufacture of signage. Any conditions that would impede the proper and timely completion of the work should be presented to the Owner's representative in writing. Sign Location Plans: Locations shown on the Sign Location Plans are for general placement.

ENGINEERING

- Footings: All footings to be verified by structural engineer as part of scope. Drawings show footings for intent only. An Engineer's Stamp is to be obtained when necessary to comply with permits and/or codes. Wind load: Exterior signs shall be designed to withstand wind pressure loading to meet or exceed all current code requirements for the state of Georgia.

ARTWORK

All enlarging and reducing of supplied artwork images is the responsibility of the signage fabricator. Any discrepancies after enlarging or reducing vs. original artwork are to be addressed with Owner's representative prior to reproduction.

SUBMITTALS

Color samples, material samples, submittals, copy layouts, and working drawings are to be provided for approval by the Owner's representative and Owner prior to manufacture.

- Shop Drawings are the responsibility of the fabricator for each of the disciplines contained within and are to include all necessary dimensions drawn to scale, details, internal mechanicals, joint connections, hidden connections, anchorage to footings, section views as needed, etc. Mock-ups: samples required for review and approval will be listed on Bid Summary Form.

- Vinyl: 3 samples of each color to be submitted as a minimum 4" x 4" submittal. All vinyl is to be 3M Scotchcal graphic vinyl, or Gerber equivalent. Inkjet and/or Printed Wallcovering: 1 proof of each type of inkjet graphic to be submitted at full-size.

MATERIALS

- All wood, stone, brick or brick veneer components to be sealed to protect against decay, mildew, and discoloration. All aluminum components and panels to have a minimum wall thickness of .125" or greater.

INSTALLATION

- Post and Panels in concrete or pavement to be installed via core drill footing and backfill. All breakaway details to conform to GA DOT standard requirements. Exterior ADA signs containing Braille should be produced using exterior grade photopolymer.

SIGNAGE PROTECTION

Fabricator to coordinate protection of all signs until punch list is completed by Owner.

Fabricator to be responsible for all equipment used to install signage, including but not limited to lifts, swing stages, equipment vehicles, and temporary attachments. It is the responsibility of the fabricator to ensure that all penetrations into all concrete, precast columns, beams, or building facades do not affect the structural integrity of the reinforcement within.

WARRANTY

- Fabricator warrants work against failure due to faulty materials, workmanship, and design for a period of five years from date of substantial completion. Fading, cracking, oil canning, peeling, delaminating, rusting, corroding, and structural failure, including distortion, will be construed to mean failure due to faulty materials and workmanship.

PROPRIETARY INFORMATION

Sky Design shall have the right to include a credit line on completed designs or any visual representation of drawings, models, sketches, photographs, etc. created by Sky Design in the development of this signage program.

1 Project Finishes

ABCDEFGHIJKLMNOPQRSTUVWXYZ
abcdefghijklmnopqrstuvwxyz 0123456789

TYPEFACE 1 - Today Sans Serif Medium

ABCDEFGHIJKLMNOPQRSTUVWXYZ
abcdefghijklmnopqrstuvwxyz 0123456789


TYPEFACE 2 - Univers 55 Roman

2 Project Typefaces


3 General Notes




4 Project Logos




4 PARK KIOSK - PLAN VIEW
SCALE: 3/4\"/>




5 PARK KIOSK - DETAIL VIEW
SCALE: 3/4\"/>



7 PARK KIOSK - FRONT ELEVATION
SCALE: 3/4\"/>



2 PARK KIOSK - SIDE ELEVATION
SCALE: 3/4\"/>



3 PARK KIOSK - BACK ELEVATION
SCALE: 3/4\"/>

MATERIALS & SPECIFICATIONS table listing items A-K (Fabricated Aluminum Post, Deep Fabricated Aluminum Medallion, Fabricated Aluminum Cabinet, Waterjet Cut Aluminum Icon, Fabricated Aluminum Cabinet with Applied Digital Print, Bulletin Board, Fabricated Aluminum Cabinet with Screenprinted Logo, Precast Stone Cap, CMU Base Clad with Stone Veneer, Concrete Footer) and installation/notes sections.

35 HWY 400, SUITE 100, ATLANTA, GA 30338 P: 404.686.6702 F: 404.686.3235 W: SKYDESIGNGRAPHICS.COM

sky design

Project information table: PROJECT # 31538.00, TITLE City of Dunwoody Park Signage, SIGN TYPE Park Kiosk, REVISED DATE 12.02.2019, DRAWN BY CW/TC.

7.0

PARK ENTRY SIGN AND KIOSK NOTES

- DESIGN INTENT, PLANS AND SPECIFICATIONS ATTACHED TO SHEETS L-8 & L-9 HAVE BEEN PROVIDED BY THE CITY OF DUNWOODY AS A STANDARD DESIGN AND BASIS OF BIDDING FOR THE PARK ENTRY SIGN AND TRAIL KIOSK. SUBMIT SHOP DRAWINGS FOR REVIEW. SEE PLANS FOR LOCATION OF EACH ITEM. PROVIDE TWO (2) TYPE 'A' ENTRY SIGNS. PROVIDE ONE (1) KIOSK.

Project Title
PERIMETER CENTER EAST PARK
CITY OF DUNWOODY, GEORGIA
4800 ASHFORD DUNWOOD RD
DUNWOODY, GA 30338

REVISIONS BY


Revision table with columns for Date, Scale, Job No., Sheet Number.

L-10

SCALE: N.T.S.

100% CONSTRUCTION DOCUMENTS

L-1.DWG



35 HWY 400, SUITE 100, ATLANTA, GA 30338 P: 404.686.6702 F: 404.686.3235 W: SKYDESIGNGRAPHICS.COM

sky design

PROJECT # 31538.00

TITLE City of Dunwoody Park Signage

SIGN TYPE Project Specifications


REV. DATE DRAWN BY

#0 12.02.2019 CW/TC

C







**SPLASHPAD PLAN NOTES**


1. SPLASH PAD SHALL BE A RECIRCULATING SYSTEM. PUMPS, FILTERS, ETC. SHALL BE LOCATED WITHIN PUMP HOUSE/EQUIPMENT BUILDING.
2. A TOTAL OF SIX (6) MAIN DRAINS SHALL BE INSTALLED AS SHOWN IN THE SPLASH PAD.
3. FEATURES SHALL BE INSTALLED AT LOCATIONS AS SHOWN AND ACCORDING TO MANUFACTURER'S INSTALLATION INSTRUCTIONS.
4. FEATURE COVER COLORS TO BE SELECTED BY OWNER DURING SUBMITTAL PROCESS.
5. SPLASH PAD ACTIVATION BOLLARD SHALL BE PROVIDED AND INSTALLED. BOLLARD SHALL ENGAGE/ACTIVATE SPRAY FEATURES WHEN PUSHED.
6. A RAIN DIVERTER & STRAINER SHALL BE PROVIDED & INSTALLED BY CONTRACTOR PER PROJECT PLANS. UNIT SHALL BE SUPPLIED BY WATER FEATURE MANUFACTURER.
7. NO ABOVE GROUND FEATURES ARE SPECIFIED. GRADE LEVEL FEATURE NOZZLES SHALL BE INSTALLED LEVEL AND PLUMB IN ALL DIRECTIONS PER MANUFACTURER'S INSTRUCTIONS.
8. FEATURE MANIFOLD SHALL BE LOCATED IN POOL EQUIPMENT SHED. SEE SP & A PLANS FOR DETAILS.
9. SPLASH PAD HOLDING RESERVOIR TANK SHALL BE A PRE-CAST CONCRETE STRUCTURE. TANK SHALL BE SUPPLIED BY CONTRACTOR AND SHALL BE INSTALLED AS PER PROJECT PLANS.

SEE SP-5 FOR ENLARGED PLAN

SEE SP-2 FOR ENLARGED PLAN

20'  
SEWER EASEMENT

**OVERALL SPLASHPAD PLAN**



Project Title  
**PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338**

REVISIONS	BY

DRAWN BY MDC  
 CHECKED BY PNG  
 DATE: 11/01/2021  
 SCALE: 1" = 5'  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER


**SP-1**

USER: 3530 - Nov 01, 2021 - 11:52am  
 V:\Projects\ANY\51061694\_000\09\_Design-DWG\Drawings\01\_Sheets\SP-1\_061694.dwg - LAYOUT: 1 VERSION: LAND DEVELOPMENT-41352

100% CONSTRUCTION DOCUMENTS

SP-1\_061694.DWG

USER: 3530 - Nov 01, 2021 - 11:49am  
 V:\Projects\WV\15\061694\000\09\_DWG\Design\DWG\Drawings\01\_Sheets\SP-2\_061694.dwg - LAYOUT: VERSION: LAND DEVELOPMENT-1125C



**1** SPLASH PAD LAYOUT PLAN  
 SCALE: 3/8" = 1'-0"

**SPLASH PAD DESIGN: FEATURE SUPPLY INFORMATION**

REF NO.	FEATURE NAME	MANF. ID#	QTY	FLOW RATE (EACH)	EXTENDED FLOW RATE	PRESSURE	HEIGHT (SPRAY)	THROW
1	ANYWAYSPRAY	W100	5	4 GPM	20 GPM	3 PSI	4 FT	4 FT
2	WATER FLOWER	W071	2	10 GPM	20 GPM	1 PSI	1 FT	2 FT
3	WATER CROWN	W070	3	29 GPM	87 GPM	3 PSI	2 FT	6 FT
4	WATER WEAVE	W093	1	14 GPM	14 GPM	2 PSI	4 FT	8 FT
5	DADDY LONG LEGS	W004	1	31 GPM	31 GPM	5 PSI	7 FT	5 FT
6	WATER FAN	W083	2	42 GPM	84 GPM	6 PSI	6 FT	12 FT
7*	SPRAY FEATURE MANIFOLD (4")	N/A	1	FULL FEATURE FLOW RATE = 256 GPM		6 PSI	N/A	N/A

\*7 NOT SHOWN ON THIS PLAN - SEE SP-5 FOR FEATURE MANIFOLD INFORMATION / LOCATION

**SPLASH PAD DESIGN: MAIN DRAIN INFORMATION**

REF #	DESCRIPTION	QTY	MAX RATED FLOW RATE	MAX TOTAL FLOW RATE
8	MAIN DRAIN (W200)	6	50 GPM EACH DRAIN	300 GPM

**SPLASH PAD DESIGN: ACTIVATION BOLLARD INFORMATION**

REF #	DESCRIPTION	QTY	POWER	TIME DURATION
9	ACTIVATION BOLLARD	1	HARD WIRED	15 MINUTES



Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**

REVISIONS	BY


DRAWN BY: MDC  
 CHECKED BY: PNG  
 DATE: 11/01/2021  
 SCALE: 3/8" = 1'-0"  
 JOB No: 20-LD-025 / 061694.00  
 SHEET NUMBER

**SP-2**

100% CONSTRUCTION DOCUMENTS

SP-2\_061694.DWG

USER: 3530 - Nov 01, 2021 - 11:54am  
 V:\Projects\WV\15\061694\000\09\_Design\DWG\Drawings\01\_Sheets\SP-3\_061694.dwg - LAYOUT1 - VERSION: LAND DEVELOPMENT-41352



**1** SPLASH PAD DIMENSION PLAN  
 SCALE: 3/8" = 1'-0"



**Project Title**  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338


REVISIONS	BY

**DRAWN BY** MDC  
**CHECKED BY** PNG  
**DATE:** 11/01/2021  
**SCALE:** 3/8" = 1'-0"  
**JOB No:** 20-LD-025 / 061694.00  
**SHEET NUMBER**

**SP-3**

100% CONSTRUCTION DOCUMENTS

SP-3\_061694.DWG




**1** SPLASH PAD CROSS SECTION A-A  
 SCALE: 1/2" = 1'-0"

USER: 3530 - Nov 01, 2021 - 12:04pm  
 V:\Projects\ANY\51061694\_000\09\_Design-DWG\Drawings\01\_Sheets\SP-5\_061694.dwg - LA\OUT: 1 VERSION: LAND DEVELOPMENT-41352



**1** SPLASH PAD PUMP ROOM EQUIPMENT LAYOUT PLAN  
 SCALE: 3/8" = 1'-0"



6745 Sugarloaf Parkway, Suite 100  
 Duluth, GA 30097  
 770.447.8999 - www.chacompanies.com



Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**


REVISIONS	BY

DRAWN BY: MDC  
 CHECKED BY: PNG  
 DATE: 11/01/2021  
 SCALE: 3/8" = 1'-0"  
 JOB No: 20-LD-025 / 061694.00  
 SHEET NUMBER

**SP-5**

100% CONSTRUCTION DOCUMENTS


SP-5\_061694.DWG



**Water Odyssey Model Number:** W100  
**Interactive Water Effect:** Shall be a solid stream of water with 30° adjustability on a 360° axis.  
**Housing:** 20 gauge deep-drawn type 304 stainless steel with grounding connection and 1" FPT inlet. Supplied with 4, 3/8" x 12" x 2" 18/8 stainless steel anchor bolts with two leveling nuts and washers per bolt and wood pour template.  
**Gaskets:** 70 durometer EPDM o-ring.  
**Construction Cover:** Reusable 7" diameter HDPE (high density polyethylene).  
**Top Plate:** 7" diameter slightly domed cast bronze with interchangeable nozzle assembly and UV stabilized, textured elastomeric urethane coating with a UV and chlorine resistant sealer coat.  
**Top Plate Anchors:** Three 1/2" x 5" machined brass with 30° hook bend.  
**Color:** (Specify red, dark blue, light blue, yellow, green, orange, or purple.)  
**Fasteners:** Tamper-resistant 18/8 stainless steel.  
**Nozzle:** Precision machined brass.  
**Quantity:** (5)  
**Foundation:** Foundation required for feature shall be coordinated with manufacturer and included in bid price.



**1 ANYWAYSpray WATER FEATURE DETAIL**  
 SCALE: NOT TO SCALE



**Water Odyssey Model Number:** W071  
**Interactive Water Effect:** Shall be a sheet effect in the shape of a morning glory.  
**Housing:** 20 gauge deep-drawn type 304 stainless steel with grounding connection and 1" FPT inlet. Supplied with 4, 3/8" x 12" x 2" 18/8 stainless steel anchor bolts with two leveling nuts and washers per bolt and wood pour template.  
**Gaskets:** 70 durometer EPDM o-ring.  
**Construction Cover:** Reusable 7" diameter HDPE (high density polyethylene).  
**Top Plate:** 7" diameter slightly domed cast bronze with interchangeable nozzle assembly and UV stabilized, textured elastomeric urethane coating with a UV and chlorine resistant sealer coat.  
**Top Plate Anchors:** Three 1/2" x 5" machined brass with 30° hook bend.  
**Color:** (Specify red, dark blue, light blue, yellow, green, orange, or purple.)  
**Fasteners:** Tamper-resistant 18/8 stainless steel.  
**Nozzle:** Precision machined brass.  
**Quantity:** (2)  
**Foundation:** Foundation required for feature shall be coordinated with manufacturer and included in bid price.



**2 WATER FLOWER WATER FEATURE DETAIL**  
 SCALE: NOT TO SCALE



Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338


REVISIONS	BY

DRAWN BY: MDC  
 CHECKED BY: PNG  
 DATE: 11/01/2021  
 SCALE: NTS  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

**SP-6**

100% CONSTRUCTION DOCUMENTS


USER: 3530 - Nov 01, 2021 - 12:06pm  
 V:\Projects\ANY\51061694\000\09\_Design-DWG\Drawings\01\_Sheets\SP-6\_061694.dwg - LA.YOUT: 1 VERSION: LAND DEVELOPMENT-41352



**Water Odyssey Model Number:** W070  
**Interactive Water Effect:** Shall be a full crystalline morning glory sheet effect.  
**Housing:** 20 gauge deep-drawn type 304 stainless steel with grounding connection and 1 1/2" FPT inlet. Supplied with 4, 3/8" x 12" x 2" 18/8 stainless steel anchor bolts with two leveling nuts and washers per bolt and wood pour template.  
**Gaskets:** 70 durometer EPDM o-ring.  
**Construction Cover:** Reusable 11" diameter HDPE (high density polyethylene).  
**Top Plate:** 11" diameter slightly domed cast bronze with interchangeable nozzle assembly and UV stabilized, textured elastomeric urethane coating.  
**Top Plate Anchors:** Six 1/2" x 5" machined brass with 30° hook bend.  
**Color:** (Specify red, dark blue, light blue, yellow, green, orange, or purple.)  
**Fasteners:** Tamper-resistant 18/8 stainless steel.  
**Nozzle:** Precision machined brass.  
**Quantity:** (3)  
**Foundation:** Foundation required for feature shall be coordinated with manufacturer and included in bid price.



**3 WATER CROWN WATER FEATURE DETAIL**  
 SCALE: NOT TO SCALE



**Water Odyssey Model Number:** W093  
**Interactive Water Effect:** Shall be a "basket weave" pattern of streams of water.  
**Housing:** 20 gauge deep-drawn type 304 stainless steel with grounding connection and 2" FPT inlet. Supplied with 4, 3/8" x 12" x 2" 18/8 stainless steel anchor bolts with two leveling nuts and washers per bolt and wood pour template.  
**Gasket:** 70 durometer EPDM o-ring.  
**Construction Cover:** Reusable 13" diameter HDPE (high density polyethylene).  
**Top Plate:** 13" diameter slightly domed cast bronze with UV stabilized, textured elastomeric urethane coating.  
**Top Plate Anchors:** Six 1/2" x 5" machined brass with 30° hook bend.  
**Color:** (Specify red, dark blue, light blue, yellow, green, orange, or purple.)  
**Fasteners:** Tamper-resistant 18/8 stainless steel.  
**Nozzles:** Eighteen precision machined brass.  
**Quantity:** (1)  
**Foundation:** Foundation required for feature shall be coordinated with manufacturer and included in bid price.



**4 WATER WEAWE WATER FEATURE DETAIL**  
 SCALE: NOT TO SCALE



Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY: MDC  
 CHECKED BY: PNG  
 DATE: 11/01/2021  
 SCALE: NTS  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER


**SP-7**

USER: 3530 - Nov 01, 2021 - 12:08pm  
 V:\Projects\ANY\51061694\_000\09\_Design-DWG\Drawings\01\_Sheets\SP-7\_061694.dwg - LA.YOUT: 1 VERSION: LAND DEVELOPMENT-41352

100% CONSTRUCTION DOCUMENTS

SP-7\_061694.DWG






**Water Odyssey Model Number:** W004  
**Interactive Water Effect:** Shall be an array of outward arching streams of water.  
**Housing:** 20 gauge deep-drawn type 304 stainless steel with grounding connection and 1 1/2" 18/8 stainless steel anchor bolts with two leveling nuts and washers per bolt and wood pour template.  
**Gasket:** 70 durometer EPDM o-ring.  
**Construction Cover:** Reusable 11" diameter HDPE (high density polyethylene).  
**Top Plate:** 11" diameter slightly domed cast bronze with UV stabilized, textured elastomeric urethane coating.  
**Top Plate Anchors:** Six 1/2" x 5" machined brass with 30° hook bend.  
**Color:** (Specify red, dark blue, light blue, yellow, green, orange, or purple.)  
**Fasteners:** Tamper-resistant 18/8 stainless steel.  
**Nozzles:** Eight precision machined brass.  
**Quantity:** (1)  
**Foundation:** Foundation required for feature shall be coordinated with manufacturer and included in bid price.



**5 DADDY LONG LEGS WATER FEATURE DETAIL**  
 SCALE: NOT TO SCALE



**Water Odyssey Model Number:** W083  
**Interactive Water Effect:** Shall be "basket weave" pattern of streams of water.  
**Housing:** 20 gauge deep-drawn type 304 stainless steel with grounding connection and 1 1/2" FPT inlet. Supplied with 4, 3/8" x 12" x 2" 18/8 stainless steel anchor bolts with two leveling nuts and washers per bolt and wood pour template.  
**Gaskets:** 70 durometer EPDM o-ring.  
**Construction Cover:** Reusable 11" diameter HDPE (high density polyethylene).  
**Top Plate:** 11" diameter cast bronze with interchangeable nozzle assembly and UV stabilized, textured elastomeric urethane coating.  
**Top Plate Anchors:** Six 1/2" x 5" machined brass with 30° hook bend.  
**Color:** (Specify red, dark blue, light blue, yellow, green, orange, or purple.)  
**Fasteners:** Tamper-resistant 18/8 stainless steel.  
**Nozzle:** Precision machined cast bronze.  
**Quantity:** (2)  
**Foundation:** Foundation required for feature shall be coordinated with manufacturer and included in bid price.



**6 WATER FAN WATER FEATURE DETAIL**  
 SCALE: NOT TO SCALE



Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY: MDC  
 CHECKED BY: PNG  
 DATE: 11/01/2021  
 SCALE: NTS  
 JOB No: 20-LD-025 / 061694.00  
 SHEET NUMBER


**SP-8**

100% CONSTRUCTION DOCUMENTS

USER: 3530 - Nov 01, 2021 - 12:10pm  
 V:\Projects\NY\15\061694\00\09\_Design-DWG\Drawings\01\_Sheets\SP-8\_061694.dwg - LA YOUT: 1 VERSION: LAND DEVELOPMENT-41352


**Specifications:**

**Model Number:** WMF-13  
**Distribution Header:** 3" type 304L stainless steel pipe with flanged ends.  
**Solenoid Valves:** Die cast bronze with stainless steel hardware, DIN connector with 15' cord, and 24VAC UL Recognized solenoid.  
**Balancing Valves:** True union ball valve, Schedule 80 PVC.  
**Water Hammer Arrestor:** 2" Copper and brass construction with pre-set operating pressure of 10-35 psi.  
**Drain Valve:** 3/4" Cast bronze hose bib.  
**Pressure Gauge:** Discharge Pressure Gauge: Tru-Tel #3550BC4L1D6F. 0-60 psi.  
**Mounting Brackets:** Type 304 stainless steel with 1/2" stainless steel u-bolt.  
**Catalog Numbering:** Numeric suffix following WMF (13) indicates number of discharge assemblies  
**Quantity:** (1)



NOTE: See sheet SP-10 Detail #11 for manifold installation.

**7** SPRAY FEATURE MANIFOLD DETAIL  
 SCALE: NOT TO SCALE




**Water Odyssey Model No:** W200  
**Sump:** Formed polyethylene.  
**Grate:** Heavy-duty FRP grate with skid resistant surface urethane coating. Meets ADA guidelines.  
**Strainer Basket:** Molded Polyurethane  
**Grate Color:** Available colors: red, light blue, yellow, green, dark blue, orange, or purple.  
**Outlet:** 4" slip connection.  
**Fasteners:** Tamper-resistant 18/8 stainless steel.  
**Quantity:** (6) Required

**8** MAIN DRAIN DETAIL  
 SCALE: NOT TO SCALE


NOTE: CONTRACTOR SHALL PROVIDE AND INSTALL LINK SEALS FOR ALL PIPE PENETRATIONS THROUGH RESERVOIR TANK.

QUANTITY = (7)

LINK-SEAL® MODULAR SEALS WITH MCDL WS STEEL WALL SLEEVES



**9** CONCRETE WALL SLEEVE DETAIL  
 SCALE: NOT TO SCALE



**10** SPLASHPAD CONCRETE SLAB DETAIL  
 SCALE: NOT TO SCALE




Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS BY


DRAWN BY: MDC  
 CHECKED BY: PNG  
 DATE: 11/01/2021  
 SCALE: NTS  
 JOB No: 20-LD-025 / 061694.00  
 SHEET NUMBER

**SP-9**

100% CONSTRUCTION DOCUMENTS




**11** SPRAY FEATURE MANIFOLD INSTALLATION DETAIL  
SCALE: NOT TO SCALE




- NOTES:
- 1) PIPES RUNNING PARALLEL AND ABOVE OTHER PIPES ALLOWED ONLY UPON SPECIAL APPROVAL OF THE ENGINEER.
  - 2) PIPES SHALL BE SLOPED PER LOCAL CODES.

**12** PIPE TRENCHING DETAIL  
SCALE: NOT TO SCALE




**13** 1" BACKFLOW PREVENTER DETAIL  
SCALE: NOT TO SCALE



DIMENSIONS			PART #
PIPE SIZE	PLATE DIA.	BOLT SIZE	PVC PLATE
4"	12"	5/8"	AVPLATE4PVCKIT
6"	16"	5/8"	AVPLATE6PVCKIT

- NOTES:
1. PLATE DIA./HEIGHT MAY VARY DEPENDING ON REQUIRED SUCTION FLOW.
  2. A.V. PLATES SHALL BE SUPPLIED BY: NEPTUNE BENSON INC. OR APPROVED EQUAL.
  3. QUANTITY = (2) REQUIRED (1 @ 4" AND 1 @ 6")
  4. CONTRACTOR SHALL INSTALL PLATES WITH STAINLESS STEEL ALL THREAD AND S/S FASTENERS.



**14** ANTI-VORTEX COVER DETAIL  
SCALE: NOT TO SCALE



Project Title  
**PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338**

REVISIONS	BY

DRAWN BY: MDC  
 CHECKED BY: PNG  
 DATE: 11/01/2021  
 SCALE: NTS  
 JOB No: 20-LD-025 / 061694.00  
 SHEET NUMBER


**SP-10**

USER: 3530 - Nov 01, 2021 - 12:13pm  
 V:\Projects\ANY\5\061694\000\09\_Design-DWG\Drawings\01\_Sheets\SP-10\_061694.dwg - LAYOUT: 1 VERSION: LAND DEVELOPMENT-41352


100% CONSTRUCTION DOCUMENTS

SP-10\_061694.DWG

**Model Number:** W009  
**Shaft:** 4" type 304 stainless steel pipe.  
**Base Plate:** Type 304 stainless steel pipe.  
**Anchors:** (4) stainless steel concrete anchors, supplied.  
**Finish:** Textured elastomeric urethane with a UV and chlorine resistance sealer coat.  
**Color:** Select from Red, Light Blue, Yellow, Green, Dark Blue, Orange, or Purple.  
**Fasteners:** Tamper-resistant type 18/8 stainless steel.  
**Activator Housing:** Tactile push button machine from polymer materials  
**Activator Housing Color:** (Select from Red, Light Blue, Yellow, Green, Dark Blue, Orange, or Purple.)  
**Activator Cord:** 150' of 18/3 type SJTOW submersible cable pre-wired to activator button, supplied.  
**Quantity:** (1)  
**Foundation:** Foundation required for feature shall be coordinated and designed with manufacturer and included in bid price.



**15 SPLASHPAD ACTIVATION BOLLARD DETAIL**  
SCALE: NOT TO SCALE




**Model No:** DSC-8-12  
**Housing:** NEMA 4X with lockable hasp.  
**Input Voltage:** 120VAC/60 Hertz, 20 Amps.  
**Wired Inputs:** 8.  
**Output Voltage:** 24VAC/60 Hertz, .75 Amps continuous per output.  
**Outputs:** 12.  
**Power Cord:** 6 foot, 16-3 type SJT with grounded plug.  
**Cord Seals:** PVC compression seal fittings with neoprene gland for 16-2 solenoid valve cables.  
**Time Clock:** Integral, electronic, 7 day, 24 hour.  
**Interface:** Keypad with 20 keys and a 4 x 20 backlit LCD display.  
**Antenna/Receiver:** Enclosed in weather resistant PVC housing with 150 feet of CAT 5 crossover cable supplied.  
**Programmable Events:** Timed duration, cycled, defined, random, and cued sequencing, field adjustable.  
**Programming:** Through keyboard; set at factory and field adjustable.  
**Safety:** ETL and Underwriters' Laboratories Listed.  
**Quantity:** (1)

- Notes:
- Conduit and wire by installer.
  - Adding suffix -A to any of the units above will designate it as factory mounted and pre-wired on manifold assembly.
  - All field wiring to be compliant with NEC and local codes. Field output wire to be stranded copper, minimum rated 60°C

This device complies with Part 15 of the FCC Rules. Operation is subject to the following conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.


**16 SPLASHPAD CONTROLLER DETAIL**  
SCALE: NOT TO SCALE



**MAXIMUM TANK VOLUME:**  
 $V_{max} = (8' \times 8' \times 16') = 1,024 \text{ FT}^3$   
 $V_{max} = 7,660 \text{ GALLONS}$

- INITIAL FILL LEVELS:**
- SPRAYGROUND BALANCE TANK: FILL TANK TO 3,830 GALLONS (= 4'-0" WATER DEPTH)

LINK SEALS TO BE INSTALLED ON ALL PIPE PENETRATIONS THROUGH TANK WALL (SEE DETAIL)




QTY REQUIRED = (1)


**NOTES:**

- BALANCE TANKS TO BE A PRECAST STRUCTURE AND SHALL BE SUPPLIED BY OLD CASTLE PRECAST, OR EQUAL.
- CONCRETE MINIMUM COMPRESSIVE STRENGTH TO BE 5,000 PSI @ 28 DAYS.
- STEEL REINFORCEMENT REBAR SHALL BE ASTM 615, GRADE 60.
- DESIGN LOADING IS BASED ON AASHTO HS-20.
- EARTH COVER = 0'-0" - 5'-0" BASED ON WORST CASE SCENARIO.
- GROUND WATER ASSUMED WORST CASE SCENARIO @ 3'-0" BELOW GRADE.
- TANK STRUCTURE PRODUCED IN ACCORDANCE WITH NPCA CERTIFICATION BY OLD CASTLE PRECAST.
- ACCESS HATCH (1 PER TANK) SHALL BE INTEGRAL WITH THE TANK AND SHALL BE LOCKABLE. HATCH TO BE SYRACUSE MODEL CH-4AL (ALUMINUM) AND SHALL BE OSHA APPROVED.
- POOL CONTRACTOR MUST PROVIDE 2 COATS OF VANDEX SUPER WHITE WATERPROOFING TO INTERIOR SURFACE OF TANK. SEE SPECIFICATIONS FOR DETAILS.
- TANK IS TO BE SET LEVEL AND PLUMB IN ALL DIRECTIONS. CONTRACTOR SHALL PROVIDE AN 18" THICK LAYER OF CLEAN #1 & 2 STONE MIX SUB-BASE DIRECTLY UNDER TANK (SHOWN IN DETAIL). CONTRACTOR SHALL OVER-EXCAVATE TO ACCOUNT FOR SUB-BASE STONE FILL.


**17 SPLASHPAD RESERVOIR TANK DETAIL**  
SCALE: NOT TO SCALE




**RAIN DIVERTER EQUIPMENT PLAN VIEW**




**RAIN DIVERTER COMPONENT ID PLAN VIEW**




**EQUIPMENT COVER LEFT SIDE ELEVATION**




**EQUIPMENT COVER RIGHT SIDE ELEVATION**




**RAIN DIVERTER VAULT FRONT ELEVATION**





**RAIN DIVERTER VAULT SIDE ELEVATION**




**EQUIPMENT PLAN VIEW**



**RECIRC EQUIPMENT COMPONENTS ID PLAN VIEW**



**EQUIPMENT COMPONENTS ID FRONT VIEW**



**WASTE LINE AIR GAP DETAIL**

**ADDITIONAL NOTES:**

1. PLUMBING - ALL PIPE & FITTINGS SHALL BE SCHEDULE 80 PVC PER ASTM D1785 AND N.S.F. APPROVED AND STAMPED FOR POTABLE WATER APPLICATIONS. JOINTS TO BE SOLVENT WELDED PER ASTM D2855.
2. ELECTRICAL - ALL ELECTRICAL EQUIPMENT WIRING, INSTALLATION AND GROUNDING OF POOL COMPONENTS SHALL CONFORM TO NATIONAL FIRE PROTECTION ASSOC. 70, NATIONAL ELECTRICAL CODE (N.E.C.) LATEST EDITION AND ALL APPLICABLE LOCAL CODES. CHEMICAL FEED PUMPS SHALL BE INTERLOCKED WITH THE RECIRCULATION PUMP.
3. EQUIPMENT - ALL PUMPS, FILTERS AND DISINFECTION EQUIPMENT SHALL BE TESTED AND APPROVED BY THE PERTINENT MANUFACTURER USING THE NSF/ANSI STANDARD 50 AND LISTED AS APPROVED BY THE NSF.
4. THE FILTER ROOM FLOOR SHALL BE SLIP RESISTANT AND SLOPED TO FLOOR DRAINS.
5. ALL PLASTIC PIPING SUBJECT TO PROLONGED SUNLIGHT EXPOSURE MUST BE COATED TO PROTECT IT FROM ULTRAVIOLET LIGHT DEGRADATION.
6. EACH WASTE LINE SHALL HAVE A UNIQUE AIR GAP. WASTE LINES FROM DIFFERENT SOURCES SHALL NOT BE TIED TOGETHER BUT MAY DISCHARGE INTO A COMMON SUMP OR RECEPTACLE.
7. THE WASTE LINE MUST BE CONNECTED TO AN APPROVED WASTE DISPOSAL SYSTEM ACCORDING TO LOCAL OR STATE CODES.
8. COLLECTOR TANK SHALL HAVE LOCKABLE ACCESS HATCH. PIPE PENETRATIONS SHALL BE WATERTIGHT.
9. AN AUTOMATIC AND MANUAL WATER MAKEUP CONTROL SHALL BE PROVIDED TO MAINTAIN THE WATER LEVEL IN THE TANK RESERVOIR. WATER SOURCE SHALL BE PROTECTED BY AN APPROVED 1" RPZ FOR BACKFLOW PREVENTION.
10. A RATE OF FLOW INDICATOR, READING IN GPM, SHALL BE INSTALLED ON THE FILTER RETURN LINE. THE RATE OF FLOW INDICATOR SHALL BE PROPERLY SIZED FOR THE DESIGN FLOW RATE AND SHALL BE CAPABLE OF MEASURING FROM ONE HALF TO AT LEAST ONE-AND-ONE-HALF TIMES THE DESIGN FLOW RATE. THE CLEARANCES UPSTREAM AND DOWNSTREAM FROM THE RATE OF FLOW INDICATOR SHALL COMPLY WITH THE MANUFACTURER'S INSTALLATION SPECIFICATIONS.

EQUIPMENT LIST	
FEATURE PUMP	SPECK, 95X, 7.5 HP WITH INTEGRAL BASKET STRAINER, 267 GPM @ 60' TDH, 208-230V, 3Ø, 19.9A
RECIRC PUMP	SPECK, 95X, 7.5 HP WITH INTEGRAL BASKET STRAINER, 256 GPM @ 60' TDH, 208-230V, 3Ø, 19.9A
COLLECTOR TANK	PRE-CAST CONCRETE (SEE SEPARATE DETAIL)
FILTER ELEMENT (FEATURE)	(8) UNICELL C-7697, 105 SQ FT FILTER AREA EACH (304 GPM MAX)
WATER LEVEL CONTROL	AQUAWORX HYDRAULIC VALVE W/ MANUAL FILL VALVE, RESERVOIR
CHLORINE FEEDER	STENNER 43M5, 50 GPD CAPACITY, 110V
CHLORINE RESERVOIR TANK	65 GALLON WITH LOCKABLE LID
pH FEEDER	STENNER 43M2, 10 GPD CAPACITY, 110V
pH RESERVOIR TANK	30 GALLON WITH LOCKABLE LID
VACUUM GAUGE	WIKA, 0-30 IN HG, LIQUID FILLED, 1/4" NPT, 2" FACE DIAMETER
PRESSURE GAUGE	WIKA, 0-60 PSI, LIQUID FILLED, 1/4" NPT, 2" FACE DIAMETER
CHEMISTRY CONTROLLER	HAYWARD, CAT2000
SAND FILTER (RECIRC)	(2) TRITON, TR140, 7.09 SQ FT FILTER AREA EACH
IWF CONTROLLER	MCG, AQUAWORX FEATURE CONTROLLER
RECIRC FLOWMETER	3" BLUE/W-HITE F-30300P, 45 TO 240 GPM RANGE
MULTI-PORT VALVE (2)	PENTAIR 261050 HI FLOW
BACKWASH SIGHTGLASS (2)	HAYWARD SP1074S
FEATURE/RECIRC VFD	SPECK, VACCON VFD, 7.5 HP
RAIN DIVERTER MANIFOLD	AQUAWORX, 8" RAIN DIVERTER



Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**


REVISIONS	BY

DRAWN BY	MDC
CHECKED BY	PNG
DATE:	11/01/2021
SCALE:	NTS
JOB No.	20-LD-025 / 061694.00
SHEET NUMBER	

**SP-12**

100% CONSTRUCTION DOCUMENTS

USER: 3530 - Nov 01, 2021 - 12:17pm  
V:\Projects\11\115\061694.000\09\_Design-DWG\Drawings\01\_Sheets\SP-12\_061694.dwg - LAYOUT: 1 VERSION: LAND DEVELOPMENT-41352



**1** SPLASH PAD PIPING PLAN  
SCALE: 1/4" = 1'-0"

**PIPING NOTES**

1. CONTRACTOR SHALL PROVIDE AND INSTALL ALL SPLASH PAD PIPING AS SHOWN. SEE TRENCH DETAIL FOR INSTALLATION DETAILS / GUIDANCE.
2. ALL SPLASH PAD PIPING SHALL BE SCHEDULE 80 PVC OR APPROVED EQUAL.
3. CERTAIN SPLASH PAD EXPANSIONS JOINTS ARE PURPOSEFULLY HIDDEN FOR CLARITY. REFER TO PREVIOUS SHEETS FOR FULL EXPANSION JOINT LAYOUT.
4. SPLASH PAD PIPE JOINTS ARE TO BE GLUED CONNECTIONS. MECHANICAL CONNECTIONS WILL NOT BE ACCEPTED.
5. PIPING SHALL BE INSTALLED AT DEPTHS REQUIRED TO MAINTAIN SPLASH PAD'S OPERATION AND WINTERIZATION. PIPING SHALL BE PITCHED WHEN REQUIRED TO WINTERIZE THE LINES.
6. PIPE & PIPE FITTING MATERIALS SHALL BE MANUFACTURED BY SPEARS CORPORATION OR APPROVED EQUAL.
7. ELECTRICAL CONDUIT SHALL BE SCHEDULE 40 PVC OR APPROVED EQUAL.



USER: 3530 - Nov 01, 2021 - 12:20pm  
V:\Projects\ANY\5161694\000\09\_Design-DWG\Drawings\01\_Sheets\SP-13\_061694.dwg - LAYOUT: 1 VERSION: LAND DEVELOPMENT-41352



Project Title  
**PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338**


REVISIONS	BY

DRAWN BY: MDC  
CHECKED BY: PNG  
DATE: 11/01/2021  
SCALE: 1/4" = 1'-0"  
JOB No: 20-LD-025 / 061694.00  
SHEET NUMBER

**SP-13**

100% CONSTRUCTION DOCUMENTS

SP-13\_061694.DWG



**FIXTURE SCHEDULE:**

MARK	DESCRIPTION	VOLTAGE	MANUFACTURER & MODEL NO.
(A)	MAIN LUG BREAKER PANEL (12 CIRCUIT)	240V 1PH	SIEMENS, PW1224L3125CU
(B)	RECIRCULATION PUMP	240V 1 PH	SPECK, 95X, 7.5 HP
(C)	FEATURE PUMP	240V 1PH	SPECK, 95X, 7.5 HP
(D)	CHLORINE FEEDER PUMP	115V	STENNER 45M5
(E)	ACID FEEDER PUMP	115V	STENNER, 45M2
(F)	CHEMICAL CONTROLLER	115V	HAYWARD CAT 2000
(G)	100 WATT SERVICE LIGHT FIXTURE	115V	INTERMATIC, VPXG11GCI 100W
(H)	GFCI DUPLEX RECEPTACLE	115V	PASS & SEYMOUR
(I)	ELECTRICAL INTERLOCK	115/208-230V	MCG, 40A DEFINITE PURPOSE CONTACTOR
(J)	FEATURE CONTROLLER	115/208-230V	WATER ODYSSEY FEATURE CONTROLLER
(K)	ACTIVATION BOLLARD	12/24/115V	WATER ODYSSEY FEATURE ACTIVATOR

**FEEDER & CIRCUIT SCHEDULE:**

MARK	CONDUCTORS			CONDUIT	REMARKS
	PHASE	NEUTRAL	GROUND		
△1					PANEL FEED
△2	3 -#8		1 - #8	1"	UL SEALTITE
△3	3 -#8		1 - #8	1"	UL SEALTITE
△4	1 -#12	1 - #12	1 - #12	1/2"	SEALTITE TO PANEL
△5	1 -#12	1 - #12	1 - #12	1/2"	SEALTITE TO PANEL
△6	1 -#12	1 - #12	1 - #12	1/2"	SEALTITE TO PANEL
△7	2 -#18	1 - #18	1 - #18	1/2"	SEALTITE TO PANEL
△8	CONDUCTORS AND CONDUIT INSTALLED BY OTHERS				

**PANEL SCHEDULE:**

3-PHASE, 4-WIRE — 208Y/120 VAC OR 240 VAC INSULATED/BONDABLE NEUTRAL CURRENT WITHSTAND RATING MAX. RMS. SYM. 10,000A 12/240V				
CIRCUIT	POLE	TRIP	LOAD	AMPS
1-3	3	40A GFI	REC. PUMP W/INTERLOCKED CHEMICALS	23.3
4-6	3	40A GFI	FEATURE PUMP	19.9
7	1	20A	GFCI	3.0
8	1	20A	SERVICE LIGHT	1.5
9	1	20A	FEATURE CONTROLLER	1.1
10-12			SPARE	
<b>TOTAL MAXIMUM LOAD</b>				<b>48.8</b>

# 12'X12' PAVILION DETAILS

**GENERAL NOTES:**

UNLESS NOTED OTHERWISE, THIS STRUCTURE WAS DESIGNED TO ONLY SUPPORT WHAT IS SHOWN ON THESE DRAWINGS. MFG MUST BE CONTACTED IF ANYTHING ELSE IS TO BE ATTACHED TO THIS STRUCTURE (WALLS, COLUMN WRAPS, RAILINGS, ETC.) SO THE DESIGN OF THIS STRUCTURE CAN BE REVIEWED AND POSSIBLY REVISED.

UNLESS NOTED OTHERWISE, THIS STRUCTURE WAS DESIGNED ASSUMING A 20' SEPARATION BETWEEN ANY ADJACENT STRUCTURE WITH AN EAVE HEIGHT EQUAL TO OR GREATER THAN THE EAVE HEIGHT OF THIS STRUCTURE. IF THAT SEPARATION DOES NOT EXIST, SRP MUST BE CONTACTED SO THE DESIGN OF THIS STRUCTURE CAN BE REVIEWED AND POSSIBLY REVISED.

STRUCTURAL STEEL SHALL BE DETAILED, FABRICATED, AND ERECTED IN ACCORDANCE WITH THE LATEST EDITION OF THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC) SPECIFICATION MANUAL.

SHELTER MANUFACTURER SHALL BE RESPONSIBLE TO PROVIDE A COMPLETE SHELTER INCLUDING BUT NOT LIMITED TO:

- ALL STRUCTURAL COMPONENTS
- ALL FINISHES
- ALL FOUNDATIONS
- SIGNED & SEALED DESIGN CALCULATIONS SIGNED BY AN ENGINEER LICENSED IN THE STATE OF CONSTRUCTION.

**MATERIALS:**


DESCRIPTION	ASTM DESIGNATION
TUBE STEEL	A500 (GRADE B)
SCHEDULE PIPE	A53 (GRADE B)
RMT PIPE	A519
LIGHT GAGE COLD FORMED	A1003 (GRADE 50)
STRUCTURAL STEEL PLATE	A36
ROOF PANELS (STEEL)	A653

ALL WELDING IS PERFORMED BY AMERICAN WELDING SOCIETY CERTIFIED WELDERS AND CONFORMS TO THE LATEST EDITION OF AWS D1.1 OR D1.3 AS REQUIRED.


PARTS SHOWN MAY BE UPGRADED DUE TO STANDARDIZED FABRICATION. REFER TO THE SHIPPING BILL OF MATERIALS FOR POSSIBLE SUBSTITUTIONS.

FOR PROPER FIELD INSTALLATION OF THE BUILDING IT IS RECOMMENDED THAT THE PRIMARY FRAME INSTALLER AND THE ROOF INSTALLER HAVE A MINIMUM FIVE (5) YEARS DOCUMENTED EXPERIENCE INSTALLING THIS TYPE OF PRODUCT.

FOR PROPER FIELD INSTALLATION OF THE BUILDING IT IS RECOMMENDED THAT ELECTRIC WIRING, IF REQUIRED, BE RUN THROUGH THE STRUCTURAL MEMBERS BEFORE THE BUILDING IS ERECTED.




3 12'-0" X 12'-0" STRUCTURAL & FRAMING PLAN  
A1 SCALE: N.T.S.



- GENERAL ROOF NOTES:**
1. METAL ROOFING:
    - 24 GAUGE
    - GALVALUME COATED
    - KYNAR 500 PAINTED
  2. TRIM COLOR MATCHES ROOF

1 12'-0" X 12'-0" PLAN & ELEVATION  
A1 SCALE: N.T.S.



- BASEPLATE NOTES:**
1. MFG ENGINEERING WILL DETERMINE REQUIRED BASEPLATE DESIGN AFTER ENGINEERING PACKAGE IS ORDERED.
  2. CUSTOMER MAY SUGGEST PREFERRED BASEPLATE DESIGN.

2 12'-0" X 12'-0" COLUMN PLAN  
A1 SCALE: N.T.S.



Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY: RS/AM  
 CHECKED BY: KRA  
 DATE: 11/01/2021  
 SCALE: NTS  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

A-1



# 30'X30' PAVILION DETAILS

**GENERAL NOTES:**

UNLESS NOTED OTHERWISE, THIS STRUCTURE WAS DESIGNED TO ONLY SUPPORT WHAT IS SHOWN ON THESE DRAWINGS. MFG MUST BE CONTACTED IF ANYTHING ELSE IS TO BE ATTACHED TO THIS STRUCTURE (WALLS, COLUMN WRAPS, RAILINGS, ETC.) SO THE DESIGN OF THIS STRUCTURE CAN BE REVIEWED AND POSSIBLY REVISED.

UNLESS NOTED OTHERWISE, THIS STRUCTURE WAS DESIGNED ASSUMING A 20' SEPARATION BETWEEN ANY ADJACENT STRUCTURE WITH AN EAVE HEIGHT EQUAL TO OR GREATER THAN THE EAVE HEIGHT OF THIS STRUCTURE. IF THAT SEPARATION DOES NOT EXIST, SRP MUST BE CONTACTED SO THE DESIGN OF THIS STRUCTURE CAN BE REVIEWED AND POSSIBLY REVISED.

STRUCTURAL STEEL SHALL BE DETAILED, FABRICATED, AND ERECTED IN ACCORDANCE WITH THE LATEST EDITION OF THE AMERICAN INSTITUTE OF STEEL CONSTRUCTION (AISC) SPECIFICATION MANUAL.

SHELTER MANUFACTURER SHALL BE RESPONSIBLE TO PROVIDE A COMPLETE SHELTER INCLUDING BUT NOT LIMITED TO:

- ALL STRUCTURAL COMPONENTS
- ALL FINISHES
- ALL FOUNDATIONS
- SIGNED & SEALED DESIGN CALCULATIONS SIGNED BY AN ENGINEER LICENSED IN THE STATE OF CONSTRUCTION.

**MATERIALS:**


DESCRIPTION	ASTM DESIGNATION
TUBE STEEL	A500 (GRADE B)
SCHEDULE PIPE	A53 (GRADE B)
RMT PIPE	A519
LIGHT GAGE COLD FORMED	A1003 (GRADE 50)
STRUCTURAL STEEL PLATE	A36
ROOF PANELS (STEEL)	A653

ALL WELDING IS PERFORMED BY AMERICAN WELDING SOCIETY CERTIFIED WELDERS AND CONFORMS TO THE LATEST EDITION OF AWS D1.1 OR D1.3 AS REQUIRED.


PARTS SHOWN MAY BE UPGRADED DUE TO STANDARDIZED FABRICATION. REFER TO THE SHIPPING BILL OF MATERIALS FOR POSSIBLE SUBSTITUTIONS.

FOR PROPER FIELD INSTALLATION OF THE BUILDING IT IS RECOMMENDED THAT THE PRIMARY FRAME INSTALLER AND THE ROOF INSTALLER HAVE A MINIMUM FIVE (5) YEARS DOCUMENTED EXPERIENCE INSTALLING THIS TYPE OF PRODUCT.

FOR PROPER FIELD INSTALLATION OF THE BUILDING IT IS RECOMMENDED THAT ELECTRIC WIRING, IF REQUIRED, BE RUN THROUGH THE STRUCTURAL MEMBERS BEFORE THE BUILDING IS ERECTED.




3 30'-0" X 30'-0" STRUCTURAL & FRAMING PLAN  
SCALE: N.T.S.



- GENERAL ROOF NOTES:**
1. METAL ROOFING:
    - 24 GAUGE
    - GALVALUME COATED
    - KYNAR 500 PAINTED
  2. TRIM COLOR MATCHES ROOF

1 30'-0" X 30'-0" PLAN & ELEVATION  
SCALE: N.T.S.



2 30'-0" X 30'-0" COLUMN PLAN  
SCALE: N.T.S.




Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS	BY


DRAWN BY: RS/AM  
 CHECKED BY: KRA  
 DATE: 11/01/2021  
 SCALE: NTS  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

A-2



1 RESTROOM FLOOR PLAN  
 A3 SCALE: 1" = 1'-0"  
 0 1/2 1 2

BASIS OF DESIGN:  
 DENALI PRECAST RESTROOM  
 BY CXT PRECAST PRODUCTS




Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS	BY


DRAWN BY RS/AM  
 CHECKED BY KRA  
 DATE: 11/01/2021  
 SCALE: 1"=1'-0"  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

A-3


100% CONSTRUCTION DOCUMENTS




FRONT ELEVATION



RIGHT SIDE ELEVATION



REAR ELEVATION



LEFT SIDE ELEVATION

1 RESTROOM ELEVATIONS  
A4 SCALE: 1/2" = 1'-0"  
0 1 2 4

BASIS OF DESIGN:  
DENALI PRECAST RESTROOM  
BY CXT PRECAST PRODUCTS







Project Title  
PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY RS/AM  
CHECKED BY KRA  
DATE: 11/01/2021  
SCALE: 1/2" = 1'-0"  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER

A-4

100% CONSTRUCTION DOCUMENTS



1 RESTROOM SECTIONS  
 A5 SCALE: 1" = 1'-0"  
 0 1/2 1 2

BASIS OF DESIGN:  
 DENALI PRECAST RESTROOM  
 BY CXT PRECAST PRODUCTS



Project Title  
 PERIMETER CENTER EAST PARK  
 CITY OF DUNWOODY, GEORGIA  
 4800 ASHFORD DUNWOOD RD  
 DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY RS/AM  
 CHECKED BY KRA  
 DATE: 11/01/2021  
 SCALE: 1/2"=1'-0"  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

A-5


100% CONSTRUCTION DOCUMENTS




**BASIS OF DESIGN:**

1. Standing Seam Roof - Englert Series A1000, Galvalume standing seam roof, 22 gauge
2. James Hardie vertical siding, trim boards, and batten boards; smooth face primed and ready to be painted
3. Stone Veneer Base - Sandstone Mosaic Whispering Pine Fieldstone Full 4" Stone Veneer as Manufactured by Buechel Or Equal.
4. Stone Base Cap - Match the base stone veneer, form sloping cap, trim as required for 1" overhang
5. Paint colors: Sherwin Williams; All color selections to be selected by Architect approved by Owner including but not limited to:


- Door & Door Frame
- Board & Batten Wall Siding
- Corners, Vented Soffits, Fascia, Horizontal & Vertical Trim
- Aluminum Louvers




**FRONT ELEVATION**



**SIDE ELEVATION**




**REAR ELEVATION**




**SIDE ELEVATION**


**2 BUILDING ELEVATIONS**  
SCALE: 3" = 1'-0"  
0 3' 6' 9'



**1 WALL SECTION**  
SCALE: 3/4" = 1'-0"  
0 1' 2' 3'



**3 HEAD DETAIL**  
SCALE: 3" = 1'-0"  
0 3' 6' 9'









**4 JAMB DETAIL**  
SCALE: 3" = 1'-0"  
0 3' 6' 9'



REVISIONS	BY

DRAWN BY: **KRA**  
CHECKED BY: **KRA**  
DATE: **11/01/2021**  
SCALE: **VARIES**  
JOB No. **20-LD-025 / 061694.00**  
SHEET NUMBER

ABBREVIATIONS		
A	AMPERE	HPS HIGH PRESSURE SODIUM
AC	ALTERNATING CURRENT	HTR HEATER
AF	AMPERE FRAME	HV HIGH VOLTAGE
AFF/G	ABOVE FINISHED FLOOR/GRADE	HW HOT WATER
AIC	AMPERE INTERRUPTING CAPACITY	ID IDENTIFY, IDENTIFICATION
AT	AMPERE TRIP	INCAND INCANDESCENT
AUX	AUXILIARY	J-BOX JUNCTION BOX
A/V	AUDIBLE/VISUAL	J.C. JANITOR CLOSET
AWG	AMERICAN WIRE GAUGE	JCT JUNCTION
BB	BACKBOARD	JCM/Kcmil THOUSAND CIRCULAR MILS
BCW	BARE COPPER WIRE	KVA KILO VOLT AMPERE
BATT	BATTERY	KW KILOWATT
BTM	BOTTOM	LGT LIGHTING
BKR	BREAKER	LIT(S) LIGHT(S)
BLDG	BUILDING	LED LIGHT EMITTING DIODE
C	CONDUIT	L LOUVER
CAB	CABINET	MAX MAXIMUM
CATV	COMMUNITY ACCESS TELEVISION (CABLE TELEVISION)	MCB MAIN CIRCUIT BREAKER
CB	CIRCUIT BREAKER	MC METAL CLAD CABLE
CIR	CIRCUIT	MFR MANUFACTURER
CKT	CIRCUIT	MH METAL HALIDE
C	CENTER LINE	MECH MECHANICAL
CO	COMPANY	MIN MINIMUM
COMM	COMMUNICATIONS	ML MOTORIZED LOUVER
CONN	CONNECTION, CONNECT	MLO MAIN LUGS ONLY
CJH	CABINET UNIT HEATER	MT MOUNT
CT	CURRENT TRANSFORMER	MTD MOUNTED
CU	COPPER	MTR MOTOR
CWA	CONSTANT WATTAGE AUTOTRANSFORMER	N NORTH
Δ	DELTA CONNECTION	NEC NATIONAL ELECTRICAL CODE
D	DEEP	NF NON-FUSED
DB	DECIBEL	NL NIGHT LIGHT
DET	DETECTOR	No/# NUMBER
DIA	DIAMETER	OC OVER COUNTER
DISC	DISCONNECT	OL OVERLOAD
DIST	DISTRIBUTION	P POLE(S)
DIV	DIVISION	PA PUBLIC ADDRESS
DN	DOWN	PNL PANEL
DWG	DRAWING	PR PAIR
EA	EACH	PRI PRIMARY
EBH	ELECTRIC BASEBOARD HEATER	PWR POWER
EF	EXHAUST FAN	φ PHASE
EL	ELEVATION	PT PRESSURE TREATED
ELEC	ELECTRIC(AL)	RECEPT RECEPTACLE
EMER	EMERGENCY	RGS RIGID GALVANIZED STEEL
ENCL	ENCLOSURE	RM ROOM
EQUIP	EQUIPMENT	SEC SECONDARY
EWC	ELECTRIC WATER COOLER	SH SHIELDED
EXT	EXTERIOR	SPKR SPEAKER
F	FUSE(D)	SW SWITCH
FA	FIRE ALARM	TEMP TEMPORARY/TEMPERATURE
FACP	FIRE ALARM CONTROL PANEL	T-STAT THERMOSTAT
FC	FOOTCANDLES	TB TERMINAL BOARD
FIXT	FIXTURE	TYP TYPICAL
FLR	FLOOR	UH UNIT HEATER
FLUOR	FLUORESCENT	UON UNLESS OTHERWISE NOTED
FT	FOOT (FEET)	V VOLT, VOLTS
FUT	FUTURE	VA VOLT-AMPERES
G, GND	GROUND	W WATT, WIRE
GALV	GALVANIZE(D)	W/ WITH
GC	GENERAL CONTRACTOR	WP WEATHERPROOF
GFI	GROUND FAULT CIRCUIT INTERRUPTER	XFMR/T TRANSFORMER
GFP	GROUND FAULT PROTECTION	Y WYE CONNECTION
HD	HEAVY DUTY	
HGT	HEIGHT	
HID	HIGH INTENSITY DISCHARGE	
HO	HIGH OUTPUT	
HOA	HAND-OFF-AUTOMATIC	
HP	HORSEPOWER	
HPF	HIGH POWER FACTOR	



- GENERAL NOTES**
- REFER TO CIVIL, STRUCTURAL, ARCHITECTURAL, MECHANICAL, PLUMBING AND AQUATICS DRAWINGS FOR SYMBOLS ASSOCIATED WITH WORK, EQUIPMENT, ETC. BY OTHER(S).
  - ALL WORK SHOWN ON THE ELECTRICAL DRAWINGS SHALL BE BY THE ELECTRICAL CONTRACT UNLESS OTHERWISE INDICATED.
  - COORDINATE WORK WITH ALL TRADES.
  - CONDUIT RUNS SHOWN ARE DIAGRAMMATIC UON. EXACT LOCATION OF ALL CONDUIT RUNS SHALL BE DETERMINED IN THE FIELD. COORDINATE INSTALLATIONS AND AVOID CONFLICT WITH PIPING, DUCTWORK, ACCESS DOORS AND WORK BY OTHER TRADES.
  - GENERAL NOTES APPLY TO ALL ELECTRICAL CONTRACT DRAWINGS.




Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**


REVISIONS	BY

DRAWN BY: KML  
 CHECKED BY: JJD  
 DATE: 11/01/2021  
 SCALE: AS SHOWN  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

100% CONSTRUCTION DOCUMENTS



1 OVERALL ELECTRICAL SITE PLAN  
 1" = 30'-0"




REVISIONS	BY


DRAWN BY: KML  
 CHECKED BY: JJD  
 DATE: 11/01/2021  
 SCALE: AS SHOWN  
 JOB No. 20-LD-025 / 061694.00  
 SHEET NUMBER

100% CONSTRUCTION DOCUMENTS








**1** ELECTRICAL PARTIAL SITE PLAN  
- 1" = 30'-0"



**2** ELECTRICAL PARTIAL SITE PLAN  
- 1" = 30'-0"

**CODED NOTES**

- ① PROVIDE (2)#10, (1)#10G FROM PANEL 'LV-1' TO PAVILION RECEPTACLES.
- ② PROVIDE (3)#1, (1)#8G FROM PANEL 'LV-1' TO RESTROOM PANEL.
- ③ PROVIDE EMPTY 4" CONDUIT FOR UTILITY PROVIDED TRANSFORMER PRIMARY CABLES FROM UTILITY TRANSFORMER TO UTILITY TIE-IN POINT.
- ④ PROVIDE EMPTY 4" CONDUIT FROM UTILITY TRANSFORMER TO CT CABINET/METER FOR UTILITY PROVIDED CONDUCTORS.
- ⑤ PROVIDE 1"C, (2)#10, (1)#10G FROM LIGHTING CONTACTOR PANEL LC-1 TO PARKING LOT L1 LIGHT FIXTURES.
- ⑥ PROVIDE 1"C, (2)#10, (1)#10G FROM LIGHTING CONTACTOR PANEL LC-1 TO LARGE PAVILION L2 LIGHT FIXTURES.
- ⑦ PROVIDE 1"C, (2)#10, (1)#10G FROM LIGHTING CONTACTOR PANEL LC-1 TO SMALL PAVILION L2 LIGHT FIXTURES.
- ⑧ MOUNT LIGHT FIXTURE TO CEILING BEAM.




Project Title  
**PERIMETER CENTER EAST PARK**  
**CITY OF DUNWOODY, GEORGIA**  
**4800 ASHFORD DUNWOOD RD**  
**DUNWOODY, GA 30338**


REVISIONS	BY

DRAWN BY: **KML**  
 CHECKED BY: **JJD**  
 DATE: **11/01/2021**  
 SCALE: **AS SHOWN**  
 JOB No. **20-LD-025 / 061694.00**  
 SHEET NUMBER

100% CONSTRUCTION DOCUMENTS





**1 POWER PLAN - PUMP HOUSE**  
 - 1/4" = 1'-0"



**2 LIGHTING PLAN - PUMP HOUSE**  
 - 1/4" = 1'-0"


**CODED NOTES**

- ① PROVIDE CONDUIT AND WIRING. SEE ONE-LINE DIAGRAM ON SHEET E-5 FOR QUANTITIES AND SIZES.
- ② PROVIDE (1) SOLID #8 BARE COPPER CONDUCTOR TO EACH SPLASHPAD FEATURE, DRAIN AND TO ACTIVATOR BUTTON. SEE DRAWING SP-2 FOR EXACT LOCATIONS AND QUANTITIES.
- ③ PROVIDE CONTROL WIRING FROM WATERPLAY CONTROL PANEL TO ACTIVATOR BUTTON. SEE ONE-LINE DIAGRAM ON SHEET E-5 FOR QUANTITIES AND SIZES. SEE DRAWING SP-2 FOR EXACT LOCATION OF ACTIVATOR BUTTON.
- ④ PROVIDE CONDUIT AND WIRING FROM WATERPLAY CONTROL PANEL TO EACH OF THE MANIFOLD VALVES. SEE ONE-LINE DIAGRAM ON SHEET E-5 FOR QUANTITIES AND SIZES.
- ⑤ PROVIDE (1) SOLID #8 BARE COPPER CONDUCTOR. BOND TO DIVERTER & STRAINER SYSTEM.
- ⑥ PROVIDE 10', COPPER CLAD, 5/8" MIN. DRIVEN GROUND ROD.
- ⑦ PROVIDE (1) SOLID #4 BARE COPPER CONDUCTOR TO GROUND BAR.
- ⑧ PROVIDE (1) SOLID #4 BARE COPPER CONDUCTOR. BOND TO BUILDING REBAR.
- ⑨ PROVIDE (1) SOLID #8 BARE COPPER CONDUCTOR. BOND TO PUMP.
- ⑩ PROVIDE (1) SOLID #8 BARE COPPER CONDUCTOR. BOND TO RESERVOIR TANK.
- ⑪ PROVIDE (1) SOLID #4 BARE COPPER CONDUCTOR. BOND TO PANEL LV-1.
- ⑫ PROVIDE CONDUIT AND WIRING FROM WATERPLAY CONTROL PANEL TO DIVERTER & STRAINER SYSTEM. SEE ONE-LINE DIAGRAM ON SHEET E-5 FOR QUANTITIES AND SIZES.



REVISIONS	BY

DRAWN BY	KML
CHECKED BY	JJD
DATE:	11/01/2021
SCALE:	AS SHOWN
JOB No.	20-LD-025 / 061694.00
SHEET NUMBER	




1 ONE-LINE DIAGRAM  
- NOT TO SCALE

LOCATION: PUMP HOUSE		PANEL ID		VOLTS, PHASE, WIRE: 120/240V, 1 $\phi$ , 3W			
MOUNTING: SURFACE		LV-1		MAINS: 250A MCB			
SOURCE: UTILITY TRANSFORMER				SHORT CIRCUIT RATING: 22KAIC			
CKT	LOAD DESCRIPTION	CB AMPS/POLE	CONN LOAD KVA	CONN LOAD KVA	CB AMPS/POLE	LOAD DESCRIPTION	CKT
1	SMALL PAVILION RECEPITS	20/1	0.32	0.32	20/1	LARGE PAVILION RECEPITS	2
3	PARKING LOT LIGHT FIXTURES	20/2	0.22	8.86	125/2	AQUAWORX PANELBOARD	4
5				8.86			6
7	SMALL PAVILION LIGHT FIXTURES	20/2	0.04	0.04	20/2	LARGE PAVILION LIGHT FIXTURES	8
9				0.04			10
11	LIGHTING CONTROLS	20/1	0.10	0.08	20/2	LIGHTING PUMP HOUSE	12
13	PUMP HOUSE RECEPITS	20/1	0.72	0.08			14
15	PROVISIONED SPACE					PROVISIONED SPACE	16
17	PROVISIONED SPACE					PROVISIONED SPACE	18
19	PROVISIONED SPACE					PROVISIONED SPACE	20
21	PROVISIONED SPACE					PROVISIONED SPACE	22
23	PROVISIONED SPACE					PROVISIONED SPACE	24
25	PROVISIONED SPACE					PROVISIONED SPACE	26
27	PROVISIONED SPACE					PROVISIONED SPACE	28
29	PROVISIONED SPACE					PROVISIONED SPACE	30
31	PROVISIONED SPACE					PROVISIONED SPACE	32
33	PROVISIONED SPACE				20/1	SPARE	34
35	PROVISIONED SPACE				20/1	SPARE	36
37	SPARE	20/1			20/1	SPARE	38
39	SPARE	20/1		9.60		RESTROOM PANELBOARD	40
41	SPARE	20/1		9.60	100/2		42
NOTES:				1.30	0.36	18.90	18.58
1. SERVICE ENTRANCE RATED PANELBOARD.				TOTAL KVA			
				39.14			

TAG	DESCRIPTION	MOUNTING	LAMP(S)	VOLTS	MANUFACTURER & CATALOG NUMBER	COMMENTS
L1	POLE MOUNTED, LED LIGHT FIXTURE	POLE MOUNTED, 20'	LED, 54W	240V	LITHONIA LIGHTING CATALOG #: DSX1-LED-P1-40K-T4M-MVOLT-SPA	PROVIDE 20' SQUARE POLE.
L2	SURFACE MOUNTED, STRIP LED FIXTURE, SEALED AND GASKETED, 6000 LUMEN OUTPUT, 4000K COLOR TEMPERATURE, 80CRI	SURFACE MOUNTED	LED, 37.8W	240V	LITHONIA LIGHTING CATALOG #: FEM-L48-6000LM-IMAFL-MD-MVOLT-40K-80CRI	



6745 Sugarloaf Parkway, Suite 100  
Duluth, GA 30097  
770.447.8999 · www.chacompanies.com



11/1/2021


Project Title  
PERIMETER CENTER EAST PARK  
CITY OF DUNWOODY, GEORGIA  
4800 ASHFORD DUNWOOD RD  
DUNWOODY, GA 30338

REVISIONS	BY

DRAWN BY: KML  
CHECKED BY: JJD  
DATE: 11/01/2021  
SCALE: AS SHOWN  
JOB No. 20-LD-025 / 061694.00  
SHEET NUMBER

E-5

100% CONSTRUCTION DOCUMENTS




**CODED NOTES**

- ① PRE-CAST REINFORCED CONCRETE BASE.
- ② ANCHOR BOLTS. SIZE AS RECOMMENDED BY MANUFACTURER.
- ③ 10'-0" RIGID STEEL CONDUIT, ENTERING AND LEAVING BASE.
- ④ ADAPTER AS REQUIRED FOR CONDUIT SPECIFIED.
- ⑤ RIGID STEEL CONDUIT AND ELBOWS CAST IN CONCRETE.
- ⑥ #3 REBAR SPACED 12" ON CENTER HORIZONTALLY AND (4)#8 REBAR VERTICALLY.
- ⑦ POLEBASE COVER SIMILAR TO WHATLEY#BC-105 COLOR TO MATCH POLE.
- ⑧ 1/2" x 45° CHAMFER

**GENERAL NOTES**

1. PROVIDE FUSE HOLDERS IN EACH POLE BASE. FUSE HOLDERS SHALL BE IN-LINE TYPE, ONE-POLE AS MANUFACTURED BY LITTLEFUSE. FUSES SHALL BE KTK-R TYPE.


**1 LIGHT POLE BASE**  
- NOT TO SCALE



**NOTE:**

1. REPLACE EXISTING SURFACE CONDITIONS IN KIND TO INCLUDE, BUT NOT LIMITED TO: CONCRETE, CRUSHED STONE, SELECT GRAVEL, ASPHALT, TOPSOIL AND GRASS


**2 UNDERGROUND CONDUIT**  
- NOT TO SCALE



**NOTES**

1. SIZE HANDHOLE AT EACH LOCATION PER NEC. MINIMUM SIZE SHALL BE 18" X 18" X 24".
2. PROVIDE ALL CONDUITS WITH A PULL ROPE.
3. REPLACE EXISTING SURFACE CONDITIONS IN KIND TO INCLUDE, BUT NOT LIMITED TO: CONCRETE, CRUSHED STONE, SELECT GRAVEL, ASPHALT CONCRETE, TOPSOIL AND GRASS.


**3 HANDHOLE - DETAIL**  
- NOT TO SCALE



**CODED NOTES**

- ① MOUNT PHOTOCELL ON NORTH SIDE OF PUMP HOUSE BUILDING. MOUNT AWAY FROM NEARBY LIGHT SOURCES.
- ② PROVIDE 6P LIGHTING CONTACTOR.

**4 LIGHTING CONTROLS - DETAIL**  
- NOT TO SCALE



**CODED NOTES**

- ① COPPER GROUND BAR, 1/4" X 4" X 20", ERICO #EGBA14420CC. HOLE CENTERS TO MATCH NEMA DOUBLE LUG CONFIGURATION.
- ② INSULATORS, NEWTON INSTRUMENT CAT. NO. 3061-4
- ③ 5/8" LOCKWASHERS, NEWTON INSTRUMENT CO. CAT. NO. 3015-8
- ④ WALL MOUNTING BRACKET, NEWTON INSTRUMENT CO.
- ⑤ 5/8-11 X 1" H.H.C.S.BOLTS, NEWTON INSTRUMENT CO. CAT NO. 3012-1

**5 GROUND BAR**  
- NOT TO SCALE

REVISIONS	BY

DRAWN BY	KML
CHECKED BY	JJD
DATE:	11/01/2021
SCALE:	AS SHOWN
JOB No.	20-LD-025 / 061694.00
SHEET NUMBER	